

Package ‘jlme’

September 17, 2024

Title Regression Modelling with 'GLM.jl' and 'MixedModels.jl' in 'Julia'

Version 0.3.0

Description Bindings to 'Julia' packages 'GLM.jl' <[doi:10.5281/zenodo.3376013](https://doi.org/10.5281/zenodo.3376013)> and 'MixedModels.jl' <[doi:10.5281/zenodo.12575371](https://doi.org/10.5281/zenodo.12575371)>, powered by 'JuliaConnector'. Fits (generalized) linear (mixed-effects) regression models in 'Julia' using familiar model fitting syntax from R. Offers 'broom'-style data frame summary functionalities for 'Julia' regression models.

License MIT + file LICENSE

URL <https://yjunechoe.github.io/jlme/>,
<https://github.com/yjunechoe/jlme/>

BugReports <https://github.com/yjunechoe/jlme/issues/>

Depends R (>= 4.1)

Imports generics, JuliaConnector, JuliaFormulae, MASS, stats, utils

Suggests broom, broom.mixed, lme4, testthat (>= 3.0.0)

Config/testthat/edition 3

Encoding UTF-8

RoxygenNote 7.3.2

SystemRequirements Julia (>= 1.8)

NeedsCompilation no

Author June Choe [aut, cre] (<<https://orcid.org/0000-0002-0701-921X>>)

Maintainer June Choe <jchoe001@gmail.com>

Repository CRAN

Date/Publication 2024-09-17 19:10:02 UTC

Contents

check_julia_ok	2
jlme	3
jlme-model-helpers	4
parametricbootstrap	5
tidy.jlmeboot	6
Index	7

check_julia_ok	<i>Set up Julia connection for jlme</i>
----------------	---

Description

Set up Julia connection for jlme

Usage

```
check_julia_ok()

stop_julia()

jlme_status()

jlme_setup(
  ...,
  add = NULL,
  restart = FALSE,
  threads = NULL,
  verbose = interactive()
)
```

Arguments

...	Unused
add	A character vector of additional Julia packages to add and load.
restart	Whether to run stop_julia() first, before attempting setup
threads	Number of threads to start Julia with. Defaults to 1
verbose	Whether to alert setup progress. Defaults to interactive()

Value

Invisibly returns TRUE on success

Examples

```

# Check whether Julia installation meets requirements
check_julia_ok()

# Connect to a Julia runtime for use with `{jlme}`
jlme_setup()

# Show information about the Julia runtime
jlme_status()

# Stop Julia runtime
stop_julia()

```

jlm

Fit a (mixed-effects) regression model in Julia

Description

Fit a (mixed-effects) regression model in Julia

Usage

```

jlm(formula, data, family = "gaussian", contrasts = jl_contrasts(data), ...)

jlmer(
  formula,
  data,
  family = NULL,
  contrasts = jl_contrasts(data),
  ...,
  progress = interactive()
)

```

Arguments

formula	A formula written in Julia syntax. Can be a string or a language object.
data	A data frame
family	A distribution family
contrasts	A Julia dictionary of contrasts Inferred from data by default.
...	Additional arguments to the <code>fit()</code> function called in Julia
progress	Whether to print model fitting progress. Defaults to <code>interactive()</code>

Value

A julia model object of class jlme

Examples

```
jlme_setup(restart = TRUE)

# Fixed effects models
lm(mpg ~ hp, mtcars)
jlm(mpg ~ hp, mtcars)

# Auto-handling of contrasts
x <- mtcars
x$cyl_helm <- factor(x$cyl)
contrasts(x$cyl_helm) <- contr.helmert(3)
colnames(contrasts(x$cyl_helm)) <- c("4vs6", "4&6vs8")
lm(mpg ~ cyl_helm, x)
jlm(mpg ~ cyl_helm, x)

# Mixed effects models
library(lme4)

glmer(r2 ~ Anger + Gender + (1 | id), VerbAgg, family = "binomial")
jlmer(r2 ~ Anger + Gender + (1 | id), VerbAgg, family = "binomial")

stop_julia()
```

jlme-model-helpers *Helpers for interacting with Julia model objects and functions*

Description

Helpers for interacting with Julia model objects and functions

Usage

```
propertynames(x)
```

```
issingular(x)
```

Arguments

x Julia model object

Value

An appropriate R object

Examples

```

jlme_setup(restart = TRUE)

x <- jlmer(r2 ~ Anger + (1 | id), lme4::VerbAgg, family = "binomial")

# `propertynames()` lists properties accessible via `$`
propertynames(x)

# `issingular()` reports whether model has singular fit
issingular(x)

stop_julia()

```

parametricbootstrap *Parametric bootstrap for Julia mixed effects models*

Description

Parametric bootstrap for Julia mixed effects models

Usage

```

parametricbootstrap(
  x,
  nsim,
  seed,
  ...,
  optsum_overrides = list(ftol_rel = 1e-08)
)

```

Arguments

x	A Julia MixedModel of class jlme
nsim	Number of simulations
seed	Seed for the random number generator (Random.MersenneTwister)
...	Not implemented
optsum_overrides	Values to override in the OptSummary.

Value

MixedModels.parametricbootstrap() output as object of class jlmeboot

Examples

```

jlme_setup(restart = TRUE)

jmod <- jlmer(Reaction ~ Days + (Days | Subject), lme4::sleepstudy)
tidy(jmod)

samp <- parametricbootstrap(jmod, nsim = 100L, seed = 42L)
samp

tidy(samp)

stop_julia()

```

tidy.jlmeboot

Tidier methods for Julia regression models

Description

Tidier methods for Julia regression models

Usage

```

## S3 method for class 'jlmeboot'
tidy(x, effects = c("var_model", "ran_pars", "fixed"), ...)

## S3 method for class 'jlme'
tidy(x, effects = c("var_model", "ran_pars", "fixed"), ...)

## S3 method for class 'jlme'
glance(x, ...)

```

Arguments

x	An object of class jlme
effects	One of "var_model", "ran_pars", or "fixed"
...	Unused

Value

A data frame

Index

`check_julia_ok`, 2
`glance.jlme` (`tidy.jlmeboot`), 6
`issingular` (`jlme-model-helpers`), 4
`jlm`, 3
`jlme-model-helpers`, 4
`jlme_setup` (`check_julia_ok`), 2
`jlme_status` (`check_julia_ok`), 2
`jlme_tidiers` (`tidy.jlmeboot`), 6
`jlmer` (`jlm`), 3
`parametricbootstrap`, 5
`propertynames` (`jlme-model-helpers`), 4
`stop_julia` (`check_julia_ok`), 2
`tidy.jlme` (`tidy.jlmeboot`), 6
`tidy.jlmeboot`, 6