

Package ‘SeqArray’

March 30, 2021

Type Package

Title Data management of large-scale whole-genome sequence variant calls

Version 1.30.0

Date 2020-09-13

Depends R (>= 3.5.0), gdsfmt (>= 1.23.5)

Imports methods, parallel, IRanges, GenomicRanges, GenomeInfoDb, Biostrings, S4Vectors

LinkingTo gdsfmt

Suggests Biobase, BiocGenerics, BiocParallel, RUnit, Rcpp, SNPRelate, digest, crayon, knitr, Rsamtools, VariantAnnotation

Description Data management of large-scale whole-genome sequencing variant calls with thousands of individuals: genotypic data (e.g., SNVs, indels and structural variation calls) and annotations in SeqArray GDS files are stored in an array-oriented and compressed manner, with efficient data access using the R programming language.

License GPL-3

VignetteBuilder knitr

ByteCompile TRUE

URL <http://github.com/zhengxwen/SeqArray>

BugReports <http://github.com/zhengxwen/SeqArray/issues>

biocViews Infrastructure, DataRepresentation, Sequencing, Genetics

git_url <https://git.bioconductor.org/packages/SeqArray>

git_branch RELEASE_3_12

git_last_commit 6a9e919

git_last_commit_date 2020-10-27

Date/Publication 2021-03-29

Author Xiuwen Zheng [aut, cre] (<<https://orcid.org/0000-0002-1390-0708>>),
Stephanie Gogarten [aut],
David Levine [ctb],
Cathy Laurie [ctb]

Maintainer Xiuwen Zheng <zhengx@u.washington.edu>

R topics documented:

SeqArray-package	3
KG_P1_SampData	5
seqAddValue	5
seqAlleleFreq	7
seqApply	9
seqAsVCF	12
seqBED2GDS	13
seqBlockApply	14
seqCheck	17
seqClose-methods	18
seqDelete	18
seqDigest	19
seqExampleFileName	20
seqExport	21
seqGDS2SNP	22
seqGDS2VCF	24
seqGetData	26
seqGetFilter	28
seqMerge	30
seqMissing	32
seqNumAllele	33
seqOpen	34
seqOptimize	35
seqParallel	36
seqParallelSetup	38
seqRecompress	40
seqResetVariantID	41
seqSetFilter-methods	42
seqSetFilterCond	45
seqSNP2GDS	46
seqStorageOption	48
seqSummary	49
seqSystem	52
seqTranspose	52
seqUnitApply	54
seqUnitFilterCond	56
seqUnitSlidingWindows	57
SeqVarGDSClass	58
seqVCF2GDS	59
seqVCF_Header	62
seqVCF_SampID	64

SeqArray-package	<i>Data Management of Large-scale Whole-Genome Sequence Variant Calls</i>
------------------	---

Description

Data management of large-scale whole-genome sequencing variants.

Details

As the cost of DNA sequencing rapidly decreases, whole-genome sequencing (WGS) is generating data at an unprecedented rate. Scientists are being challenged to manage data sets that are terabyte-sized, contain diverse types of data and complex data relationships. Data analyses of WGS requires a general file format for storing genetic variants including single nucleotide variations (SNVs), insertions and deletions (indels) and structural variants. The variant call format (VCF) is a generic and flexible format for storing DNA polymorphisms developed for the 1000 Genomes Project that is the standard WGS format in use today. VCF is a textual format usually stored in compressed files that supports rich annotations and relatively efficient data retrieval. However, VCF files are large and the computational burden associated with all data retrieval from text files can be significant for a large WGS study with thousands of samples.

To provide an efficient alternative to VCF for WGS data, we developed a new data format and accompanying Bioconductor package, “SeqArray”. Key features of SeqArray are efficient storage including multiple high compression options, data retrieval by variant or sample subsets, support for parallel access and computing, and C++ integration in the R programming environment. The SeqArray package provides R functions for efficient block-wise computations, and enables scientists to develop custom R scripts for exploratory data analysis.

Webpage: <http://github.com/zhengxwen/SeqArray>, <http://www.bioconductor.org/packages/SeqArray/>

Author(s)

Xiuwen Zheng <zhengxwen@gmail.com>

Examples

```
# the file of VCF
vcf.fn <- seqExampleFileName("vcf")
vcf.fn
# or vcf.fn <- "C:/YourFolder/Your_VCF_File.vcf"

# parse the header
seqVCF_Header(vcf.fn)

# get sample id
seqVCF_SampID(vcf.fn)

# convert
seqVCF2GDS(vcf.fn, "tmp.gds", storage.option="ZIP_RA")
seqSummary("tmp.gds")

# list the structure of GDS variables
f <- seqOpen("tmp.gds")
```

```

f

seqClose(f)
unlink("tmp.gds")

#####

# the GDS file
(gds.fn <- seqExampleFileName("gds"))

# display
(f <- seqOpen(gds.fn))

# get 'sample.id'
(samp.id <- seqGetData(f, "sample.id"))
# "NA06984" "NA06985" "NA06986" ...

# get 'variant.id'
head(variant.id <- seqGetData(f, "variant.id"))

# get 'chromosome'
table(seqGetData(f, "chromosome"))

# get 'allele'
head(seqGetData(f, "allele"))
# "T,C" "G,A" "G,A" ...

# set sample and variant filters
seqSetFilter(f, sample.id=samp.id[c(2,4,6,8,10)])
set.seed(100)
seqSetFilter(f, variant.id=sample(variant.id, 10))

# get genotypic data
seqGetData(f, "genotype")

# get annotation/info/DP
seqGetData(f, "annotation/info/DP")

# get annotation/info/AA, a variable-length dataset
seqGetData(f, "annotation/info/AA")
# $length      <- indicating the length of each variable-length data
# [1] 1 1 1 1 1 1 ...
# $data        <- the data according to $length
# [1] "T" "C" "T" "C" "G" "C" ...

# get annotation/format/DP, a variable-length dataset
seqGetData(f, "annotation/format/DP")
# $length      <- indicating the length of each variable-length data
# [1] 1 1 1 1 1 1 ...
# $data        <- the data according to $length
#      variant
# sample [ ,1] [ ,2] [ ,3] [ ,4] [ ,5] [ ,6] ...
# [1,]    25    25    22     3     4    17 ...

```

```

# read multiple variables variant by variant
seqApply(f, c(geno="genotype", phase="phase", qual="annotation/id"),
  FUN=function(x) print(x), as.is="none")

# get the numbers of alleles per variant
head(seqApply(f, "allele",
  FUN=function(x) length(unlist(strsplit(x,","))), as.is="integer"))
# or
head(seqGetData(f, "$num_allele"))

#####

# remove the sample and variant filters
seqResetFilter(f)

# calculate the frequency of reference allele,
# a faster version could be obtained by C coding
af <- seqApply(f, "genotype", FUN=function(x) mean(x==0L, na.rm=TRUE),
  as.is="double")
length(af)
summary(af)

# close the GDS file
seqClose(f)

```

KG_P1_SampData

Simulated sample data for 1000 Genomes Phase 1

Description

An AnnotatedDataFrame with columns sample.id, sex, age, and phenotype, where the identifiers in sample.id match those in the SeqArray file.

Usage

```
KG_P1_SampData
```

Value

An AnnotatedDataFrame

seqAddValue

Add values to a GDS File

Description

Add or modify the values in a GDS file with hash code

Usage

```
seqAddValue(gdsfile, varnm, val, desp=character(), replace=FALSE,
            compress="LZMA_RA", packed=TRUE, verbose=TRUE, verbose.attr=TRUE)
```

Arguments

<code>gdsfile</code>	character for file name, or a SeqVarGDSClass object
<code>varnm</code>	the variable name, e.g., "sample.id", "variant.id", "chromosome", "annotation/info/NEW_VARIABLE"
<code>val</code>	the R value can be integers, real numbers, characters, factor, logical, raw variable, <code>data.frame</code> or a list; a list of vectors is used for variable-length annotation data
<code>desp</code>	variable description
<code>replace</code>	if TRUE, replace the existing variable silently if possible
<code>compress</code>	the compression method can be "" (no compression), see add.gdsn
<code>packed</code>	TRUE, pack data if there is any missing value
<code>verbose</code>	if TRUE, show information
<code>verbose.attr</code>	if TRUE, show attribute information in a GDS node

Value

Return none.

Author(s)

Xiuwen Zheng

See Also

[seqVCF2GDS](#)

Examples

```
# the file of GDS
gds.fn <- seqExampleFileName("gds")
file.copy(gds.fn, "tmp.gds", overwrite=TRUE)

# display
(f <- seqOpen("tmp.gds", FALSE))

show(index.gdsn(f, "sample.id"))
seqAddValue(f, "sample.id", 1:90, replace=TRUE)
show(index.gdsn(f, "sample.id"))

show(index.gdsn(f, "chromosome"))
v <- seqGetData(f, "chromosome")
seqAddValue(f, "chromosome", paste0("chr", v), replace=TRUE)
show(index.gdsn(f, "chromosome"))
table(seqGetData(f, "chromosome"))

# annotation info
seqAddValue(f, "annotation/info/folder", NULL) # add a new folder
seqAddValue(f, "annotation/info/folder/val", 1:1348, "random number")
```

```

seqAddValue(f, "annotation/info/folder/packed", c(rep(2L, 1000), rep(NA, 348)))
seqAddValue(f, "annotation/info/newff",
  data.frame(x=1:1348, y=rep("s", 1348), stringsAsFactors=FALSE),
  desp=c("integer numbers", "character"))

# variable-length annotation info data
v <- lapply(1:1348, function(x) as.character(x))
v[[1]] <- 1:10
seqAddValue(f, "annotation/info/folder/val1", v)
head(seqGetData(f, "annotation/info/folder/val1", .tolist=TRUE))

# sample annotation
seqAddValue(f, "sample.annotation", data.frame(ii=1:90, y=rep("A", 90)),
  replace=TRUE)
seqAddValue(f, "sample.annotation/float", (1:90)/90)

# close the GDS file
seqClose(f)

# remove the temporary file
unlink("tmp.gds", force=TRUE)

```

seqAlleleFreq

*Get Allele Frequencies or Counts***Description**

Calculates the allele frequencies or counts for reference or minor alleles.

Usage

```

seqAlleleFreq(gdsfile, ref.allele=0L, minor=FALSE, .progress=FALSE,
  parallel=seqGetParallel(), verbose=FALSE)
seqAlleleCount(gdsfile, ref.allele=0L, minor=FALSE, .progress=FALSE,
  parallel=seqGetParallel(), verbose=FALSE)

```

Arguments

<code>gdsfile</code>	a SeqVarGDSClass object
<code>ref.allele</code>	NULL, a single numeric value, a numeric vector or a character vector; see Value
<code>minor</code>	if TRUE, return minor allele frequency/count
<code>.progress</code>	[deprecated] if TRUE, show progress information
<code>parallel</code>	FALSE (serial processing), TRUE (multicore processing), numeric value or other value; <code>parallel</code> is passed to the argument <code>cl</code> in seqParallel , see seqParallel for more details.
<code>verbose</code>	if TRUE, show progress information

Details

If the gds node 'genotype/data' (integer genotypes) is not available, the node 'annotation/format/DS' (numeric genotype dosages for alternative alleles) will be used to calculate allele frequencies. At a site, it assumes 'annotation/format/DS' stores the dosage of the 1st alternative allele in the 1st column, 2nd alt. allele in the 2nd column if it is multi-allelic, and so on.

Value

If ref.allele=NULL, the function returns a list of allele frequencies/counts according to all allele per site. If ref.allele is a single numeric value (like 0L), it returns a numeric/integer vector for the specified allele (0L for the reference allele, 1L for the first alternative allele, etc). If ref.allele is a numeric vector, ref.allele specifies each allele per site. If ref.allele is a character vector, ref.allele specifies the desired allele for each site (e.g. ancestral allele for the derived allele frequency/count).

Author(s)

Xiuwen Zheng

See Also

[seqNumAllele](#), [seqMissing](#), [seqParallel](#), [seqGetParallel](#)

Examples

```
# the GDS file
(gds.fn <- seqExampleFileName("gds"))

# display
f <- seqOpen(gds.fn)

# return a list
head(seqAlleleFreq(f, NULL, verbose=TRUE))

# return a numeric vector
summary(seqAlleleFreq(f, 0L, verbose=TRUE))

# return a numeric vector
summary(seqAlleleFreq(f, 0L, minor=TRUE, verbose=TRUE))

# return a numeric vector, AA is ancestral allele
AA <- seqGetData(f, "annotation/info/AA", .padNA=TRUE)
summary(seqAlleleFreq(f, AA))
summary(seqAlleleFreq(f, AA, minor=TRUE))

# allele counts
head(seqAlleleCount(f, NULL, verbose=TRUE))
head(seqAlleleCount(f, 0L, verbose=TRUE))
head(seqAlleleCount(f, 0L, minor=TRUE, verbose=TRUE))
head(seqAlleleCount(f, AA, verbose=TRUE))
head(seqAlleleCount(f, AA, minor=TRUE, verbose=TRUE))

# close the GDS file
seqClose(f)
```


seqApply

*Apply Functions Over Array Margins***Description**

Returns a vector or list of values obtained by applying a function to margins of genotypes and annotations.

Usage

```
seqApply(gdsfile, var.name, FUN, margin=c("by.variant", "by.sample"),
  as.is=c("none", "list", "integer", "double", "character", "logical", "raw"),
  var.index=c("none", "relative", "absolute"), parallel=FALSE,
  .useraw=FALSE, .progress=FALSE, .list_dup=TRUE, ...)
```

Arguments

gdsfile	a SeqVarGDSCClass object
var.name	the variable name(s), see details
FUN	the function to be applied
margin	giving the dimension which the function will be applied over; margin="by.variant" by default
as.is	returned value: a list, an integer vector, etc; return nothing by default as.is="none"; as.is can be a connection object, or a GDS node gdsn.class object; if "unlist" is used, produces a vector which contains all the atomic components, via <code>unlist(..., recursive=FALSE)</code>
var.index	if "none" (by default), call FUN(x, ...) without variable index; if "relative" or "absolute", add an argument to the user-defined function FUN like FUN(index, x, ...) where index is an index of variant starting from 1 if margin = "by.variant": "relative" for indexing in the selection defined by seqSetFilter , "absolute" for indexing with respect to all data
parallel	FALSE (serial processing), TRUE (multicore processing), numeric value or other value; parallel is passed to the argument cl in seqParallel , see seqParallel for more details.
.useraw	TRUE, force to use RAW instead of INTEGER for genotypes and dosages; FALSE, use INTEGER; NA, use RAW for small numbers instead of INTEGER if possible, it is needed to detect data type (RAW or INTEGER) in the user-defined function; for genotypes, 0xFF is missing value if RAW is used
.progress	if TRUE, show progress information
.list_dup	internal use only
...	optional arguments to FUN

Details

The variable name should be "sample.id", "variant.id", "position", "chromosome", "allele", "genotype", "annotation/id", "annotation/qual", "annotation/filter", "annotation/info/VARIABLE_NAME" or "annotation/format/VARIABLE_NAME".

"@genotype", "annotation/info/@VARIABLE_NAME" or "annotation/format/@VARIABLE_NAME" are used to obtain the index associated with these variables.

"\$dosage" is also allowed for the dosages of reference allele (integer: 0, 1, 2 and NA for diploid genotypes).

"\$dosage_alt" returns a RAW/INTEGER matrix for the dosages of alternative allele without distinguishing different alternative alleles.

"\$num_allele" returns an integer vector with the numbers of distinct alleles.

"\$ref" returns a character vector of reference alleles

"\$alt" returns a character vector of alternative alleles (delimited by comma)

"\$chrom_pos" returns characters with the combination of chromosome and position, e.g., "1:1272721".

"\$chrom_pos_allele" returns characters with the combination of chromosome, position and alleles, e.g., "1:1272721_A_G" (i.e., chr:position_REF_ALT).

The algorithm is highly optimized by blocking the computations to exploit the high-speed memory instead of disk.

Value

A vector, a list of values or none.

Author(s)

Xiuwen Zheng

See Also

[seqBlockApply](#), [seqSetFilter](#), [seqGetData](#), [seqParallel](#), [seqGetParallel](#)

Examples

```
# the GDS file
(gds.fn <- seqExampleFileName("gds"))

# display
(f <- seqOpen(gds.fn))

# get 'sample.id'
(samp.id <- seqGetData(f, "sample.id"))
# "NA06984" "NA06985" "NA06986" ...

# get 'variant.id'
head(variant.id <- seqGetData(f, "variant.id"))

# set sample and variant filters
set.seed(100)
seqSetFilter(f, sample.id=samp.id[c(2,4,6,8,10)],
            variant.id=sample(variant.id, 10))

# read
seqApply(f, "genotype", FUN=print, margin="by.variant")
seqApply(f, "genotype", FUN=print, margin="by.variant", .useraw=TRUE)

seqApply(f, "genotype", FUN=print, margin="by.sample")
```

```

seqApply(f, "genotype", FUN=print, margin="by.sample", .useraw=TRUE)

# read multiple variables variant by variant
seqApply(f, c(geno="genotype", phase="phase", rsid="annotation/id",
  DP="annotation/format/DP"), FUN=print, as.is="none")

# get the numbers of alleles per variant
seqApply(f, "allele",
  FUN=function(x) length(unlist(strsplit(x,","))), as.is="integer")

# output to a file
fl <- file("tmp.txt", "wt")
seqApply(f, "genotype", FUN=sum, na.rm=TRUE, as.is=fl)
close(fl)
readLines("tmp.txt")

seqApply(f, "genotype", FUN=sum, na.rm=TRUE, as.is=stdout())
seqApply(f, "genotype", FUN=sum, na.rm=TRUE, as.is="integer")
# should be identical

#####
# with an index of variant

seqApply(f, c(geno="genotype", phase="phase", rsid="annotation/id"),
  FUN=function(index, x) { print(index); print(x); index },
  as.is="integer", var.index="relative")
# it is as the same as
which(seqGetFilter(f)$variant.sel)

#####
# reset sample and variant filters
seqResetFilter(f)

# calculate the frequency of reference allele,
# a faster version could be obtained by C coding
af <- seqApply(f, "genotype", FUN=function(x) mean(x==0L, na.rm=TRUE),
  as.is="double")
length(af)
summary(af)

#####
# apply the user-defined function sample by sample

# reset sample and variant filters
seqResetFilter(f)
summary(seqApply(f, "genotype", FUN=function(x) { mean(is.na(x)) },
  margin="by.sample", as.is="double"))

# set sample and variant filters
set.seed(100)

```

```

seqSetFilter(f, sample.id=samp.id[c(2,4,6,8,10)],
             variant.id=sample(variant.id, 10))

seqApply(f, "genotype", FUN=print, margin="by.variant", as.is="none")

seqApply(f, "genotype", FUN=print, margin="by.sample", as.is="none")

seqApply(f, c(sample.id="sample.id", genotype="genotype"), FUN=print,
         margin="by.sample", as.is="none")

# close the GDS file
seqClose(f)

# delete the temporary file
unlink("tmp.txt")

```

seqAsVCF

VariantAnnotation objects

Description

Create a [VCF-class](#) object

Usage

```
seqAsVCF(x, chr.prefix="", info=NULL, geno=NULL)
```

Arguments

x	a SeqVarGDSCClass object
chr.prefix	prefix to add to seqlevels
info	which INFO fields to return
geno	which GENO fields to return

Details

Coerces a [SeqVarGDSCClass](#) object to a [VCF-class](#) object. Row names correspond to the variant.id. info and geno specify the 'INFO' and 'GENO' (FORMAT) fields to return, respectively. If not specified, all fields are returned; if 'NA' no fields are returned. Use [seqSetFilter](#) prior to calling seqAsVCF to specify samples and variants to return.

The **VariantAnnotation** package should be loaded to explore this object.

Value

A [CollapsedVCF](#) object.

Author(s)

Stephanie Gogarten, Xiuwen Zheng

See Also[VCF-class](#)**Examples**

```
gds <- seqOpen(seqExampleFileName("gds"))

## Not run:
library(VariantAnnotation)
seqAsVCF(gds)

## End(Not run)

seqClose(gds)
```

seqBED2GDS

*Conversion between PLINK BED and SeqArray GDS***Description**

Conversion between PLINK BED format and SeqArray GDS format.

Usage

```
seqBED2GDS(bed.fn, fam.fn, bim.fn, out.gdsfn, compress.geno="LZMA_RA",
           compress.annotation="LZMA_RA", chr.conv=TRUE, optimize=TRUE, digest=TRUE,
           parallel=FALSE, verbose=TRUE)
seqGDS2BED(gdsfile, out.fn, multi.row=FALSE, verbose=TRUE)
```

Arguments

bed.fn	the file name of binary file, genotype information
fam.fn	the file name of first six columns of ".ped"
bim.fn	the file name of extended MAP file: two extra columns = allele names
gdsfile	character (a GDS file name), or a SeqVarGDSClass object
out.gdsfn	the file name, output a file of SeqArray format
out.fn	the file name of PLINK binary format without extended names
compress.geno	the compression method for "genotype"; optional values are defined in the function <code>add.gdsn</code>
compress.annotation	the compression method for the GDS variables, except "genotype"; optional values are defined in the function <code>add.gdsn</code>
chr.conv	if TRUE, convert numeric chromosome codes 23 to X, 24 to Y, 25 to XY, and 26 to MT
optimize	if TRUE, optimize the access efficiency by calling cleanup.gds
digest	a logical value (TRUE/FALSE) or a character ("md5", "sha1", "sha256", "sha384" or "sha512"); add hash codes to the GDS file if TRUE or a digest algorithm is specified

parallel	FALSE (serial processing), TRUE (parallel processing), a numeric value indicating the number of cores, or a cluster object for parallel processing; parallel is passed to the argument c1 in seqParallel , see seqParallel for more details
multi.row	if TRUE, a multiallelic site is converted to multiple rows in PLINK bim and bed files
verbose	if TRUE, show information

Value

Return the file name of SeqArray file with an absolute path.

Author(s)

Xiuwen Zheng

See Also

[seqSNP2GDS](#), [seqVCF2GDS](#)

Examples

```
library(SNPRelate)

# PLINK BED files
bed.fn <- system.file("extdata", "plinkhapmap.bed.gz", package="SNPRelate")
fam.fn <- system.file("extdata", "plinkhapmap.fam.gz", package="SNPRelate")
bim.fn <- system.file("extdata", "plinkhapmap.bim.gz", package="SNPRelate")

# convert bed to gds
seqBED2GDS(bed.fn, fam.fn, bim.fn, "tmp.gds")

seqSummary("tmp.gds")

# convert gds to bed
gdsfn <- seqExampleFileName("gds")
seqGDS2BED(gdsfn, "plink")

# remove the temporary file
unlink(c("tmp.gds", "plink.fam", "plink.bim", "plink.bed"), force=TRUE)
```

seqBlockApply

Apply Functions Over Array Margins via Blocking

Description

Returns a vector or list of values obtained by applying a function to margins of genotypes and annotations via blocking.

Usage

```
seqBlockApply(gdsfile, var.name, FUN, margin=c("by.variant"),
  as.is=c("none", "list", "unlist"), var.index=c("none", "relative", "absolute"),
  bsize=1024L, parallel=FALSE, .useraw=FALSE, .padNA=TRUE, .tolist=FALSE,
  .progress=FALSE, ...)
```

Arguments

<code>gdsfile</code>	a SeqVarGDSClass object
<code>var.name</code>	the variable name(s), see details
<code>FUN</code>	the function to be applied
<code>margin</code>	giving the dimension which the function will be applied over
<code>as.is</code>	returned value: a list, an integer vector, etc; return nothing by default <code>as.is="none"</code> ; <code>as.is</code> can be a connection object, or a GDS node gdsn.class object; if "unlist" is used, produces a vector which contains all the atomic components, via <code>unlist(..., recursive=FALSE)</code>
<code>var.index</code>	if "none" (by default), call <code>FUN(x, ...)</code> without variable index; if "relative" or "absolute", add an argument to the user-defined function <code>FUN</code> like <code>FUN(index, x, ...)</code> where <code>index</code> is an index of variant starting from 1 if <code>margin = "by.variant"</code> : "relative" for indexing in the selection defined by seqSetFilter , "absolute" for indexing with respect to all data
<code>bsize</code>	block size
<code>parallel</code>	FALSE (serial processing), TRUE (multicore processing), numeric value or other value; <code>parallel</code> is passed to the argument <code>cl</code> in seqParallel , see seqParallel for more details.
<code>.useraw</code>	TRUE, force to use RAW instead of INTEGER for genotypes and dosages; FALSE, use INTEGER; NA, use RAW instead of INTEGER if possible; for genotypes, 0xFF is missing value if RAW is used
<code>.padNA</code>	TRUE, pad a variable-length vector with NA if the number of data points for each variant is not greater than 1
<code>.tolist</code>	if TRUE, return a list of vectors instead of the structure <code>list(length, data)</code> for variable-length data
<code>.progress</code>	if TRUE, show progress information
<code>...</code>	optional arguments to <code>FUN</code>

Details

The variable name should be "sample.id", "variant.id", "position", "chromosome", "allele", "genotype", "annotation/id", "annotation/qual", "annotation/filter", "annotation/info/VARIABLE_NAME" or "annotation/format/VARIABLE_NAME".

"@genotype", "annotation/info/@VARIABLE_NAME" or "annotation/format/@VARIABLE_NAME" are used to obtain the index associated with these variables.

"\$dosage" is also allowed for the dosages of reference allele (integer: 0, 1, 2 and NA for diploid genotypes).

"\$dosage_alt" returns a RAW/INTEGER matrix for the dosages of alternative allele without distinguishing different alternative alleles.

"\$num_allele" returns an integer vector with the numbers of distinct alleles.

"\$ref" returns a character vector of reference alleles

"\$alt" returns a character vector of alternative alleles (delimited by comma)

"\$chrom_pos" returns characters with the combination of chromosome and position, e.g., "1:1272721".

"\$chrom_pos_allele" returns characters with the combination of chromosome, position and alleles, e.g., "1:1272721_A_G" (i.e., chr:position_REF_ALT).

"\$variant_index" returns the indices of selected variants starting from 1, and "\$sample_index" returns the indices of selected samples starting from 1.

The algorithm is highly optimized by blocking the computations to exploit the high-speed memory instead of disk.

Value

A vector, a list of values or none.

Author(s)

Xiuwen Zheng

See Also

[seqApply](#), [seqSetFilter](#), [seqGetData](#), [seqParallel](#), [seqGetParallel](#)

Examples

```
# the GDS file
(gds.fn <- seqExampleFileName("gds"))

# display
(f <- seqOpen(gds.fn))

# get 'sample.id'
(samp.id <- seqGetData(f, "sample.id"))
# "NA06984" "NA06985" "NA06986" ...

# get 'variant.id'
head(variant.id <- seqGetData(f, "variant.id"))

# set sample and variant filters
set.seed(100)
seqSetFilter(f, sample.id=samp.id[c(2,4,6,8,10)],
            variant.id=sample(variant.id, 10))

# read
seqApply(f, "genotype", FUN=print, margin="by.variant")
seqApply(f, "genotype", FUN=print, margin="by.variant", .useraw=TRUE)

seqApply(f, "genotype", FUN=print, margin="by.sample")
seqApply(f, "genotype", FUN=print, margin="by.sample", .useraw=TRUE)

# read in block
seqGetData(f, "$dosage")
seqBlockApply(f, "$dosage", print, bsize=3)
seqBlockApply(f, "$dosage", function(x) x, as.is="list", bsize=3)
seqBlockApply(f, c(dos="$dosage", pos="position"), print, bsize=3)
```



```
# close the GDS file
seqClose(f)
```

seqCheck *Data Integrity Checking*

Description

Performs data integrity on a SeqArray GDS file.

Usage

```
seqCheck(gdsfile, verbose=TRUE)
```

Arguments

gdsfile	a SeqVarGDSClass object, or a file name
verbose	if TRUE, display information

Value

A list of the following components:

hash	a data.frame for hash checking, including algo for digest algorithms and ok for the checking states
dimension	a data.frame for checking the dimension of each variable, including ok for the checking states and info for the error messages

Author(s)

Xiuwen Zheng

Examples

```
# the GDS file
(gds.fn <- seqExampleFileName("gds"))

seqCheck(gds.fn)
```

seqClose-methods *Close the SeqArray GDS File*

Description

Closes a SeqArray GDS file which is open.

Usage

```
## S4 method for signature 'gds.class'  
seqClose(object)  
## S4 method for signature 'SeqVarGDSClass'  
seqClose(object)
```

Arguments

object a SeqArray object

Details

If object is

- [gds.class](#), close a general GDS file
- [SeqVarGDSClass](#), close the sequence GDS file.

Value

None.

Author(s)

Xiuwen Zheng

See Also

[seqOpen](#)

seqDelete *Delete GDS Variables*

Description

Deletes variables in the SeqArray GDS file.

Usage

```
seqDelete(gdsfile, info.var=character(), fmt.var=character(),  
          samp.var=character(), verbose=TRUE)
```

Arguments

<code>gdsfile</code>	a SeqVarGDSClass object
<code>info.var</code>	the variables in the INFO field, i.e., "annotation/info/VARIABLE_NAME"
<code>fmt.var</code>	the variables in the FORMAT field, i.e., "annotation/format/VARIABLE_NAME"
<code>samp.var</code>	the variables in the sample annotation field, i.e., "sample.annotation/VARIABLE_NAME"
<code>verbose</code>	if TRUE, show information

Value

None.

Author(s)

Xiuwen Zheng

See Also

[seqOpen](#), [seqClose](#)

Examples

```
# the file of GDS
gds.fn <- seqExampleFileName("gds")
file.copy(gds.fn, "tmp.gds", overwrite=TRUE)

# display
(f <- seqOpen("tmp.gds", FALSE))

seqDelete(f, info.var=c("HM2", "AA"), fmt.var="DP")
f

# close the GDS file
seqClose(f)

# clean up the fragments, reduce the file size
cleanup.gds("tmp.gds")

# remove the temporary file
unlink("tmp.gds", force=TRUE)
```

seqDigest

Hash function digests

Description

Create hash function digests for all or a subset of data

Usage

```
seqDigest(gdsfile, varname, algo=c("md5"), verbose=FALSE)
```

Arguments

<code>gdsfile</code>	a SeqVarGDSClass object
<code>varname</code>	the variable name(s), see details
<code>algo</code>	the digest hash algorithm: "md5"
<code>verbose</code>	if TRUE, show progress information

Details

The variable name should be "sample.id", "variant.id", "position", "chromosome", "allele", "annotation/id", "annotation/qual", "annotation/filter", "annotation/info/VARIABLE_NAME", or "annotation/format/VARIABLE_NAME".

Users can define a subset of data via [seqSetFilter](#) and create a hash digest for the subset only.

Value

A hash character.

Author(s)

Xiuwen Zheng

See Also

[seqSetFilter](#), [seqApply](#)

Examples

```
# the GDS file
(gds.fn <- seqExampleFileName("gds"))

# display
f <- seqOpen(gds.fn)

seqDigest(f, "genotype")
seqDigest(f, "annotation/filter")
seqDigest(f, "annotation/format/DP")

# close the GDS file
seqClose(f)
```

`seqExampleFileName` *Example files*

Description

The example files of VCF and GDS format.

Usage

```
seqExampleFileName(type=c("gds", "vcf", "KG_Phase1"))
```

Arguments

type either "gds" (by default) or "vcf"

Value

Return the path of a VCF file in the package if type="vcf", or the path of a GDS file if type="gds". If type="KG_Phase1", return the path of GDS file on Chromosome 22 of the 1000 Genomes Phase 1 project.

Author(s)

Xiuwen Zheng

Examples

```
seqExampleFileName("gds")
seqExampleFileName("vcf")
seqExampleFileName("KG_Phase1")
```

seqExport

Export to a GDS File

Description

Exports to a GDS file with selected samples and variants, which are defined by seqSetFilter().

Usage

```
seqExport(gdsfile, out.fn, info.var=NULL, fmt.var=NULL, samp.var=NULL,
          optimize=TRUE, digest=TRUE, verbose=TRUE)
```

Arguments

gdsfile	a SeqVarGDSCClass object
out.fn	the file name of output GDS file
info.var	characters, the variable name(s) in the INFO field for import; or NULL for all variables
fmt.var	characters, the variable name(s) in the FORMAT field for import; or NULL for all variables
samp.var	characters, the variable name(s) in the folder "sample.annotation"
optimize	if TRUE, optimize the access efficiency by calling cleanup.gds
digest	a logical value (TRUE/FALSE) or a character ("md5", "sha1", "sha256", "sha384" or "sha512"); add md5 hash codes to the GDS file if TRUE or a digest algorithm is specified
verbose	if TRUE, show information

Value

Return the file name of GDS format with an absolute path.

Author(s)

Xiuwen Zheng

See Also

[seqVCF2GDS](#)

Examples

```
# open the GDS file
(gds.fn <- seqExampleFileName("gds"))
(f <- seqOpen(gds.fn))

# get 'sample.id'
head(samp.id <- seqGetData(f, "sample.id"))

# get 'variant.id'
head(variant.id <- seqGetData(f, "variant.id"))

set.seed(100)
# set sample and variant filters
seqSetFilter(f, sample.id=samp.id[c(2,4,6,8,10,12,14,16)])
seqSetFilter(f, variant.id=sample(variant.id, 100))

# export
seqExport(f, "tmp.gds")
seqExport(f, "tmp.gds", info.var=character())
seqExport(f, "tmp.gds", fmt.var=character())
seqExport(f, "tmp.gds", samp.var=character())

# show file
(f1 <- seqOpen("tmp.gds")); seqClose(f1)

# close
seqClose(f)

# delete the temporary file
unlink("tmp.gds")
```

seqGDS2SNP

Convert to a SNP GDS File

Description

Converts a SeqArray GDS file to a SNP GDS file.

Usage

```
seqGDS2SNP(gdsfile, out.gdsfn, dosage=FALSE, compress.geno="LZMA_RA",
           compress.annotation="LZMA_RA", ds.type=c("packedreal16", "float", "double"),
           optimize=TRUE, verbose=TRUE)
```

Arguments

<code>gdsfile</code>	character (a GDS file name), or a SeqVarGDSClass object
<code>out.gdsfn</code>	the file name, output a file of VCF format
<code>dosage</code>	a logical value, or characters for the variable name of dosage in the SeqArray file; if FALSE exports genotypes, otherwise exports dosages
<code>compress.geno</code>	the compression method for "genotype"; optional values are defined in the function <code>add.gdsn</code>
<code>compress.annotation</code>	the compression method for the GDS variables, except "genotype"; optional values are defined in the function <code>add.gdsn</code>
<code>ds.type</code>	applicable when import dosages, the data type for storing dosages; see add.gdsn ; <code>ds.type="packedreal16"</code> by default
<code>optimize</code>	if TRUE, optimize the access efficiency by calling cleanup.gds
<code>verbose</code>	if TRUE, show information

Details

[seqSetFilter](#) can be used to define a subset of data for the conversion.

Value

Return the file name of VCF file with an absolute path.

Author(s)

Xiuwen Zheng

See Also

[seqSNP2GDS](#), [seqVCF2GDS](#), [seqGDS2VCF](#)

Examples

```
# the GDS file
gds.fn <- seqExampleFileName("gds")

seqGDS2SNP(gds.fn, "tmp.gds")

# delete the temporary file
unlink("tmp.gds")
```

seqGDS2VCF

*Convert to a VCF File***Description**

Converts a SeqArray GDS file to a Variant Call Format (VCF) file.

Usage

```
seqGDS2VCF(gdsfile, vcf.fn, info.var=NULL, fmt.var=NULL, chr_prefix="",
           use_Rsamtools=TRUE, verbose=TRUE)
```

Arguments

<code>gdsfile</code>	a SeqVarGDSClass object
<code>vcf.fn</code>	the file name, output a file of VCF format; or a connection object
<code>info.var</code>	a list of variable names in the INFO field, or NULL for using all variables; character(0) for no variable in the INFO field
<code>fmt.var</code>	a list of variable names in the FORMAT field, or NULL for using all variables; character(0) for no variable in the FORMAT field
<code>chr_prefix</code>	the prefix of chromosome, e.g., "chr"; no prefix by default
<code>use_Rsamtools</code>	TRUE for loading the Rsamtools package, see details
<code>verbose</code>	if TRUE, show information

Details

[seqSetFilter](#) can be used to define a subset of data for the export.

If the filename extension is ".gz", the gzip compression algorithm is used to compress the output data. When the Rsamtools package is installed and `use_Rsamtools=TRUE`, the exported file utilizes the bgzf format ([bgzip](#), a variant of gzip format) allowing for fast indexing.

Value

Return the file name of VCF file with an absolute path.

Author(s)

Xiuwen Zheng

References

Danecek, P., Auton, A., Abecasis, G., Albers, C.A., Banks, E., DePristo, M.A., Handsaker, R.E., Lunter, G., Marth, G.T., Sherry, S.T., et al. (2011). The variant call format and VCFtools. *Bioinformatics* 27, 2156-2158.

See Also

[seqVCF2GDS](#)

Examples

```

# the GDS file
(gds.fn <- seqExampleFileName("gds"))

# display
(f <- seqOpen(gds.fn))

# output the first 10 samples
samp.id <- seqGetData(f, "sample.id")
seqSetFilter(f, sample.id=samp.id[1:5])

# convert
seqGDS2VCF(f, "tmp.vcf.gz")

# no INFO and FORMAT
seqGDS2VCF(f, "tmp1.vcf.gz", info.var=character(), fmt.var=character())

# output BN,GP,AA,DP,HM2 in INFO (the variables are in this order), no FORMAT
seqGDS2VCF(f, "tmp2.vcf.gz", info.var=c("BN","GP","AA","DP","HM2"),
  fmt.var=character())

# read
(txt <- readLines("tmp.vcf.gz", n=20))
(txt <- readLines("tmp1.vcf.gz", n=20))
(txt <- readLines("tmp2.vcf.gz", n=20))

#####
# Users could compare the new VCF file with the original VCF file
# call "diff" in Unix (a command line tool comparing files line by line)

# using all samples and variants
seqResetFilter(f)

# convert
seqGDS2VCF(f, "tmp.vcf.gz")

# file.copy(seqExampleFileName("vcf"), "old.vcf.gz", overwrite=TRUE)
# system("diff <(gunzip -c old.vcf.gz) <(gunzip -c tmp.vcf.gz)")

# 1a2,3
# > ##fileDate=20130309
# > ##source=SeqArray_RPackage_v1.0

# LOOK GOOD!

# delete temporary files
unlink(c("tmp.vcf.gz", "tmp1.vcf.gz", "tmp2.vcf.gz"))

```

```
# close the GDS file
seqClose(f)
```

seqGetData

Get Data

Description

Gets data from a SeqArray GDS file.

Usage

```
seqGetData(gdsfile, var.name, .useraw=FALSE, .padNA=TRUE, .tolist=FALSE,
           .envir=NULL)
```

Arguments

<code>gdsfile</code>	a SeqVarGDSClass object
<code>var.name</code>	a variable name or a character vector, see details
<code>.useraw</code>	TRUE, force to use RAW instead of INTEGER for genotypes and dosages; FALSE, use INTEGER; NA, use RAW for small numbers instead of INTEGER if possible; 0xFF is missing value if RAW is used
<code>.padNA</code>	TRUE, pad a variable-length vector with NA if the number of data points for each variant is not greater than 1
<code>.tolist</code>	if TRUE, return a list of vectors instead of the structure <code>list(length, data)</code> for variable-length data
<code>.envir</code>	NULL, an environment object, a list or a <code>data.frame</code>

Details

The variable name should be "sample.id", "variant.id", "position", "chromosome", "allele", "genotype", "annotation/id", "annotation/qual", "annotation/filter", "annotation/info/VARIABLE_NAME" or "annotation/format/VARIABLE_NAME".

"@genotype", "annotation/info/@VARIABLE_NAME" or "annotation/format/@VARIABLE_NAME" are used to obtain the index associated with these variables.

"\$dosage" is also allowed for the dosages of reference allele (integer: 0, 1, 2 and NA for diploid genotypes).

"\$dosage_alt" returns a RAW/INTEGER matrix for the dosages of alternative allele without distinguishing different alternative alleles.

"\$num_allele" returns an integer vector with the numbers of distinct alleles.

"\$ref" returns a character vector of reference alleles. "\$alt" returns a character vector of alternative alleles (delimited by comma).

"\$chrom_pos" returns characters with the combination of chromosome and position, e.g., "1:1272721".

"\$chrom_pos_allele" returns characters with the combination of chromosome, position and alleles, e.g., "1:1272721_A_G" (i.e., chr:position_REF_ALT).

"\$variant_index" returns the indices of selected variants starting from 1, and "\$sample_index" returns the indices of selected samples starting from 1.

"\$:VAR" return the variable "VAR" from .envir according to the selected variants.

Value

Return vectors, matrices or lists (with length and data components) with a class name `SeqVarDataList`.

Author(s)

Xiuwen Zheng

See Also

[seqSetFilter](#), [seqApply](#)

Examples

```
# the GDS file
(gds.fn <- seqExampleFileName("gds"))

# display
(f <- seqOpen(gds.fn))

# get 'sample.id'
(samp.id <- seqGetData(f, "sample.id"))
# "NA06984" "NA06985" "NA06986" ...

# get 'variant.id'
head(variant.id <- seqGetData(f, "variant.id"))

# get 'chromosome'
table(seqGetData(f, "chromosome"))

# get 'allele'
head(seqGetData(f, "allele"))
# "T,C" "G,A" "G,A" ...

# get '$chrom_pos'
head(seqGetData(f, "$chrom_pos"))

# get '$dosage'
seqGetData(f, "$dosage")[1:6, 1:10]

# get '$num_allele'
head(seqGetData(f, "$num_allele"))

# set sample and variant filters
set.seed(100)
seqSetFilter(f, sample.id=samp.id[c(2,4,6,8,10)])
seqSetFilter(f, variant.id=sample(variant.id, 10))

# get a list
seqGetData(f, c(chr="chromosome", pos="position", allele="allele"))

# get the indices of selected variants/samples
seqGetData(f, "$variant_index")
seqGetData(f, "$sample_index")

# get genotypic data
```

```

seqGetData(f, "genotype")

# get annotation/info/DP
seqGetData(f, "annotation/info/DP")

# get annotation/info/AA, a variable-length dataset
seqGetData(f, "annotation/info/AA", .padNA=FALSE)
# $length          <- indicating the length of each variable-length data
# [1] 1 1 1 1 1 1 ...
# $data            <- the data according to $length
# [1] "T" "C" "T" "C" "G" "C" ...

# or return a simplified vector
seqGetData(f, "annotation/info/AA", .padNA=TRUE)

# get annotation/format/DP, a variable-length dataset
seqGetData(f, "annotation/format/DP")
# $length          <- indicating the length of each variable-length data
# [1] 1 1 1 1 1 1 ...
# $data            <- the data according to $length
#   variant
# sample [1,] [2,] [3,] [4,] [5,] [6,] ...
# [1,] 25 25 22 3 4 17 ...

# get values from R environment
env <- new.env()
env$x <- 1:1348 / 10
env$x[seqGetData(f, "$variant_index")]
seqGetData(f, "$:x", .envir=env)

# close the GDS file
seqClose(f)

```

seqGetFilter

Get the Filter of GDS File

Description

Gets the filter of samples and variants.

Usage

```
seqGetFilter(gdsfile, .useraw=FALSE)
```

Arguments

gdsfile	a SeqVarGDSClass object
.useraw	returns logical vectors if FALSE, and returns raw vectors if TRUE

Value

Return a list:

sample.sel a logical/raw vector indicating selected samples
variant.sel a logical/raw vector indicating selected variants

Author(s)

Xiuwen Zheng

See Also

[seqSetFilter](#)

Examples

```
# the GDS file
(gds.fn <- seqExampleFileName("gds"))

# display
(f <- seqOpen(gds.fn))

# get 'sample.id'
(samp.id <- seqGetData(f, "sample.id"))
# "NA06984" "NA06985" "NA06986" ...

# get 'variant.id'
head(variant.id <- seqGetData(f, "variant.id"))

# set sample and variant filters
seqSetFilter(f, sample.id=samp.id[c(2,4,6,8,10)])
set.seed(100)
seqSetFilter(f, variant.id=sample(variant.id, 10))

# get filter
z <- seqGetFilter(f)

# the number of selected samples
sum(z$sample.sel)
# the number of selected variants
sum(z$variant.sel)

z <- seqGetFilter(f, .useraw=TRUE)
head(z$sample.sel)
head(z$variant.sel)

# close the GDS file
seqClose(f)
```

seqMerge

*Merge Multiple SeqArray GDS Files***Description**

Merges multiple SeqArray GDS files.

Usage

```
seqMerge(gds.fn, out.fn, storage.option="LZMA_RA", info.var=NULL, fmt.var=NULL,
         samp.var=NULL, optimize=TRUE, digest=TRUE, geno.pad=TRUE, verbose=TRUE)
```

Arguments

<code>gds.fn</code>	the file names of multiple GDS files
<code>out.fn</code>	the output file name
<code>storage.option</code>	specify the storage and compression option, "ZIP_RA" (<code>seqStorageOption("ZIP_RA")</code>); or "LZMA_RA" to use LZMA compression algorithm with higher compression ratio (by default)
<code>info.var</code>	characters, the variable name(s) in the INFO field; NULL for all variables, or <code>character()</code> excludes all INFO variables
<code>fmt.var</code>	characters, the variable name(s) in the FORMAT field; NULL for all variables, or <code>character()</code> excludes all FORMAT variables
<code>samp.var</code>	characters, the variable name(s) in 'sample.annotation'; or NULL for all variables
<code>optimize</code>	if TRUE, optimize the access efficiency by calling <code>cleanup.gds</code>
<code>digest</code>	a logical value (TRUE/FALSE) or a character ("md5", "sha1", "sha256", "sha384" or "sha512"); add md5 hash codes to the GDS file if TRUE or a digest algorithm is specified
<code>geno.pad</code>	TRUE, pad a 2-bit genotype array in bytes to avoid recompressing genotypes if possible
<code>verbose</code>	if TRUE, show information

Details

The function merges multiple SeqArray GDS files. Users can specify the compression method and level for the new GDS file. If `gds.fn` contains one file, users can change the storage type to create a new file.

WARNING: the functionality of `seqMerge()` is limited.

Value

Return the file name of GDS format with an absolute path.

Author(s)

Xiuwen Zheng

See Also

[seqVCF2GDS](#), [seqExport](#)

Examples

```
# the VCF file
vcf.fn <- seqExampleFileName("vcf")

# the number of variants
total.count <- seqVCF_Header(vcf.fn, getnum=TRUE)$num.variant

split.cnt <- 5
start <- integer(split.cnt)
count <- integer(split.cnt)

s <- (total.count+1) / split.cnt
st <- 1L
for (i in 1:split.cnt)
{
  z <- round(s * i)
  start[i] <- st
  count[i] <- z - st
  st <- z
}

fn <- paste0("tmp", 1:split.cnt, ".gds")

# convert to 5 gds files
for (i in 1:split.cnt)
{
  seqVCF2GDS(vcf.fn, fn[i], storage.option="ZIP_RA",
            start=start[i], count=count[i])
}

# merge different variants
seqMerge(fn, "tmp.gds", storage.option="ZIP_RA")
seqSummary("tmp.gds")

#### merging different samples ####

vcf.fn <- seqExampleFileName("gds")
file.copy(vcf.fn, "test.gds", overwrite=TRUE)

# modify 'sample.id'
seqAddValue("test.gds", "sample.id", paste0("S", 1:90), replace=TRUE)

# merging
seqMerge(c(vcf.fn, "test.gds"), "output.gds", storage.option="ZIP_RA")

# delete the temporary files
unlink(c("tmp.gds", "test.gds", "output.gds"), force=TRUE)
unlink(fn, force=TRUE)
```

seqMissing	<i>Missing genotype percentage</i>
------------	------------------------------------

Description

Calculates the missing rates per variant or per sample.

Usage

```
seqMissing(gdsfile, per.variant=TRUE, .progress=FALSE,
           parallel=seqGetParallel(), verbose=FALSE)
```

Arguments

gdsfile	a SeqVarGDSClass object
per.variant	missing rate per variant if TRUE, missing rate per sample if FALSE, or calculating missing rates for variants and samples if NA
.progress	[deprecated] if TRUE, show progress information
parallel	FALSE (serial processing), TRUE (multicore processing), numeric value or other value; parallel is passed to the argument cl in seqParallel , see seqParallel for more details.
verbose	if TRUE, show progress information

Details

If the gds node 'genotype/data' (integer genotypes) is not available, the node 'annotation/format/DS' (numeric genotype dosages for alternative alleles) will be used to calculate allele frequencies. At a site, it assumes 'annotation/format/DS' stores the dosage of the 1st alternative allele in the 1st column, 2nd alt. allele in the 2nd column if it is multi-allelic, and so on.

Value

A vector of missing rates, or a `list(variant, sample)` for both variants and samples.

Author(s)

Xiuwen Zheng

See Also

[seqAlleleFreq](#), [seqNumAllele](#), [seqParallel](#), [seqGetParallel](#)

Examples

```
# the GDS file
(gds.fn <- seqExampleFileName("gds"))

# display
(f <- seqOpen(gds.fn))

summary(m1 <- seqMissing(f, TRUE, verbose=TRUE))
```



```
summary(m2 <- seqMissing(f, FALSE, verbose=TRUE))

str(m <- seqMissing(f, NA, verbose=TRUE))
identical(m1, m$variant) # should be TRUE
identical(m2, m$sample)  # should be TRUE

# close the GDS file
seqClose(f)
```

seqNumAllele	<i>Number of alleles</i>
--------------	--------------------------

Description

Returns the numbers of alleles for each site.

Usage

```
seqNumAllele(gdsfile)
```

Arguments

gdsfile a [SeqVarGDSClass](#) object

Value

The numbers of alleles for each site.

Author(s)

Xiuwen Zheng

See Also

[seqAlleleFreq](#), [seqMissing](#)

Examples

```
# the GDS file
(gds.fn <- seqExampleFileName("gds"))

# display
f <- seqOpen(gds.fn)

table(seqNumAllele(f))

# close the GDS file
seqClose(f)
```

`seqOpen`*Open a SeqArray GDS File*

Description

Opens a SeqArray GDS file.

Usage

```
seqOpen(gds.fn, readonly=TRUE, allow.duplicate=FALSE)
```

Arguments

<code>gds.fn</code>	the file name
<code>readonly</code>	whether read-only or not
<code>allow.duplicate</code>	if TRUE, it is allowed to open a GDS file with read-only mode when it has been opened in the same R session

Details

It is strongly suggested to call `seqOpen` instead of `openfn.gds`, since `seqOpen` will perform internal checking for data integrity.

Value

Return an object of class `SeqVarGDSClass` inherited from `gds.class`.

Author(s)

Xiuwen Zheng

See Also

[seqClose](#), [seqGetData](#), [seqApply](#)

Examples

```
# the GDS file
(gds.fn <- seqExampleFileName("gds"))

# open the GDS file
gdsfile <- seqOpen(gds.fn)

# display the contents of the GDS file in a hierarchical structure
gdsfile

# close the GDS file
seqClose(gdsfile)
```

seqOptimize	<i>Optimize the Storage of Data Array</i>
-------------	---

Description

Transpose data array or matrix for possibly higher-speed access.

Usage

```
seqOptimize(gdsfn, target=c("chromosome", "by.sample"), format.var=TRUE,  
            cleanup=TRUE, verbose=TRUE)
```

Arguments

gdsfn	the file name of GDS
target	"chromosome", "by.sample"; see details
format.var	a character vector for selected variable names, or TRUE for all variables, according to "annotation/format"
cleanup	call <code>link{cleanup.gds}</code> if TRUE
verbose	if TRUE, show information

Details

"chromosome": adding or updating two additional nodes '@chrom_rle_val' and '@chrom_rle_len' for faster chromosome indexing, requiring `SeqArray` >= v1.20.0.

"by.sample": optimizing GDS file for `seqApply(..., margin="by.sample")`. Warning: optimizing GDS file for reading data by sample may increase file size by up to 2X as genotype data and all format data are duplicated.

Value

None.

Author(s)

Xiuwen Zheng

See Also

[seqGetData](#), [seqApply](#)

Examples

```
# the file name of VCF  
(vcf.fn <- seqExampleFileName("vcf"))  
# or vcf.fn <- "C:/YourFolder/Your_VCF_File.vcf"  
  
# convert  
seqVCF2GDS(vcf.fn, "tmp.gds", storage.option="ZIP_RA")  
  
# prepare data for the SeqVarTools package
```

```
seqOptimize("tmp.gds", target="by.sample")

# list the structure of GDS variables
(f <- seqOpen("tmp.gds"))
# close
seqClose(f)

# delete the temporary file
unlink("tmp.gds")
```

seqParallel

*Apply Functions in Parallel***Description**

Applies a user-defined function in parallel.

Usage

```
seqParallel(cl=seqGetParallel(), gdsfile, FUN,
            split=c("by.variant", "by.sample", "none"), .combine="unlist",
            .selection.flag=FALSE, .initialize=NULL, .finalize=NULL, .initparam=NULL,
            .balancing=FALSE, .bl_size=10000L, .bl_progress=FALSE, ...)
seqParApply(cl=seqGetParallel(), x, FUN, load.balancing=TRUE, ...)
```

Arguments

<code>cl</code>	NULL or FALSE: serial processing; TRUE: multicore processing (the maximum number of cores minor one); a numeric value: the number of cores to be used; a cluster object for parallel processing, created by the functions in the package parallel , like makeCluster ; a BiocParallelParam object from the BiocParallel package. See details
<code>gdsfile</code>	a SeqVarGDSClass object, or NULL
<code>FUN</code>	the function to be applied, should be like <code>FUN(gdsfile, ...)</code> or <code>FUN(...)</code>
<code>split</code>	split the dataset by variant or sample according to multiple processes, or "none" for no split; <code>split="by.variant"</code> by default
<code>.combine</code>	define a function for combining results from different processes; by default, "unlist" is used, to produce a vector which contains all the atomic components, via <code>unlist(..., recursive=FALSE)</code> ; "list", return a list of results created by child processes; "none", no return; or a function with one or two arguments, like "+"
<code>.selection.flag</code>	TRUE – passes a logical vector of selection to the second argument of <code>FUN(gdsfile, selection, ...)</code>
<code>.initialize</code>	a user-defined function for initializing workers, should have two arguments (<code>process_id</code> , <code>param</code>)
<code>.finalize</code>	a user-defined function for finalizing workers, should have two arguments (<code>process_id</code> , <code>param</code>)
<code>.initparam</code>	parameters passed to <code>.initialize</code> and <code>.finalize</code>

.balancing	load balancing if TRUE
.bl_size	chunk size, the increment for load balancing, 10000 for variants
.bl_progress	if TRUE and .balancing=TRUE, show progress information
x	a vector (atomic or list), passed to FUN
load.balancing	if TRUE, call clusterApplyLB instead of clusterApply
...	optional arguments to FUN

Details

When `cl` is TRUE or a numeric value, forking techniques are used to create a new child process as a copy of the current R process, see `?parallel::mcfork`. However, forking is not available on Windows, and [makeCluster](#) is called to make a cluster which will be deallocated after calling FUN.

It is strongly suggested to use `seqParallel` together with `seqParallelSetup`. `seqParallelSetup` could work around the problem of forking on Windows, without allocating clusters frequently.

The user-defined function could use two predefined variables `SeqArray:::process_count` and `SeqArray:::process_index` to tell the total number of cluster nodes and which cluster node being used.

`seqParallel(,gdsfile=NULL,FUN=...,split="none")` could be used to setup multiple streams of pseudo-random numbers, and see [nextRNGStream](#) or [nextRNGSubStream](#) in the package `parallel`.

Value

A vector or list of values.

Author(s)

Xiuwen Zheng

See Also

[seqSetFilter](#), [seqGetData](#), [seqApply](#), [seqParallelSetup](#), [seqGetParallel](#)

Examples

```
library(parallel)

# choose an appropriate cluster size or number of cores
seqParallelSetup(2)

# the GDS file
(gds.fn <- seqExampleFileName("gds"))

# display
(gdsfile <- seqOpen(gds.fn))

# the uniprocessor version
afreq1 <- seqParallel(, gdsfile, FUN = function(f) {
  seqApply(f, "genotype", as.is="double",
    FUN=function(x) mean(x==0, na.rm=TRUE))
}, split="by.variant")

length(afreq1)
```

```

summary(afreq1)

# run in parallel
afreq2 <- seqParallel(, gdsfile, FUN = function(f) {
  seqApply(f, "genotype", as.is="double",
    FUN=function(x) mean(x==0, na.rm=TRUE))
  }, split="by.variant")

length(afreq2)
summary(afreq2)

# check
length(afreq1) # 1348
all(afreq1 == afreq2)

#####
# check -- variant splits

seqParallel(, gdsfile, FUN = function(f) {
  v <- seqGetFilter(f)
  sum(v$variant.sel)
  }, split="by.variant")
# [1] 674 674

#####

seqParallel(, NULL, FUN = function() {
  paste(SeqArray:::process_index, SeqArray:::process_count, sep=" / ")
  }, split="none")

seqParallel(, NULL, FUN = function() {
  SeqArray:::process_index
  }, split="none", .combine=function(i) print(i))

seqParallel(, NULL, FUN = function() {
  SeqArray:::process_index
  }, split="none", .combine="+")

#####

# close the GDS file
seqClose(gdsfile)

# clear the parallel cluster
seqParallelSetup(FALSE)

```

Description

Sets up a parallel environment in R for the current session.

Usage

```
seqParallelSetup(cluster=TRUE, verbose=TRUE)
seqGetParallel()
```

Arguments

cluster	NULL or FALSE: serial processing; TRUE: parallel processing with the maximum number of cores minor one; a numeric value: the number of cores to be used; a cluster object for parallel processing, created by the functions in the package parallel , like makeCluster . See details
verbose	if TRUE, show information

Details

When `cl` is TRUE or a numeric value, forking techniques are used to create a new child process as a copy of the current R process, see `?parallel::mcfork`. However, forking is not available on Windows, so multiple processes created by [makeCluster](#) are used instead. The R environment option `seqarray.parallel` will be set according to the value of `cluster`. Using `seqParallelSetup(FALSE)` removes the registered cluster, as does stopping the registered cluster.

Value

`seqParallelSetup()` has no return, and `seqGetParallel()` returns `getOption("seqarray.parallel", FALSE)`.

Author(s)

Xiuwen Zheng

See Also

[seqParallel](#), [seqApply](#)

Examples

```
library(parallel)

seqParallelSetup(2L)

# the GDS file
(gds.fn <- seqExampleFileName("gds"))

# display
(f <- seqOpen(gds.fn))

# run in parallel
summary(seqMissing(f))

# close the GDS file
seqClose(f)
```

```
seqParallelSetup(FALSE)
```

```
seqRecompress          Recompress the GDS file
```

Description

Recompress the SeqArray GDS file.

Usage

```
seqRecompress(gds.fn, compress=c("ZIP", "LZ4", "LZMA", "Ultra", "UltraMax", "none"),
  exclude=character(), optimize=TRUE, verbose=TRUE)
```

Arguments

<code>gds.fn</code>	the file name of SeqArray file
<code>compress</code>	the compression method, <code>compress="ZIP"</code> by default
<code>exclude</code>	a list of GDS nodes to be excluded, see details
<code>optimize</code>	if TRUE, optimize the access efficiency by calling cleanup.gds
<code>verbose</code>	if TRUE, show information

Details

This function requires `gdsfmt` (\geq v1.17.2). [seqVCF2GDS](#) usually takes lots of memory when the compression method `"LZMA_RA.max"`, `"Ultra"` or `"UltraMax"` is specified. So users could call `seqVCF2GDS(, storage.option="ZIP_RA")` first, and then recompress the GDS file with a higher compression option, e.g., `"UltraMax"`. `seqRecompress()` takes much less memory, since it recompresses data in a GDS node each time.

`ls.gdsn(gdsfile, include.hidden=TRUE, recursive=TRUE)` returns a list of GDS nodes to be re-compressed, and users can specify the excluded nodes in the argument `exclude`.

Value

None.

Author(s)

Xiuwen Zheng

See Also

[seqVCF2GDS](#), [seqStorageOption](#)

Examples

```
gds.fn <- seqExampleFileName("gds")
file.copy(gds.fn, "tmp.gds")

seqRecompress("tmp.gds", "LZMA")

unlink("tmp.gds")
```

seqResetVariantID	<i>Reset Variant ID in SeqArray GDS Files</i>
-------------------	---

Description

Resets the variant IDs in multiple SeqArray GDS files.

Usage

```
seqResetVariantID(gds.fn, set=NULL, digest=TRUE, optimize=TRUE, verbose=TRUE)
```

Arguments

<code>gds.fn</code>	a character vector of multiple GDS file names
<code>set</code>	NULL or a logical vector; NULL for resetting all files, or TRUE for resetting variant.id for that GDS file
<code>digest</code>	a logical value, if TRUE, add a md5 hash code
<code>optimize</code>	if TRUE, optimize the access efficiency by calling cleanup.gds
<code>verbose</code>	if TRUE, show information

Details

The variant IDs will be replaced by the numbers in sequential order and adjacent to each file. The variant ID starts from 1 in the first GDS file.

Value

None.

Author(s)

Xiuwen Zheng

See Also

[seqVCF2GDS](#)

Examples

```
fn <- seqExampleFileName("gds")

file.copy(fn, "tmp1.gds", overwrite=TRUE)
file.copy(fn, "tmp2.gds", overwrite=TRUE)

gds.fn <- c("tmp1.gds", "tmp2.gds")
seqResetVariantID(gds.fn)

f <- seqOpen("tmp1.gds")
head(seqGetData(f, "variant.id"))
seqClose(f)

f <- seqOpen("tmp2.gds")
```

```
head(seqGetData(f, "variant.id"))
seqClose(f)
```

```
# delete the temporary files
unlink(gds.fn, force=TRUE)
```

seqSetFilter-methods *Set a Filter to Sample or Variant*

Description

Sets a filter to sample and/or variant.

Usage

```
## S4 method for signature 'SeqVarGDSCClass,ANY'
seqSetFilter(object, variant.sel,
             sample.sel=NULL, variant.id=NULL, sample.id=NULL,
             action=c("set", "intersect", "push", "push+set", "push+intersect", "pop"),
             verbose=TRUE)
## S4 method for signature 'SeqVarGDSCClass,GRanges'
seqSetFilter(object, variant.sel,
             rm.txt="chr", intersect=FALSE, verbose=TRUE)
## S4 method for signature 'SeqVarGDSCClass,GRangesList'
seqSetFilter(object, variant.sel,
             rm.txt="chr", intersect=FALSE, verbose=TRUE)
## S4 method for signature 'SeqVarGDSCClass,IRanges'
seqSetFilter(object, variant.sel,
             chr, intersect=FALSE, verbose=TRUE)
seqResetFilter(object, sample=TRUE, variant=TRUE, verbose=TRUE)
seqSetFilterChrom(object, include=NULL, is.num=NA, from.bp=NULL, to.bp=NULL,
                 intersect=FALSE, verbose=TRUE)
seqSetFilterPos(object, chr, pos, intersect=FALSE, multi.pos=FALSE,
                verbose=TRUE)
seqSetFilterAnnotID(object, id, verbose=TRUE)
```

Arguments

object	a SeqVarGDSCClass object
variant.sel	a logical/raw/index vector indicating the selected variants; GRanges , a GRanges object for the genomic locations; GRangesList , a GRangesList object for storing a collection of GRanges objects; IRanges , a IRanges object for storing a collection of range objects
sample.sel	a logical/raw/index vector indicating the selected samples
variant.id	ID of selected variants
sample.id	ID of selected samples
action	"set" – set the current filter via <code>sample.id</code> , <code>variant.id</code> , <code>samp.sel</code> or <code>variant.sel</code> ; "intersect" – set the current filter to the intersection of selected samples and/or variants; "push" – push the current filter to the stack, and it could be

	recovered by "pop" later, no change on the current filter; "push+set" – push the current filter to the stack, and changes the current filter via <code>sample.id</code> , <code>variant.id</code> , <code>samp.sel</code> or <code>variant.sel</code> ; "push+intersect" – push the current filter to the stack, and set the current filter to the intersection of selected samples and/or variants; "pop" – pop up the last filter
<code>rm.txt</code>	a character, the characters will be removed from <code>seqnames(variant.sel)</code>
<code>chr</code>	a vector of character for chromosome coding
<code>pos</code>	a vector of numeric values for genome coordinate
<code>sample</code>	logical, if TRUE, include all samples
<code>variant</code>	logical, if TRUE, include all variants
<code>include</code>	NULL, or a vector of characters for specified chromosome(s)
<code>is.num</code>	a logical variable: TRUE, chromosome code is numeric; FALSE, chromosome is not numeric; <code>is.num=TRUE</code> is usually used to exclude non-autosomes
<code>from.bp</code>	NULL, no limit; a numeric vector, the lower bound of position
<code>to.bp</code>	NULL, no limit; a numeric vector, the upper bound of position
<code>intersect</code>	if FALSE, the candidate samples/variants for selection are all samples/variants (by default); if TRUE, the candidate samples/variants are from the selected samples/variants defined via the previous call
<code>multi.pos</code>	FALSE, use the first matched position; TRUE, allow multiple variants at the same position
<code>id</code>	a character vector for RS IDs (stored in "annotation/id")
<code>verbose</code>	if TRUE, show information

Details

`seqResetFilter(file)` is equivalent to `seqSetFilter(file)`, where the selection arguments in `seqSetFilter` are NULL.

If `from.bp` and `to.bp` has values, they should be equal-size as `include`. A trio of `include`, `from.bp` and `to.bp` indicates a region on human genomes. NA in `from.bp` is treated as 0, and NA in `to.bp` is treated as the maximum of integer ($2^{31} - 1$).

Value

None.

Author(s)

Xiuwen Zheng

See Also

[seqSetFilterChrom](#), [seqSetFilterCond](#), [seqGetFilter](#), [seqGetData](#), [seqApply](#)

Examples

```
# the GDS file
(gds.fn <- seqExampleFileName("gds"))

# display
(f <- seqOpen(gds.fn))
```

```

# get 'sample.id'
(samp.id <- seqGetData(f, "sample.id"))
# "NA06984" "NA06985" "NA06986" ...

# get 'variant.id'
head(variant.id <- seqGetData(f, "variant.id"))

# get 'chromosome'
table(seqGetData(f, "chromosome"))

# get 'allele'
head(seqGetData(f, "allele"))
# "T,C" "G,A" "G,A" ...

# set sample and variant filters
seqSetFilter(f, sample.id=samp.id[c(2,4,6,8)])
set.seed(100)
seqSetFilter(f, variant.id=sample(variant.id, 5))

# get genotypic data
seqGetData(f, "genotype")

## OR
# set sample and variant filters
seqSetFilter(f, sample.sel=c(2,4,6,8))
set.seed(100)
seqSetFilter(f, variant.sel=sample.int(length(variant.id), 5))

# get genotypic data
seqGetData(f, "genotype")

## set the intersection

seqResetFilter(f)
seqSetFilterChrom(f, 10L)
seqSummary(f, "genotype", check="none")

AF <- seqAlleleFreq(f)
table(AF <= 0.9)

seqSetFilter(f, variant.sel=(AF<=0.9), action="intersect")
seqSummary(f, "genotype", check="none")

## chromosome

seqResetFilter(f)

seqSetFilterChrom(f, is.num=TRUE)
seqSummary(f, "genotype", check="none")

```

```

seqSetFilterChrom(f, is.num=FALSE)
seqSummary(f, "genotype", check="none")

seqSetFilterChrom(f, 1:4)
seqSummary(f, "genotype", check="none")
table(seqGetData(f, "chromosome"))

# HLA region
seqSetFilterChrom(f, 6, from.bp=29719561, to.bp=32883508)
seqSummary(f, "genotype", check="none")

# two regions
seqSetFilterChrom(f, c(1, 6), from.bp=c(1000000, 29719561),
  to.bp=c(90000000, 32883508))
seqSummary(f, "genotype", check="none")
seqGetData(f, "chromosome")

## intersection option

seqResetFilter(f)
seqSetFilterChrom(f, 6, from.bp=29719561, to.bp=32883508) # MHC
seqSetFilterChrom(f, include=6) # chromosome 6

seqResetFilter(f)
seqSetFilterChrom(f, 6, from.bp=29719561, to.bp=32883508) # MHC
seqSetFilterChrom(f, include=6, intersect=TRUE) # MHC region only

# close the GDS file
seqClose(f)

```

seqSetFilterCond *Set a Filter to Variant with Allele Count/Freq*

Description

Sets a filter to variant with specified allele count/frequency and missing rate.

Usage

```
seqSetFilterCond(gdsfile, maf=NaN, mac=1L, missing.rate=NaN,
  parallel=seqGetParallel(), .progress=FALSE, verbose=TRUE)
```

Arguments

gdsfile	a SeqVarGDSCClass object
maf	minimum minor reference allele frequency, or a range of MAF <code>maf[1] <= ... < maf[2]</code>
mac	minimum minor reference allele count, or a range of MAC <code>mac[1] <= ... < mac[2]</code>
missing.rate	maximum missing genotype rate

<code>.progress</code>	if TRUE, show progress information
<code>parallel</code>	FALSE (serial processing), TRUE (multicore processing), numeric value or other value; <code>parallel</code> is passed to the argument <code>cl</code> in seqParallel , see seqParallel for more details.
<code>verbose</code>	if TRUE, show information

Value

None.

Author(s)

Xiuwen Zheng

See Also

[seqSetFilter](#), [seqSetFilterChrom](#), [seqAlleleFreq](#), [seqAlleleCount](#), [seqMissing](#)

Examples

```
# the GDS file
(gds.fn <- seqExampleFileName("gds"))

# display
(f <- seqOpen(gds.fn))

seqSetFilterChrom(f, c(1, 6))
seqSetFilterCond(f, maf=0.05, .progress=TRUE)

seqSetFilterChrom(f, c(1, 6))
seqSetFilterCond(f, maf=c(0.01, 0.05), .progress=TRUE)

# close the GDS file
seqClose(f)
```

seqSNP2GDS

Convert SNPRelate Format to SeqArray Format

Description

Converts a SNP GDS file to a SeqArray GDS file.

Usage

```
seqSNP2GDS(gds.fn, out.fn, storage.option="LZMA_RA", major.ref=TRUE,
  ds.type=c("packedreal16", "float", "double"), optimize=TRUE, digest=TRUE,
  verbose=TRUE)
```

Arguments

<code>gds.fn</code>	the file name of SNP format
<code>out.fn</code>	the file name, output a file of SeqArray format
<code>storage.option</code>	specify the storage and compression options, "LZMA_RA" to use LZMA compression algorithm with higher compression ratio compared to "ZIP_RA"
<code>major.ref</code>	if TRUE, use the major allele as a reference allele; otherwise, use A allele in SNP GDS file as a reference allele
<code>ds.type</code>	applicable when import dosages, the data type for storing dosages; see add.gdsn ; <code>ds.type="packedreal16"</code> by default
<code>optimize</code>	if TRUE, optimize the access efficiency by calling cleanup.gds
<code>digest</code>	a logical value (TRUE/FALSE) or a character ("md5", "sha1", "sha256", "sha384" or "sha512"); add hash codes to the GDS file if TRUE or a digest algorithm is specified
<code>verbose</code>	if TRUE, show information

Value

Return the file name of SeqArray file with an absolute path. If the input file is genotype dosage, the dosage matrix is stored in the node `annotation/format/DS` with the estimated dosage of alternative alleles. Any value less than 0 or greater than 2 will be replaced by NaN.

Author(s)

Xiuwen Zheng

See Also

[seqGDS2SNP](#), [seqVCF2GDS](#), [seqGDS2VCF](#), [seqBED2GDS](#)

Examples

```
library(SNPrelate)

# the GDS file
gds.fn <- snpgdsExampleFileName()

seqSNP2GDS(gds.fn, "tmp.gds")

seqSummary("tmp.gds")

# remove the temporary file
unlink("tmp.gds", force=TRUE)
```

seqStorageOption *Storage and Compression Options*

Description

Storage and compression options for GDS import and merging.

Usage

```
seqStorageOption(compression=c("ZIP_RA", "ZIP_RA.fast", "ZIP_RA.max", "LZ4_RA",
    "LZ4_RA.fast", "LZ4_RA.max", "LZMA_RA", "LZMA_RA.fast", "LZMA_RA.max",
    "Ultra", "UltraMax", "none"), mode=NULL, float.mode="float32",
    geno.compress=NULL, info.compress=NULL, format.compress=NULL,
    index.compress=NULL, ...)
```

Arguments

compression	the default compression level ("ZIP_RA"), see add.gdsn for the description of compression methods
mode	a character vector, specifying storage type for corresponding variable, e.g., c('annotation/info/HM'='int', 'annotation/format/PL'='int')
float.mode	specify the storage mode for read numbers, e.g., "float32", "float64", "packedreal16"; the additional parameters can follow by colon, like "packedreal16:scale=0.0001"
geno.compress	NULL for the default value, or the compression method for genotypic data
info.compress	NULL for the default value, or the compression method for data sets stored in the INFO field (i.e., "annotation/info")
format.compress	NULL for the default value, or the compression method for data sets stored in the FORMAT field (i.e., "annotation/format")
index.compress	NULL for the default value, or the compression method for data index variables (e.g., "annotation/info/@HM")
...	other specified storage compression for corresponding variable, e.g., 'annotation/info/HM'="ZIP_MAX"

Details

The compression modes "Ultra" and "UltraMax" attempt to maximize the compression ratio using gigabyte-sized or even terabyte-sized virtual memory, according to "LZMA_RA.ultra" and "LZMA_RA.ultra_max" in [compression.gdsn](#). These features require gdsfmt (>=v1.16.0). "Ultra" and "UltraMax" may not increase the compression ratio much compared with "LZMA_RA.max", and these options are designed for the users who want to exhaust the computational resources.

Value

Return a list with a class name "SeqGDSSStorageClass", contains the compression algorithm for each data type.

Author(s)

Xiuwen Zheng

See Also

[seqVCF2GDS](#), [seqRecompress](#), [seqMerge](#)

Examples

```
# the file of VCF
(vcf.fn <- seqExampleFileName("vcf"))

# convert
seqVCF2GDS(vcf.fn, "tmp1.gds", storage.option=seqStorageOption())
(f1 <- seqOpen("tmp1.gds"))

# convert (maximize the compression ratio)
seqVCF2GDS(vcf.fn, "tmp2.gds", storage.option=seqStorageOption("ZIP_RA.max"))
(f2 <- seqOpen("tmp2.gds"))

# does not compress the genotypic data
seqVCF2GDS(vcf.fn, "tmp3.gds", storage.option=
  seqStorageOption("ZIP_RA", geno.compress=""))
(f3 <- seqOpen("tmp3.gds"))

# compress with LZ4
seqVCF2GDS(vcf.fn, "tmp4.gds", storage.option=seqStorageOption("LZ4_RA"))
(f4 <- seqOpen("tmp4.gds"))

# close and remove the files
seqClose(f1)
seqClose(f2)
seqClose(f3)
seqClose(f4)

unlink(c("tmp1.gds", "tmp2.gds", "tmp3.gds", "tmp4.gds"))
```

seqSummary

Summarize a SeqArray GDS File

Description

Gets the summary of SeqArray GDS file.

Usage

```
seqSummary(gdsfile, varname=NULL, check=c("default", "none", "full"),
  verbose=TRUE)
```

Arguments

gdsfile	a SeqVarGDSClass object, or a file name
varname	if NULL, check the whole GDS file; or a character specifying variable name, and return a description of that variable. See details
check	should be one of "default", "none", "full"; check="default" by default
verbose	if TRUE, display information

Details

If `check="default"`, the function performs regular checking, like variable dimensions. If `check="full"`, it performs more checking, e.g., unique sample id, unique variant id, whether genotypic data are in a valid range or not.

Value

If `varname=NULL`, the function returns a list:

<code>filename</code>	the file name
<code>version</code>	the version of SeqArray format
<code>reference</code>	genome reference, a character vector (0-length for undefined)
<code>ploidy</code>	the number of sets of chromosomes
<code>num.sample</code>	the total number of samples
<code>num.variant</code>	the total number of variants
<code>allele</code>	allele information, see <code>seqSummary(gdsfile, "allele")</code>
<code>annot_qual</code>	the total number of "annotation/qual" if <code>check="none"</code> , or a summary object including min, max, median, mean
<code>filter</code>	filter information, see <code>seqSummary(gdsfile, "annotation/filter")</code>
<code>info</code>	a <code>data.frame</code> of INFO field: ID, Number, Type, Description, Source and Version
<code>format</code>	a <code>data.frame</code> of FORMAT field: ID, Number, Type and Description
<code>sample.annot</code>	a <code>data.frame</code> of sample annotation with ID, Type and Description

— `seqSummary(gdsfile, "genotype", check="none", verbose=FALSE)` returns a list with components:

<code>dim</code>	an integer vector: ploidy, # of samples, # of variants
<code>seldim</code>	an integer vector: ploidy, # of selected samples, # of selected variants

— `seqSummary(gdsfile, "allele")` returns a `data.frame` with ID and descriptions (`check="none"`), or a list with components:

<code>value</code>	a <code>data.frame</code> with ID and Description
<code>table</code>	cross tabulation for the number of alleles per site

— `seqSummary(gdsfile, "$alt")` returns a `data.frame` with ID and Description for describing the alternative alleles.

— `seqSummary(gdsfile, "annotation/filter")` or `seqSummary(gdsfile, "$filter")` returns a `data.frame` with ID and description (`check="none"`), or a list with components: `value` (a `data.frame` with ID and Description), `table` (cross tabulation for the variable 'filter').

— `seqSummary(gdsfile, "annotation/info")` or `seqSummary(gdsfile, "$info")` returns a `data.frame` describing the variables in the folder "annotation/info" with ID, Number, Type, Description, Source and Version.

— `seqSummary(gdsfile, "annotation/format")` returns a `data.frame` describing the variables in the folder "annotation/format" with ID, Number, Type and Description.

— `seqSummary(gdsfile, "sample.annotation")` returns a `data.frame` describing sample annotation with ID, Type and Description.

- seqSummary(gdsfile, "\$reference") returns the genome reference if it is defined (a 0-length character vector if undefined).
- seqSummary(gdsfile, "\$contig") returns the contig information, a data.frame including ID.
- seqSummary(gdsfile, "\$format") returns a data.frame describing VCF FORMAT header with ID, Number, Type and Description. The first row is used for genotypes.
- seqSummary(gdsfile, "\$digest") returns a data.frame with the full names of GDS variables, digest codes and validation (FALSE/TRUE).

Author(s)

Xiuwen Zheng

See Also

[seqGetData](#), [seqApply](#)

Examples

```
# the GDS file
(gds.fn <- seqExampleFileName("gds"))

seqSummary(gds.fn)

ans <- seqSummary(gds.fn, check="full")
ans

seqSummary(gds.fn, "genotype")
seqSummary(gds.fn, "allele")
seqSummary(gds.fn, "annotation/filter")
seqSummary(gds.fn, "annotation/info")
seqSummary(gds.fn, "annotation/format")
seqSummary(gds.fn, "sample.annotation")

seqSummary(gds.fn, "$reference")
seqSummary(gds.fn, "$contig")
seqSummary(gds.fn, "$filter")
seqSummary(gds.fn, "$alt")
seqSummary(gds.fn, "$info")
seqSummary(gds.fn, "$format")
seqSummary(gds.fn, "$digest")

# open a GDS file
f <- seqOpen(gds.fn)

# get 'sample.id'
samp.id <- seqGetData(f, "sample.id")
# get 'variant.id'
variant.id <- seqGetData(f, "variant.id")

# set sample and variant filters
seqSetFilter(f, sample.id=samp.id[c(2,4,6,8,10)])
set.seed(100)
seqSetFilter(f, variant.id=sample(variant.id, 10))
```

```
seqSummary(f, "genotype")

# close a GDS file
seqClose(f)
```

seqSystem	<i>Get the parameters in the GDS system</i>
-----------	---

Description

Get a list of parameters in the GDS system

Usage

```
seqSystem()
```

Value

A list including

num.logical.core	the number of logical cores
compiler.flag	SIMD instructions supported by the compiler
options	list all options associated with SeqArray GDS format or packages

Author(s)

Xiuwen Zheng

References

<http://github.com/zhengxwen/SeqArray>

Examples

```
seqSystem()
```

seqTranspose	<i>Transpose Data Array</i>
--------------	-----------------------------

Description

Transpose data array or matrix for possibly higher-speed access.

Usage

```
seqTranspose(gdsfile, var.name, compress=NULL, digest=TRUE, verbose=TRUE)
```

Arguments

<code>gdsfile</code>	a SeqVarGDSClass object
<code>var.name</code>	the variable name with <code>'/'</code> as a separator
<code>compress</code>	the compression option used in add.gdsn ; or determine automatically if NULL
<code>digest</code>	a logical value (TRUE/FALSE) or a character ("md5", "sha1", "sha256", "sha384" or "sha512"); add md5 hash codes to the GDS file if TRUE or a digest algorithm is specified
<code>verbose</code>	if TRUE, show information

Details

It is designed for possibly higher-speed access. More details will be provided in the future version.

Value

None.

Author(s)

Xiuwen Zheng

See Also

[seqGetData](#), [seqApply](#)

Examples

```
# the VCF file
(vcf.fn <- seqExampleFileName("vcf"))

# convert
seqVCF2GDS(vcf.fn, "tmp.gds", storage.option="ZIP_RA")

# list the structure of GDS variables
f <- seqOpen("tmp.gds", FALSE)
f

seqTranspose(f, "genotype/data")
f

# the original array
index.gdsn(f, "genotype/data")
# the transposed array
index.gdsn(f, "genotype/~data")

# close
seqClose(f)

# delete the temporary file
unlink("tmp.gds")
```

seqUnitApply

*Apply Function Over Variant Units***Description**

Applies a user-defined function to each variant unit.

Usage

```
seqUnitApply(gdsfile, units, var.name, FUN, as.is=c("none", "list", "unlist"),
             parallel=FALSE, ..., .bl_size=256L, .progress=FALSE, .useraw=FALSE,
             .padNA=TRUE, .tolist=FALSE, .envir=NULL)
```

Arguments

<code>gdsfile</code>	a SeqVarGDSClass object
<code>units</code>	a list of units of selected variants, with S3 class SeqUnitListClass
<code>var.name</code>	the variable name(s), see details
<code>FUN</code>	the function to be applied
<code>as.is</code>	returned value: a list, an integer vector, etc; return nothing by default <code>as.is="none"</code> ; <code>as.is</code> can be a connection object, or a GDS node gdsn.class object; if "unlist" is used, produces a vector which contains all the atomic components, via <code>unlist(..., recursive=FALSE)</code>
<code>parallel</code>	FALSE (serial processing), TRUE (multicore processing), numeric value or other value; <code>parallel</code> is passed to the argument <code>cl</code> in seqParallel , see seqParallel for more details.
<code>.bl_size</code>	chunk size, the increment for load balancing, 256 for units
<code>.progress</code>	if TRUE, show progress information
<code>.useraw</code>	TRUE, force to use RAW instead of INTEGER for genotypes and dosages; FALSE, use INTEGER; NA, use RAW instead of INTEGER if possible; for genotypes, 0xFF is missing value if RAW is used
<code>.padNA</code>	TRUE, pad a variable-length vector with NA if the number of data points for each variant is not greater than 1
<code>.tolist</code>	if TRUE, return a list of vectors instead of the structure <code>list(length, data)</code> for variable-length data
<code>.envir</code>	NULL, an environment object, or a list/data.frame
<code>...</code>	optional arguments to FUN

Details

The variable name should be "sample.id", "variant.id", "position", "chromosome", "allele", "genotype", "annotation/id", "annotation/qual", "annotation/filter", "annotation/info/VARIABLE_NAME" or "annotation/format/VARIABLE_NAME".

"@genotype", "annotation/info/@VARIABLE_NAME" or "annotation/format/@VARIABLE_NAME" are used to obtain the index associated with these variables.

"\$dosage" is also allowed for the dosages of reference allele (integer: 0, 1, 2 and NA for diploid genotypes).

"\$dosage_alt" returns a RAW/INTEGER matrix for the dosages of alternative allele without distinguishing different alternative alleles.

"\$num_allele" returns an integer vector with the numbers of distinct alleles.

"\$ref" returns a character vector of reference alleles

"\$alt" returns a character vector of alternative alleles (delimited by comma)

"\$chrom_pos" returns characters with the combination of chromosome and position, e.g., "1:1272721".

"\$chrom_pos_allele" returns characters with the combination of chromosome, position and alleles, e.g., "1:1272721_A_G" (i.e., chr:position_REF_ALT).

"\$variant_index" returns the indices of selected variants starting from 1, and "\$sample_index" returns the indices of selected samples starting from 1.

Value

A vector, a list of values or none.

Author(s)

Xiuwen Zheng

See Also

[seqUnitSlidingWindows](#), [seqUnitFilterCond](#)

Examples

```
# open the GDS file
gdsfile <- seqOpen(seqExampleFileName("gds"))

# variant units via sliding windows
units <- seqUnitSlidingWindows(gdsfile)

v1 <- seqUnitApply(gdsfile, units, "genotype", function(x) dim(x)[3L],
  as.is="unlist", .progress=TRUE)
v2 <- seqUnitApply(gdsfile, units, "genotype", function(x) dim(x)[3L],
  as.is="unlist", parallel=2, .progress=TRUE)

all(v1 == lengths(units$index))
all(v1 == v2)

# call with an external R variable
ext <- list(x=1:1348/10)
v3 <- seqUnitApply(gdsfile, units, "$:x", function(x) x,
  as.is="list", .progress=TRUE, .envir=ext)
head(units$index)
head(v3)

table(sapply(seq_along(units$index), function(i) all(units$index[[i]] == v3[[i]]*10)))
# all TRUE

# close the GDS file
seqClose(gdsfile)
```

seqUnitFilterCond *Filter unit variants*

Description

Filters out the unit variants according to MAF, MAC and missing rates.

Usage

```
seqUnitFilterCond(gdsfile, units, maf=NaN, mac=1L, missing.rate=NaN,
  minsize=1L, parallel=seqGetParallel(), verbose=TRUE)
```

Arguments

gdsfile	a SeqVarGDSClass object
units	a list of units of selected variants, with S3 class SeqUnitListClass
maf	minimum minor reference allele frequency, or a range of MAF <code>maf[1] <= ... < maf[2]</code>
mac	minimum minor reference allele count, or a range of MAC <code>mac[1] <= ... < mac[2]</code>
missing.rate	maximum missing genotype rate
minsize	the minimum of unit size
parallel	FALSE (serial processing), TRUE (multicore processing), numeric value or other value; <code>parallel</code> is passed to the argument <code>c1</code> in seqParallel , see seqParallel for more details.
verbose	if TRUE, show information

Value

A S3 object with the class name "SeqUnitListClass" and two components (`desp` and `index`): the first is a data.frame with columns "chr", "start" and "end", and the second is list of integer vectors (the variant indices).

Author(s)

Xiuwen Zheng

See Also

[seqUnitApply](#), [seqUnitFilterCond](#)

Examples

```
# open the GDS file
gdsfile <- seqOpen(seqExampleFileName("gds"))

unit1 <- seqUnitSlidingWindows(gdsfile)
unit1 # "desp" "index"

# only rare variants
```



```
newunit <- seqUnitFilterCond(gdsfile, unit1, maf=c(0, 0.01))
newunit

# excluded variants
exvar <- setdiff(unique(unlist(unit1$index)), unique(unlist(newunit$index)))

seqSetFilter(gdsfile, variant.sel=exvar)
maf <- seqAlleleFreq(gdsfile, minor=TRUE)
table(maf > 0)
summary(maf[maf > 0]) # > 0.01

# close the GDS file
seqClose(gdsfile)
```

seqUnitSlidingWindows *Sliding units of selected variants*

Description

Generates units of selected variants via sliding windows.

Usage

```
seqUnitSlidingWindows(gdsfile, win.size=5000L, win.shift=2500L, win.start=0L,
  dup.rm=TRUE, verbose=TRUE)
```

Arguments

gdsfile	a SeqVarGDSCClass object
win.size	window size in basepair
win.shift	the shift of sliding window in basepair
win.start	the start position in basepair
dup.rm	if TRUE, remove duplicate and zero-length windows
verbose	if TRUE, display information

Value

A S3 object with the class name "SeqUnitListClass" and two components (desp and index): the first is a data.frame with columns "chr", "start" and "end", and the second is list of integer vectors (the variant indices).

Author(s)

Xiuwen Zheng

See Also

[seqUnitApply](#), [seqUnitFilterCond](#)

Examples

```
# open the GDS file
gdsfile <- seqOpen(seqExampleFileName("gds"))

v <- seqUnitSlidingWindows(gdsfile)
v # "desp" "index"

# close the GDS file
seqClose(gdsfile)
```

SeqVarGDSClass

*SeqVarGDSClass***Description**

A SeqVarGDSClass object provides access to a GDS file containing Variant Call Format (VCF) data. It extends [gds.class](#).

Details

A SeqArray GDS file is created from a VCF file with [seqVCF2GDS](#). This file can be opened with [seqOpen](#) to create a SeqVarGDSClass object.

Accessors

In the following code snippets `x` is a SeqVarGDSClass object.

`granges(x)`: Returns the chromosome and position of variants as a GRanges object. Names correspond to the variant.id.

`ref(x)`: Returns the reference alleles as a DNASTringSet.

`alt(x)`: Returns the alternate alleles as a DNASTringSetList.

`qual(x)`: Returns the quality scores.

`filt(x)`: Returns the filter data.

`fixed(x)`: Returns the fixed fields (ref, alt, qual, filt).

`header(x)`: Returns the header as a DataFramelist.

`rowRanges(x)`: Returns a GRanges object with metadata.

`colData(x)`: Returns a DataFrame with sample identifiers and any information in the 'sample.annotation' node.

`info(x, info=NULL)`: Returns the info fields as a DataFrame. `info` is a character vector with the names of fields to return (default is to return all).

`geno(x, geno=NULL)`: Returns the geno (format) fields as a SimpleList. `geno` is a character vector with the names of fields to return (default is to return all).

Other data can be accessed with [seqGetData](#).

Coercion methods

In the following code snippets `x` is a SeqVarGDSClass object.

```
seqAsVCF(x, chr.prefix="", info=NULL, geno=NULL):
```

Author(s)

Stephanie Gogarten, Xiuwen Zheng

See Also

[gds.class](#), [seqOpen](#)

Examples

```
gds <- seqOpen(seqExampleFileName("gds"))
gds

## sample ID
head(seqGetData(gds, "sample.id"))

## variants
granges(gds)

## Not run:
## alleles as comma-separated character strings
head(seqGetData(gds, "allele"))

## alleles as DNStringSet or DNStringSetList
ref(gds)
v <- alt(gds)

## genotype
geno <- seqGetData(gds, "genotype")
dim(geno)
## dimensions are: allele, sample, variant
geno[1,1:10,1:5]

## rsID
head(seqGetData(gds, "annotation/id"))

## alternate allele count
head(seqGetData(gds, "annotation/info/AC"))

## individual read depth
depth <- seqGetData(gds, "annotation/format/DP")
names(depth)
## VCF header defined DP as variable-length data
table(depth$length)
## all length 1, so depth$data should be a sample by variant matrix
dim(depth$data)
depth$data[1:10,1:5]

## End(Not run)

seqClose(gds)
```

Description

Reformats Variant Call Format (VCF) files.

Usage

```
seqVCF2GDS(vcf.fn, out.fn, header=NULL, storage.option="LZMA_RA",
  info.import=NULL, fmt.import=NULL, genotype.var.name="GT",
  ignore.chr.prefix="chr", scenario=c("general", "imputation"),
  reference=NULL, start=1L, count=-1L, optimize=TRUE, raise.error=TRUE,
  digest=TRUE, parallel=FALSE, verbose=TRUE)
seqBCF2GDS(bcf.fn, out.fn, header=NULL, storage.option="LZMA_RA",
  info.import=NULL, fmt.import=NULL, genotype.var.name="GT",
  ignore.chr.prefix="chr", scenario=c("general", "imputation"),
  reference=NULL, optimize=TRUE, raise.error=TRUE, digest=TRUE,
  bcftools="bcftools", verbose=TRUE)
```

Arguments

vcf.fn	the file name(s) of VCF format; or a connection object
bcf.fn	a file name of binary VCF format (BCF)
out.fn	the file name of output GDS file
header	if NULL, header is set to be seqVCF_Header (vcf.fn)
storage.option	specify the storage and compression option, "ZIP_RA" (seqStorageOption ("ZIP_RA")); or "LZMA_RA" to use LZMA compression algorithm with higher compression ratio by default; or "LZ4_RA" to use an extremely fast compression and decompression algorithm. "ZIP_RA.max", "LZMA_RA.max" and "LZ4_RA.max" correspond to the algorithms with a maximum compression level; the suffix "_RA" indicates that fine-level random access is available; see more details at seqStorageOption
info.import	characters, the variable name(s) in the INFO field for import; or NULL for all variables
fmt.import	characters, the variable name(s) in the FORMAT field for import; or NULL for all variables
genotype.var.name	the ID for genotypic data in the FORMAT column; "GT" by default, VCFv4.0
ignore.chr.prefix	a vector of character, indicating the prefix of chromosome which should be ignored, like "chr"; it is not case-sensitive
scenario	"general": use float32 to store floating-point numbers (by default); "imputation": use packedreal16 to store DS and GP in the FORMAT field with four decimal place accuracy
reference	genome reference, like "hg19", "GRCh37"; if the genome reference is not available in VCF files, users could specify the reference here
start	the starting variant if importing part of VCF files
count	the maximum count of variant if importing part of VCF files, -1 indicates importing to the end
optimize	if TRUE, optimize the access efficiency by calling cleanup.gds
raise.error	TRUE: throw an error if numeric conversion fails; FALSE: get missing value if numeric conversion fails

digest	a logical value (TRUE/FALSE) or a character ("md5", "sha1", "sha256", "sha384" or "sha512"); add md5 hash codes to the GDS file if TRUE or a digest algorithm is specified
parallel	FALSE (serial processing), TRUE (parallel processing), a numeric value indicating the number of cores, or a cluster object for parallel processing; parallel is passed to the argument c1 in seqParallel , see seqParallel for more details
verbose	if TRUE, show information
bcftools	the path of the program bcftools

Details

If there are more than one files in `vcf.fn`, `seqVCF2GDS` will merge all VCF files together if they contain the same samples. It is useful to merge multiple VCF files if variant data are split by chromosomes.

The real numbers in the VCF file(s) are stored in 32-bit floating-point format by default. Users can set `storage.option=seqStorageOption(float.mode="float64")` to switch to 64-bit floating point format. Or packed real numbers can be adopted by setting `storage.option=seqStorageOption(float.mode="pa`

By default, the compression method is "LZMA_RA" (<http://tukaani.org/xz>, LZMA algorithm with default compression level + independent data blocks for fine-level random access). Users can maximize the compression ratio by `storage.option="LZMA_RA.max"` or `storage.option=seqStorageOption("LZMA_RA.max")`. LZMA is known to have higher compression ratio than the zlib algorithm. LZ4 (<https://github.com/lz4/lz4>) is an option via `storage.option="LZ4_RA"` or `storage.option=seqStorageOption("LZ4_RA")`.

If multiple cores/processes are specified in `parallel`, all VCF files are scanned to calculate the total number of variants before format conversion, and then split by the number of cores/processes.

`storage.option="Ultra"` and `storage.option="UltraMax"` need much larger memory than other compression methods. Users may consider using [seqRecompress](#) to recompress the GDS file after calling `seqVCF2GDS()` with `storage.option="ZIP_RA"`, since `seqRecompress()` compresses data nodes one by one, taking much less memory than "Ultra" and "UltraMax".

If `storage.option="LZMA_RA"` runs out of memory (e.g., there are too many annotation fields in the VCF file), users could use `storage.option="ZIP_RA"` and then call `seqRecompress(,compress="LZMA")`.

Value

Return the file name of GDS format with an absolute path.

Author(s)

Xiuwen Zheng

References

Danecek, P., Auton, A., Abecasis, G., Albers, C.A., Banks, E., DePristo, M.A., Handsaker, R.E., Lunter, G., Marth, G.T., Sherry, S.T., et al. (2011). The variant call format and VCFtools. *Bioinformatics* 27, 2156-2158.

See Also

[seqVCF_Header](#), [seqStorageOption](#), [seqMerge](#), [seqGDS2VCF](#), [seqRecompress](#)

Examples

```

# the VCF file
vcf.fn <- seqExampleFileName("vcf")

# conversion
seqVCF2GDS(vcf.fn, "tmp.gds", storage.option="ZIP_RA")

# conversion in parallel
seqVCF2GDS(vcf.fn, "tmp_p2.gds", storage.option="ZIP_RA", parallel=2L)

# display
(f <- seqOpen("tmp.gds"))
seqClose(f)

# convert without the INFO fields
seqVCF2GDS(vcf.fn, "tmp.gds", storage.option="ZIP_RA",
  info.import=character(0))

# display
(f <- seqOpen("tmp.gds"))
seqClose(f)

# convert without the INFO and FORMAT fields
seqVCF2GDS(vcf.fn, "tmp.gds", storage.option="ZIP_RA",
  info.import=character(0), fmt.import=character(0))

# display
(f <- seqOpen("tmp.gds"))
seqClose(f)

# delete the temporary file
unlink(c("tmp.gds", "tmp_p2.gds"), force=TRUE)

```

seqVCF_Header

*Parse the Header of a VCF/BCF File***Description**

Parses the meta-information lines of a VCF or BCF file.

Usage

```
seqVCF_Header(vcf.fn, getnum=FALSE)
```

Arguments

vcf.fn	the file name of VCF or BCF format; or a connection object for VCF format
getnum	if TRUE, return the total number of variants

Details

The ID description contains four columns: ID – variable name; Number – the number of elements, see the webpage of the 1000 Genomes Project; Type – data type; Description – a variable description.

Value

Return a list (with a class name "SeqVCFHeaderClass", S3 object):

fileformat	the file format
info	the ID description in the INFO field
filter	the ID description in the FILTER field
format	the ID description in the FORMAT field
alt	the ID description in the ALT field
contig	the description in the contig field
assembly	the link of assembly
reference	genome reference, or NULL if unknown
header	the other header lines
ploidy	ploidy, two for humans
num.sample	the number of samples
num.variant	the number of variants, applicable only if getnum=TRUE
sample.id	a vector of sample IDs in the VCF/BCF file

Author(s)

Xiuwen Zheng

References

Danecek, P., Auton, A., Abecasis, G., Albers, C.A., Banks, E., DePristo, M.A., Handsaker, R.E., Lunter, G., Marth, G.T., Sherry, S.T., et al. (2011). The variant call format and VCFtools. *Bioinformatics* 27, 2156-2158.

See Also

[seqVCF_SampID](#), [seqVCF2GDS](#)

Examples

```
# the VCF file
(vcf.fn <- seqExampleFileName("vcf"))
# or vcf.fn <- "C:/YourFolder/Your_VCF_File.vcf"

# get sample id
seqVCF_Header(vcf.fn, getnum=TRUE)

# use a connection object
f <- file(vcf.fn, "r")
seqVCF_Header(f, getnum=TRUE)
close(f)
```

seqVCF_SampID	<i>Get the Sample IDs</i>
---------------	---------------------------

Description

Returns the sample IDs of a VCF file.

Usage

```
seqVCF_SampID(vcf.fn)
```

Arguments

vcf.fn the file name, output a file of VCF format; or a [connection](#) object

Author(s)

Xiuwen Zheng

References

Danecek, P., Auton, A., Abecasis, G., Albers, C.A., Banks, E., DePristo, M.A., Handsaker, R.E., Lunter, G., Marth, G.T., Sherry, S.T., et al. (2011). The variant call format and VCFtools. *Bioinformatics* 27, 2156-2158.

See Also

[seqVCF_Header](#), [seqVCF2GDS](#)

Examples

```
# the VCF file
(vcf.fn <- seqExampleFileName("vcf"))

# get sample id
seqVCF_SampID(vcf.fn)
```


Index

* VCF

- seqExport, [21](#)
- seqGDS2VCF, [24](#)
- seqVCF2GDS, [59](#)
- seqVCF_Header, [62](#)
- seqVCF_SampID, [64](#)

* gds

- KG_P1_SampData, [5](#)
- seqAddValue, [5](#)
- seqAlleleFreq, [7](#)
- seqApply, [9](#)
- SeqArray-package, [3](#)
- seqAsVCF, [12](#)
- seqBED2GDS, [13](#)
- seqBlockApply, [14](#)
- seqCheck, [17](#)
- seqClose-methods, [18](#)
- seqDelete, [18](#)
- seqDigest, [19](#)
- seqExampleFileName, [20](#)
- seqExport, [21](#)
- seqGDS2SNP, [22](#)
- seqGDS2VCF, [24](#)
- seqGetData, [26](#)
- seqGetFilter, [28](#)
- seqMerge, [30](#)
- seqMissing, [32](#)
- seqNumAllele, [33](#)
- seqOpen, [34](#)
- seqOptimize, [35](#)
- seqParallel, [36](#)
- seqParallelSetup, [38](#)
- seqRecompress, [40](#)
- seqResetVariantID, [41](#)
- seqSetFilter-methods, [42](#)
- seqSetFilterCond, [45](#)
- seqSNP2GDS, [46](#)
- seqStorageOption, [48](#)
- seqSummary, [49](#)
- seqSystem, [52](#)
- seqTranspose, [52](#)
- seqUnitApply, [54](#)
- seqUnitFilterCond, [56](#)

- seqUnitSlidingWindows, [57](#)
- seqVCF2GDS, [59](#)
- seqVCF_Header, [62](#)
- seqVCF_SampID, [64](#)

* genetics

- KG_P1_SampData, [5](#)
- seqAddValue, [5](#)
- seqAlleleFreq, [7](#)
- seqApply, [9](#)
- SeqArray-package, [3](#)
- seqAsVCF, [12](#)
- seqBED2GDS, [13](#)
- seqBlockApply, [14](#)
- seqCheck, [17](#)
- seqClose-methods, [18](#)
- seqDelete, [18](#)
- seqDigest, [19](#)
- seqExampleFileName, [20](#)
- seqExport, [21](#)
- seqGDS2SNP, [22](#)
- seqGDS2VCF, [24](#)
- seqGetData, [26](#)
- seqGetFilter, [28](#)
- seqMerge, [30](#)
- seqMissing, [32](#)
- seqNumAllele, [33](#)
- seqOpen, [34](#)
- seqOptimize, [35](#)
- seqParallel, [36](#)
- seqParallelSetup, [38](#)
- seqRecompress, [40](#)
- seqResetVariantID, [41](#)
- seqSetFilter-methods, [42](#)
- seqSetFilterCond, [45](#)
- seqSNP2GDS, [46](#)
- seqStorageOption, [48](#)
- seqSummary, [49](#)
- seqSystem, [52](#)
- seqTranspose, [52](#)
- seqUnitApply, [54](#)
- seqUnitFilterCond, [56](#)
- seqUnitSlidingWindows, [57](#)
- seqVCF2GDS, [59](#)

- seqVCF_Header, 62
- seqVCF_SampID, 64
- * **sequencing**
 - KG_P1_SampData, 5
 - seqAddValue, 5
 - seqAlleleFreq, 7
 - seqApply, 9
 - SeqArray-package, 3
 - seqAsVCF, 12
 - seqBED2GDS, 13
 - seqBlockApply, 14
 - seqCheck, 17
 - seqClose-methods, 18
 - seqDelete, 18
 - seqDigest, 19
 - seqExampleFileName, 20
 - seqExport, 21
 - seqGDS2SNP, 22
 - seqGDS2VCF, 24
 - seqGetData, 26
 - seqGetFilter, 28
 - seqMerge, 30
 - seqMissing, 32
 - seqNumAllele, 33
 - seqOpen, 34
 - seqOptimize, 35
 - seqParallel, 36
 - seqParallelSetup, 38
 - seqRecompress, 40
 - seqResetVariantID, 41
 - seqSetFilter-methods, 42
 - seqSetFilterCond, 45
 - seqSNP2GDS, 46
 - seqStorageOption, 48
 - seqSummary, 49
 - seqSystem, 52
 - seqTranspose, 52
 - seqUnitApply, 54
 - seqUnitFilterCond, 56
 - seqUnitSlidingWindows, 57
 - seqVCF2GDS, 59
 - seqVCF_Header, 62
 - seqVCF_SampID, 64
- add.gdsn, 6, 23, 47, 48, 53
- alt (SeqVarGDSCClass), 58
- alt, SeqVarGDSCClass-method (SeqVarGDSCClass), 58
- bgzip, 24
- cleanup.gds, 13, 21, 23, 30, 40, 41, 47, 60
- clusterApply, 37
- clusterApplyLB, 37
- colData (SeqVarGDSCClass), 58
- colData, SeqVarGDSCClass-method (SeqVarGDSCClass), 58
- CollapsedVCF, 12
- compression.gdsn, 48
- connection, 9, 15, 24, 54, 60, 62, 64
- DataFrameList, 58
- DNAStrngSet, 58
- DNAStrngSetList, 58
- filt (SeqVarGDSCClass), 58
- filt, SeqVarGDSCClass-method (SeqVarGDSCClass), 58
- fixed (SeqVarGDSCClass), 58
- fixed, SeqVarGDSCClass-method (SeqVarGDSCClass), 58
- gds.class, 18, 34, 58, 59
- gdsn.class, 9, 15, 54
- geno (SeqVarGDSCClass), 58
- geno, SeqVarGDSCClass, ANY-method (SeqVarGDSCClass), 58
- geno, SeqVarGDSCClass-method (SeqVarGDSCClass), 58
- GRanges, 42
- granges, SeqVarGDSCClass-method (SeqVarGDSCClass), 58
- GRangesList, 42
- header (SeqVarGDSCClass), 58
- header, SeqVarGDSCClass-method (SeqVarGDSCClass), 58
- info (SeqVarGDSCClass), 58
- info, SeqVarGDSCClass-method (SeqVarGDSCClass), 58
- IRanges, 42
- KG_P1_SampData, 5
- makeCluster, 36, 37, 39
- nextRNGStream, 37
- nextRNGSubStream, 37
- openfn.gds, 34
- parallel, 36, 39
- qual (SeqVarGDSCClass), 58
- qual, SeqVarGDSCClass-method (SeqVarGDSCClass), 58

- ref (SeqVarGDSCClass), 58
- ref, SeqVarGDSCClass-method (SeqVarGDSCClass), 58
- rowRanges (SeqVarGDSCClass), 58
- rowRanges, SeqVarGDSCClass-method (SeqVarGDSCClass), 58
- seqAddValue, 5
- seqAlleleCount, 46
- seqAlleleCount (seqAlleleFreq), 7
- seqAlleleFreq, 7, 32, 33, 46
- seqApply, 9, 16, 20, 27, 34, 35, 37, 39, 43, 51, 53
- SeqArray (SeqArray-package), 3
- SeqArray-package, 3
- seqAsVCF, 12
- seqBCF2GDS (seqVCF2GDS), 59
- seqBED2GDS, 13, 47
- seqBlockApply, 10, 14
- seqCheck, 17
- seqClose, 19, 34
- seqClose (seqClose-methods), 18
- seqClose, gds.class-method (seqClose-methods), 18
- seqClose, SeqVarGDSCClass-method (seqClose-methods), 18
- seqClose-methods, 18
- seqDelete, 18
- seqDigest, 19
- seqExampleFileName, 20
- seqExport, 21, 31
- seqGDS2BED (seqBED2GDS), 13
- seqGDS2SNP, 22, 47
- seqGDS2VCF, 23, 24, 47, 61
- seqGetData, 10, 16, 26, 34, 35, 37, 43, 51, 53, 58
- seqGetFilter, 28, 43
- seqGetParallel, 8, 10, 16, 32, 37
- seqGetParallel (seqParallelSetup), 38
- seqMerge, 30, 49, 61
- seqMissing, 8, 32, 33, 46
- seqNumAllele, 8, 32, 33
- seqOpen, 18, 19, 34, 58, 59
- seqOptimize, 35
- seqParallel, 7–10, 14–16, 32, 36, 39, 46, 54, 56, 61
- seqParallelSetup, 37, 38
- seqParApply (seqParallel), 36
- seqRecompress, 40, 49, 61
- seqResetFilter (seqSetFilter-methods), 42
- seqResetVariantID, 41
- seqSetFilter, 9, 10, 12, 15, 16, 20, 23, 24, 27, 29, 37, 46
- seqSetFilter (seqSetFilter-methods), 42
- seqSetFilter, SeqVarGDSCClass, ANY-method (seqSetFilter-methods), 42
- seqSetFilter, SeqVarGDSCClass, GRanges-method (seqSetFilter-methods), 42
- seqSetFilter, SeqVarGDSCClass, GRangesList-method (seqSetFilter-methods), 42
- seqSetFilter, SeqVarGDSCClass, IRanges-method (seqSetFilter-methods), 42
- seqSetFilter-methods, 42
- seqSetFilterAnnotID (seqSetFilter-methods), 42
- seqSetFilterChrom, 43, 46
- seqSetFilterChrom (seqSetFilter-methods), 42
- seqSetFilterCond, 43, 45
- seqSetFilterPos (seqSetFilter-methods), 42
- seqSNP2GDS, 14, 23, 46
- seqStorageOption, 30, 40, 48, 60, 61
- seqSummary, 49
- seqSystem, 52
- seqTranspose, 52
- seqUnitApply, 54, 56, 57
- seqUnitFilterCond, 55, 56, 56, 57
- seqUnitSlidingWindows, 55, 57
- SeqVarGDSCClass, 6, 7, 9, 12, 13, 15, 17–21, 23, 24, 26, 28, 32, 33, 36, 42, 45, 49, 53, 54, 56, 57, 58
- SeqVarGDSCClass-class (SeqVarGDSCClass), 58
- seqVCF2GDS, 6, 14, 22–24, 31, 40, 41, 47, 49, 58, 59, 63, 64
- seqVCF_Header, 60, 61, 62, 64
- seqVCF_SampID, 63, 64
- VCF-class, 12