

Package ‘fmrs’

March 30, 2021

Type Package

Title Variable Selection in Finite Mixture of AFT Regression and FMR

Version 1.0.0

Date 2020-09-25

Depends R (>= 4.0.0)

Imports methods, survival, stats

Description Provides parameter estimation as well as variable selection in Finite Mixture of Accelerated Failure Time Regression and Finite Mixture of Regression Models.

Furthermore, this package provides Ridge Regression and Elastic Net.

biocViews Survival, Regression, DimensionReduction

Suggests BiocGenerics, testthat, knitr, utils

License GPL (>= 3)

LazyData TRUE

VignetteBuilder knitr

BugReports <https://github.com/shokoohi/fmrs/issues>

RoxygenNote 7.1.0

Encoding UTF-8

git_url <https://git.bioconductor.org/packages/fmrs>

git_branch RELEASE_3_12

git_last_commit 3e2efc3

git_last_commit_date 2020-10-27

Date/Publication 2021-03-29

Author Farhad Shokoohi [aut, cre] (<<https://orcid.org/0000-0002-6224-2609>>)

Maintainer Farhad Shokoohi <shokoohi@icloud.com>

R topics documented:

fmrs-package	2
BIC	2
coefficients	3
dispersion	4

fitted	5
fmrs.gendata	6
fmrs.mle	8
fmrs.tunsel	10
fmrs.varsel	13
fmrsfit-class	16
fmrstunpar-class	17
logLik	17
mixProp	18
ncomp	19
ncov	20
nobs	21
residuals	22
summary	23
weights	24

Index**26**

fmrs-package*Variable Selection in Finite Mixture of AFT Regression and FMR*

Description

Provides parameter estimation and variable selection in FMRs models. The `fmrs.mle` method provides Maximum Likelihood Estimation for FMRs models. The `fmrs.tunsel` method provides component-wise tuning parameters. The `fmrs.varsel` method provides variable selection for FMRs models.

fmrs methods

`fmrs.mle`, `fmrs.tunsel`, `fmrs.varsel`, `fmrs.gendata`.

fmrs objects

`fmrsfit-class`, `fmrstunpar-class`

BIC*BIC method*

Description

Provides the estimated BIC of an FMRs model from an `fmrsfit-class`

Usage

```
BIC(object, ...)

## S4 method for signature 'fmrsfit'
BIC(object, ...)
```

Arguments

object	An fmrsfit-class
...	Other possible arguments

Value

A numeric value

Author(s)

Farhad Shokoohi <shokoohi@icloud.com>

Examples

```
set.seed(1980)
nComp = 2
nCov = 10
nObs = 500
dispersion = c(1, 1)
mixProp = c(0.4, 0.6)
rho = 0.5
coeff1 = c( 2,  2, -1, -2, 1, 2, 0, 0, 0, 0, 0)
coeff2 = c(-1, -1,  1,  2, 0, 0, 0, 0, -1, 2, -2)
umax = 40

dat <- fmrs.gendata(nObs = nObs, nComp = nComp, nCov = nCov,
                     coeff = c(coeff1, coeff2), dispersion = dispersion,
                     mixProp = mixProp, rho = rho, umax = umax,
                     disFamily = 'lnorm')

res.mle <- fmrs.mle(y = dat$y, x = dat$x, delta = dat$delta,
                      nComp = nComp, disFamily = 'lnorm',
                      initCoeff = rnorm(nComp*nCov+nComp),
                      initDispersion = rep(1, nComp),
                      initmixProp = rep(1/nComp, nComp))
BIC(res.mle)
```

Description

Provides the estimated regression coefficients from the fitted FMRs model from an [fmrsfit-class](#)

Usage

```
coefficients(object, ...)
## S4 method for signature 'fmrsfit'
coefficients(object, ...)
```

Arguments

object	An fmrsfit-class
...	Other possible arguments

Value

A numeric array of dimension-(nCov+1)-nComp

Author(s)

Farhad Shokoohi <shokoohi@icloud.com>

Examples

```
set.seed(1980)
nComp = 2
nCov = 10
nObs = 500
dispersion = c(1, 1)
mixProp = c(0.4, 0.6)
rho = 0.5
coeff1 = c( 2,  2, -1, -2, 1, 2, 0, 0, 0, 0, 0)
coeff2 = c(-1, -1,  1,  2, 0, 0, 0, 0, -1, 2, -2)
umax = 40

dat <- fmrs.gendata(nObs = nObs, nComp = nComp, nCov = nCov,
coeff = c(coeff1, coeff2), dispersion = dispersion,
mixProp = mixProp, rho = rho, umax = umax,
disFamily = 'lnorm')

res.mle <- fmrs.mle(y = dat$y, x = dat$x, delta = dat$delta,
nComp = nComp, disFamily = 'lnorm',
initCoeff = rnorm(nComp*nCov+nComp),
initDispersion = rep(1, nComp),
initmixProp = rep(1/nComp, nComp))
coefficients(res.mle)
```

dispersion

*dispersion method***Description**

Provides the estimated dispersions of the fitted FMRs model from an [fmrsfit-class](#)

Usage

```
dispersion(object, ...)

## S4 method for signature 'fmrsfit'
dispersion(object, ...)
```

Arguments

object	An fmrsfit-class
...	Other possible arguments

Value

A numeric array of dimension-(nCov+1)-nComp

Author(s)

Farhad Shokoohi <shokoohi@icloud.com>

Examples

```
set.seed(1980)
nComp = 2
nCov = 10
nObs = 500
dispersion = c(1, 1)
mixProp = c(0.4, 0.6)
rho = 0.5
coeff1 = c( 2,  2, -1, -2, 1, 2, 0, 0, 0, 0, 0)
coeff2 = c(-1, -1,  1,  2, 0, 0, 0, 0, -1, 2, -2)
umax = 40

dat <- fmrs.gendata(nObs = nObs, nComp = nComp, nCov = nCov,
                     coeff = c(coeff1, coeff2), dispersion = dispersion,
                     mixProp = mixProp, rho = rho, umax = umax,
                     disFamily = 'lnorm')

res.mle <- fmrs.mle(y = dat$y, x = dat$x, delta = dat$delta,
                      nComp = nComp, disFamily = 'lnorm',
                      initCoeff = rnorm(nComp*nCov+nComp),
                      initDispersion = rep(1, nComp),
                      initmixProp = rep(1/nComp, nComp))
dispersion(res.mle)
```

Description

Provides the fitted response of the fitted FMRs model from an [fmrsfit-class](#)

Usage

```
fitted(object, ...)

## S4 method for signature 'fmrsfit'
fitted(object, ...)
```

Arguments

object	An <i>fmrsfit-class</i>
...	Other possible arguments

Value

A numeric array of dimension-nObs-nComp

Author(s)

Farhad Shokoohi <shokoohi@icloud.com>

Examples

```
set.seed(1980)
nComp = 2
nCov = 10
nObs = 500
dispersion = c(1, 1)
mixProp = c(0.4, 0.6)
rho = 0.5
coeff1 = c( 2,  2, -1, -2, 1,  2, 0,  0,  0,  0,  0)
coeff2 = c(-1, -1,  1,  2, 0,  0, 0, -1,  2, -2)
umax = 40

dat <- fmrs.gendata(nObs = nObs, nComp = nComp, nCov = nCov,
coeff = c(coeff1, coeff2), dispersion = dispersion,
mixProp = mixProp, rho = rho, umax = umax,
disFamily = 'lnorm')

res.mle <- fmrs.mle(y = dat$y, x = dat$x, delta = dat$delta,
nComp = nComp, disFamily = 'lnorm',
initCoeff = rnorm(nComp*nCov+nComp),
initDispersion = rep(1, nComp),
initmixProp = rep(1/nComp, nComp))
head(fitted(res.mle))
```

fmrs.gendata

fmrs.gendata method

Description

Generates a data set from Finite Mixture of AFT regression models or Finite Mixture of Regression models under the specified setting.

Usage

```
fmrs.gendata(nObs, nComp, nCov, coeff, dispersion, mixProp, rho, umax, ...)
## S4 method for signature 'ANY'
fmrs.gendata(
  nObs,
  nComp,
```

```

nCov,
coeff,
dispersion,
mixProp,
rho,
umax,
disFamily = "lnorm"
)

```

Arguments

nObs	A numeric value represents sample size
nComp	A numeric value represents the order mixture in FMRs
nCov	A numeric value represents the number of covariates in design matrix
coeff	A vector of all regression coefficients including intercepts. It must be a vector of length nComp *(nCov+1).
dispersion	A vector of positive values for dispersion parameters of sub-distributions in FMRs models
mixProp	A vector of mixing proportions which their sum must be one
rho	A numeric value in [-1, 1] which represents the correlation between covariates of design matrix
umax	A numeric value represents the upper bound in Uniform distribution for censoring
...	Other possible options
disFamily	A sub-distribution family. The options are 'norm' for FMR models, 'lnorm' for mixture of AFT regression models with Log-Normal sub-distributions,'weibull' for mixture of AFT regression models with Weibull sub-distributions

Value

A list including response, covariates and censoring variables

Author(s)

Farhad Shokoohi <shokoohi@icloud.com>

See Also

Other lnorm, norm, weibull: [fmrs.mle\(\)](#), [fmrs.tunsel\(\)](#), [fmrs.varsel\(\)](#)

Examples

```

set.seed(1980)
nComp = 2
nCov = 10
nObs = 500
REP = 500
dispersion = c(1, 1)
mixProp = c(0.4, 0.6)
rho = 0.5
coeff1 = c( 2,  2, -1, -2,  1,  2,  0,  0,  0,  0,  0)
coeff2 = c(-1, -1,  2,  0,  0,  0, -1,  2, -2)

```

```
umax = 40

dat <- fmrs.gendata(nObs = nObs, nComp = nComp, nCov = nCov,
coeff = c(coeff1, coeff2), dispersion = dispersion,
mixProp = mixProp, rho = rho, umax = umax,
disFamily = 'lnorm')
```

fmrs.mle*fmrs.mle method***Description**

Provides MLE for Finite Mixture of Accelerated Failure Time Regression Models or Finite Mixture of Regression Models. It also provides Ridge Regression.

Usage

```
fmrs.mle(y, delta, x, nComp, ...)

## S4 method for signature 'ANY'
fmrs.mle(
  y,
  delta,
  x,
  nComp = 2,
  disFamily = "lnorm",
  initCoeff,
  initDispersion,
  initmixProp,
  lambRidge = 0,
  nIterEM = 400,
  nIterNR = 2,
  conveps = 1e-08,
  convepsEM = 1e-08,
  convepsNR = 1e-08,
  porNR = 2,
  activeset
)
```

Arguments

y	Responses (observations)
delta	Censoring indicator vector
x	Design matrix (covariates)
nComp	Order (Number of components) of mixture model
...	Other possible options
disFamily	A sub-distribution family. The options are 'norm' for FMR models, 'lnorm' for mixture of AFT regression models with Log-Normal sub-distributions, 'weibull' for mixture of AFT regression models with Weibull sub-distributions
initCoeff	Vector of initial values for regression coefficients including intercepts

initDispersion	Vector of initial values for standard deviations
initmixProp	Vector of initial values for proportion of components
lambRidge	A positive value for tuning parameter in Ridge Regression or Elastic Net
nIterEM	Maximum number of iterations for EM algorithm
nIterNR	Maximum number of iterations for Newton-Raphson algorithm
conveps	A positive value for avoiding NaN in computing divisions
convepsEM	A positive value for threshold of convergence in EM algorithm
convepsNR	A positive value for threshold of convergence in Newton-Raphson algorithm
porNR	A positive integer for maximum number of searches in NR algorithm
activeset	A matrix of zero-one that shows which intercepts and covariates are active in the fitted fmrs model

Details

Finite mixture of AFT regression models are represented as follows. Let X be the survival time with non-negative values, and $\mathbf{z} = (z_1, \dots, z_d)^\top$ be a d -dimensional vector of covariates that may have an effect on X . If the survival time is subject to right censoring, then the observed response time is $T = \min\{Y, C\}$, where $Y = \log X$, C is logarithm of the censoring time and $\delta = I_{\{y < c\}}$ is the censoring indicator. We say that $V = (T, \delta, \mathbf{z})$ follows a finite mixture of AFT regression models of order K if the conditional density of (T, δ) given \mathbf{z} has the form

$$f(t, \delta; \mathbf{z}, \boldsymbol{\Psi}) = \sum_{k=1}^K \pi_k [f_Y(t; \theta_k(\mathbf{z}), \sigma_k)]^\delta [S_Y(t; \theta_k(\mathbf{z}), \sigma_k)]^{1-\delta} [f_C(t)]^{1-\delta} [S_C(t)]^\delta$$

where $f_Y(\cdot)$ and $S_Y(\cdot)$ are respectively the density and survival functions of Y , $f_C(\cdot)$ and $S_C(\cdot)$ are respectively the density and survival functions of C ; and $\theta_k(\mathbf{z}) = h(\beta_{0k} + \mathbf{z}^\top \boldsymbol{\beta}_k)$ for a known link function $h(\cdot)$, $\boldsymbol{\Psi} = (\pi_1, \dots, \pi_K, \beta_{01}, \dots, \beta_{0K}, \boldsymbol{\beta}_1, \dots, \boldsymbol{\beta}_K, \sigma_1, \dots, \sigma_K)^\top$ with $\boldsymbol{\beta}_k = (\beta_{k1}, \beta_{k2}, \dots, \beta_{kd})^\top$ and $0 < \pi_k < 1$ with $\sum_{k=1}^K \pi_k = 1$. The log-likelihood of a sample of size n is formed as

$$\ell_n(\boldsymbol{\Psi}) = \sum_{i=1}^n \log \sum_{k=1}^K \pi_k [f_Y(t_i, \theta_k(\mathbf{z}_i), \sigma_k)]^{\delta_i} [S_Y(t_i, \theta_k(\mathbf{z}_i), \sigma_k)]^{1-\delta_i}.$$

Note that we assume the censoring distribution is non-informative and hence won't play any role in the estimation process. We use EM and Newton-Raphson algorithms in our method to find the maximizer of above Log-Likelihood.

Value

An [fmrsfit-class](#) that includes parameter estimates of the specified FMRs model

Author(s)

Farhad Shokoohi <shokoohi@icloud.com>

References

Shokoohi, F., Khalili, A., Asgharian, M. and Lin, S. (2016 submitted) Variable Selection in Mixture of Survival Models for Biomedical Genomic Studies

See Also

Other lnorm, norm, weibull: `fmrs.gendata()`, `fmrs.tunsel()`, `fmrs.varsel()`

Examples

```
set.seed(1980)
nComp = 2
nCov = 10
nObs = 500
dispersion = c(1, 1)
mixProp = c(0.4, 0.6)
rho = 0.5
coeff1 = c( 2,  2, -1, -2, 1, 2, 0, 0, 0, 0, 0)
coeff2 = c(-1, -1,  1,  2, 0, 0, 0, 0, -1, 2, -2)
umax = 40

dat <- fmrs.gendata(nObs = nObs, nComp = nComp, nCov = nCov,
                     coeff = c(coeff1, coeff2), dispersion = dispersion,
                     mixProp = mixProp, rho = rho, umax = umax,
                     disFamily = 'lnorm')

res.mle <- fmrs.mle(y = dat$y, x = dat$x, delta = dat$delta,
                      nComp = nComp, disFamily = 'lnorm',
                      initCoeff = rnorm(nComp*nCov+nComp),
                      initDispersion = rep(1, nComp),
                      initmixProp = rep(1/nComp, nComp))
summary(res.mle)
```

fmrs.tunsel*fmrs.tunsel method***Description**

Provides component-wise tuning parameters using BIC for Finite Mixture of Accelerated Failure Time Regression Models and Finite Mixture of Regression Models.

Usage

```
fmrs.tunsel(y, delta, x, nComp, ...)
## S4 method for signature 'ANY'
fmrs.tunsel(
  y,
  delta,
  x,
  nComp,
  disFamily = "lnorm",
  initCoeff,
  initDispersion,
  initmixProp,
  penFamily = "lasso",
  lambRidge = 0,
```

```

nIterEM = 2000,
nIterNR = 2,
conveps = 1e-08,
convepsEM = 1e-08,
convepsNR = 1e-08,
porNR = 2,
gamMixPor = 1,
activeset,
lambMCP,
lambSICA
)

```

Arguments

y	Responses (observations)
delta	Censoring indicator vector
x	Design matrix (covariates)
nComp	Order (Number of components) of mixture model
...	Other possible options
disFamily	A sub-distribution family. The options are 'norm' for FMR models, 'lnorm' for mixture of AFT regression models with Log-Normal sub-distributions, 'weibull' for mixture of AFT regression models with Weibull sub-distributions,
initCoeff	Vector of initial values for regression coefficients including intercepts
initDispersion	Vector of initial values for standard deviations
initmixProp	Vector of initial values for proportion of components
penFamily	Penalty name that is used in variable selection method. The available options are 'lasso', 'adplasso', 'mcp', 'scad', 'sica' and 'hard'.
lambRidge	A positive value for tuning parameter in Ridge Regression or Elastic Net
nIterEM	Maximum number of iterations for EM algorithm
nIterNR	Maximum number of iterations for Newton-Raphson algorithm
conveps	A positive value for avoiding NaN in computing divisions
convepsEM	A positive value for threshold of convergence in EM algorithm
convepsNR	A positive value for threshold of convergence in NR algorithm
porNR	A positive integer for maximum number of searches in NR algorithm
gamMixPor	Proportion of mixing parameters in the penalty. The value must be in the interval [0,1]. If <code>gamMixPor</code> = 0, the penalty structure is no longer mixture.
activeset	A matrix of zero-one that shows which intercepts and covariates are active in the fitted fmrs model
lambMCP	A positive numbers for mcp's extra tuning parameter
lambSICA	A positive numbers for sica's extra tuning parameter

Details

The maximizer of penalized Log-Likelihood depends on selecting a set of good tuning parameters which is a rather thorny issue. We choose a value in an equally spaced set of values in $(0, \lambda_{max})$ for a pre-specified λ_{max} that maximize the component-wise BIC,

$$\hat{\lambda}_k = \operatorname{argmax}_{\lambda_k} BIC_k(\lambda_k) = \operatorname{argmax}_{\lambda_k} \left\{ \ell_{k,n}^c(\hat{\Psi}_{\lambda_k,k}) - |d_{\lambda_k,k}| \log(n) \right\},$$

where $d_{\lambda_k, k} = \{j : \hat{\beta}_{\lambda_k, kj} \neq 0, j = 1, \dots, d\}$ is the active set excluding the intercept and $|d_{\lambda_k, k}|$ is its size. This approach is much faster than using an nComp by nComp grid to select the set λ to maximize the penalized Log-Likelihood.

Value

An [fmrstunpar-class](#) that includes component-wise tuning parameter estimates that can be used in variable selection procedure.

Author(s)

Farhad Shokoohi <shokoohi@icloud.com>

References

Shokoohi, F., Khalili, A., Asgharian, M. and Lin, S. (2016 submitted) Variable Selection in Mixture of Survival Models for Biomedical Genomic Studies

See Also

Other Inorm, norm, weibull: [fmrs.gendata\(\)](#), [fmrs.mle\(\)](#), [fmrs.varsel\(\)](#)

Examples

```

set.seed(1980)
nComp = 2
nCov = 10
nObs = 500
dispersion = c(1, 1)
mixProp = c(0.4, 0.6)
rho = 0.5
coeff1 = c( 2, 2, -1, -2, 1, 2, 0, 0, 0, 0, 0)
coeff2 = c(-1, -1, 1, 2, 0, 0, 0, 0, -1, 2, -2)
umax = 40

dat <- fmrs.gendata(nObs = nObs, nComp = nComp, nCov = nCov,
coeff = c(coeff1, coeff2), dispersion = dispersion,
mixProp = mixProp, rho = rho, umax = umax,
disFamily = 'lnorm')

res.mle <- fmrs.mle(y = dat$y, x = dat$x, delta = dat$delta,
nComp = nComp, disFamily = 'lnorm',
initCoeff = rnorm(nComp*nCov+nComp),
initDispersion = rep(1, nComp),
initmixProp = rep(1/nComp, nComp))

res.lam <- fmrs.tunsel(y = dat$y, x = dat$x, delta = dat$del
nComp = nComp, disFamily = 'lnorm',
initCoeff = c(coefficients(res.mle)),
initDispersion = dispersion(res.mle),
initmixProp = mixProp(res.mle),
penFamily = 'adlasso')
show(res.lam)

```

<code>fmrs.varsel</code>	<i>fmrs.varsel method</i>
--------------------------	---------------------------

Description

Provides variable selection and penalized MLE for Finite Mixture of Accelerated Failure Time Regression (FMAFTR) Models and Finite Mixture of Regression (FMR) Models. It also provide Ridge Regression and Elastic Net.

Usage

```
fmrs.varsel(y, delta, x, nComp, ...)

## S4 method for signature 'ANY'
fmrs.varsel(
  y,
  delta,
  x,
  nComp,
  disFamily = "lnorm",
  initCoeff,
  initDispersion,
  initmixProp,
  penFamily = "lasso",
  lambPen,
  lambRidge = 0,
  nIterEM = 2000,
  nIterNR = 2,
  conveps = 1e-08,
  convepsEM = 1e-08,
  convepsNR = 1e-08,
  porNR = 2,
  gamMixPor = 1,
  activeset,
  lambMCP,
  lambSICA
)
```

Arguments

<code>y</code>	Responses (observations)
<code>delta</code>	Censoring indicators
<code>x</code>	Design matrix (covariates)
<code>nComp</code>	Order (Number of components) of mixture model
<code>...</code>	Other possible options
<code>disFamily</code>	A sub-distribution family. The options are 'norm' for FMR models, 'lnorm' for mixture of AFT regression models with Log-Normal sub-distributions, 'weibull' for mixture of AFT regression models with Weibull sub-distributions
<code>initCoeff</code>	Vector of initial values for regression coefficients including intercepts

initDispersion	Vector of initial values for standard deviations
initmixProp	Vector of initial values for proportion of components
penFamily	Penalty name that is used in variable selection method The available options are 'lasso', 'adlasso', 'mcp', 'scad', 'sica' and 'hard'.
lambPen	A vector of positive numbers for tuning parameters
lambRidge	A positive value for tuning parameter in Ridge Regression or Elastic Net
nIterEM	Maximum number of iterations for EM algorithm
nIterNR	Maximum number of iterations for Newton-Raphson algorithm
conveps	A positive value for avoiding NaN in computing divisions
convepsEM	A positive value for threshold of convergence in EM algorithm
convepsNR	A positive value for threshold of convergence in NR algorithm
porNR	A positive interger for maximum number of searches in NR algorithm
gamMixPor	Proportion of mixing parameters in the penalty. The value must be in the interval [0,1]. If <code>gamMixPor</code> = 0, the penalty structure is no longer mixture.
activeset	A matrix of zero-one that shows which intercepts and covariates are active in the fitted fmrs model
lambMCP	A positive numbers for <code>mcp</code> 's extra tuning parameter
lambSICA	A positive numbers for <code>sica</code> 's extra tuning parameter

Details

The penalized likelihood of a finite mixture of AFT regression models is written as

$$\tilde{\ell}_n(\boldsymbol{\Psi}) = \ell_n(\boldsymbol{\Psi}) - \mathbf{p}_{\lambda_n}(\boldsymbol{\Psi})$$

where

$$\mathbf{p}_{\lambda_n}(\boldsymbol{\Psi}) = \sum_{k=1}^K \pi_k^\alpha \left\{ \sum_{j=1}^d p_{\lambda_{n,k}}(\beta_{kj}) \right\}.$$

In the M step of EM algorithm the function

$$\tilde{Q}(\boldsymbol{\Psi}, \boldsymbol{\Psi}^{(m)}) = \sum_{k=1}^K \tilde{Q}_k(\boldsymbol{\Psi}_k, \boldsymbol{\Psi}_k^{(m)}) = \sum_{k=1}^K \left[Q_k(\boldsymbol{\Psi}_k, \boldsymbol{\Psi}_k^{(m)}) - \pi_k^\alpha \left\{ \sum_{j=1}^d p_{\lambda_{n,k}}(\beta_{kj}) \right\} \right]$$

is maximized. Since the penalty function is singular at origin, we use a local quadratic approximation (LQA) for the penalty as follows,

$$\mathbf{p}_{k,\lambda_n}^*(\boldsymbol{\beta}, \boldsymbol{\beta}^{(m)}) = (\pi_k^{(m)})^\alpha \sum_{j=1}^d \left\{ p_{\lambda_{n,k}}(\beta_{kj}^{(m)}) + \frac{p'_{\lambda_{n,k}}(\beta_{kj}^{(m)})}{2\beta_{kj}^{(m)}} (\beta_{kj}^2 - \beta_{kj}^{(m)2}) \right\}.$$

Therefore maximizing Q is equivalent to maximizing the function

$$Q^*(\boldsymbol{\Psi}, \boldsymbol{\Psi}^{(m)}) = \sum_{k=1}^K Q_k^*(\boldsymbol{\Psi}_k, \boldsymbol{\Psi}_k^{(m)}) = \sum_{k=1}^K \left[Q_k(\boldsymbol{\Psi}_k, \boldsymbol{\Psi}_k^{(m)}) - \mathbf{p}_{k,\lambda_n}^*(\boldsymbol{\beta}, \boldsymbol{\beta}^{(m)}) \right].$$

In case of Log-Normal sub-distributions, the maximizers of Q_k functions are as follows. Given the data and current estimates of parameters, the maximizers are

$$\boldsymbol{\beta}_k^{(m+1)} = (\mathbf{z}' \boldsymbol{\tau}_k^{(m)} \mathbf{z} + \varpi_k(\boldsymbol{\beta}_k^{(m)}))^{-1} \mathbf{z}' \boldsymbol{\tau}_k^{(m)} T_k^{(m)},$$

where $\varpi_k(\beta_{kj}^{(m)}) = \text{diag}\left(\left(\pi_k^{(m+1)}\right)^\alpha \frac{p'_{\lambda_n,k}(\beta_{kj}^{(m)})}{\beta_{kj}^{(m)}}\right)$ and $\sigma_k^{(m+1)}$ is equal to

$$\sigma_k^{(m+1)} = \sqrt{\frac{\sum_{i=1}^n \tau_{ik}^{(m)} (t_{ik}^{(m)} - z_i \beta_k^{(m)})^2}{\sum_{i=1}^n \tau_{ik}^{(m)} [\delta_i + (1 - \delta_i) \{A(w_{ik}^{(m)})[A(w_{ik}^{(m)}) - w_{ik}^{(m)}]\}]}}.$$

For the Weibull distribution, on the other hand, we have $\tilde{\Psi}_k^{(m+1)} = \tilde{\Psi}_k^{(m)} - 0.5^\kappa [H_k^{p,(m)}]^{-1} I_k^{p,(m)}$, where $H_k^p = H_k + h(\Psi_k)$ is the penalized version of hessian matrix and $I_k^p = I_k + h(\Psi_k)\Psi_k$ is the penalized version of vector of first derivatives evaluated at $\tilde{\Psi}_k^{(m)}$.

Value

`fmrsfit-class`

Author(s)

Farhad Shokoohi <shokoohi@icloud.com>

References

Shokoohi, F., Khalili, A., Asgharian, M. and Lin, S. (2016 submitted) Variable Selection in Mixture of Survival Models for Biomedical Genomic Studies

See Also

Other lnorm, norm, weibull: `fmrs.gendata()`, `fmrs.mle()`, `fmrs.tunsel()`

Examples

```
set.seed(1980)
nComp = 2
nCov = 10
nObs = 500
dispersion = c(1, 1)
mixProp = c(0.4, 0.6)
rho = 0.5
coeff1 = c( 2,  2, -1, -2,  1,  2,  0,  0,  0,  0,  0)
coeff2 = c(-1, -1,  1,  2,  0,  0,  0,  0, -1,  2, -2)
umax = 40

dat <- fmrs.gendata(nObs = nObs, nComp = nComp, nCov = nCov,
                     coeff = c(coeff1, coeff2), dispersion = dispersion,
                     mixProp = mixProp, rho = rho, umax = umax,
                     disFamily = 'lnorm')

res.mle <- fmrs.mle(y = dat$y, x = dat$x, delta = dat$delta,
                      nComp = nComp, disFamily = 'lnorm',
                      initCoeff = rnorm(nComp*nCov+nComp),
                      initDispersion = rep(1, nComp),
                      initmixProp = rep(1/nComp, nComp))

res.lam <- fmrs.tunsel(y = dat$y, x = dat$x, delta = dat$delta,
                        nComp = ncomp(res.mle), disFamily = 'lnorm',
```

```

initCoeff=c(coefficients(res.mle)),
initDispersion = dispersion(res.mle),
initmixProp = mixProp(res.mle),
penFamily = 'adlasso')
res.var <- fmrs.varsel(y = dat$y, x = dat$x, delta = dat$delta,
nComp = ncomp(res.mle), disFamily = 'lnorm',
initCoeff=c(coefficients(res.mle)),
initDispersion = dispersion(res.mle),
initmixProp = mixProp(res.mle),
penFamily = 'adlasso',
lambPen = slot(res.lam, 'lambPen'))

coefficients(res.var)[-1,]
round(coefficients(res.var)[-1,],5)

```

fmrsfit-class*An S4 class to represent a fitted FMRs model***Description**

is an S4 class represents a fitted of FMRs model resulted from running [fmrs.mle](#) or [fmrs.varsel](#)

Slots

- `y` A length-nobs numeric vector
- `delta` A length-nobs numeric vector
- `x` A dimension-nobs-ncov numeric matrix
- `nobs` A length-one numeric vector
- `ncov` A length-one numeric vector
- `ncomp` A length-one numeric vector
- `coefficients` A length-(ncov+1)-ncomp numeric matrix
- `dispersion` A length-ncomp numeric vector
- `mixProp` A length-ncomp numeric vector
- `logLik` A length-one numeric vector
- `BIC` A length-one numeric vector
- `nIterEMconv` A length-one numeric vector
- `disFamily` A length-one character vector
- `penFamily` A length-one character vector
- `lambPen` A length-ncomp numeric vector
- `lambRidge` A length-one numeric vector
- `MCPGam` A length-one numeric vector
- `SICAGam` A length-one numeric vector
- `model` A length-one character vector
- `fitted` A dimension-nobs-ncomp numeric matrix
- `residuals` A dimension-nobs-ncomp numeric matrix
- `weights` A dimension-nobs-ncomp numeric matrix
- `activeset` A dimension-nobs-ncomp 0-1 matrix

fmrstunpar-class	<i>An S4 class to represent estimated optimal lambdas</i>
------------------	---

Description

An S4 class to represent estimated optimal lambdas resulted from running [fmrs.tunsel](#)

Slots

ncomp A length-one numeric vector
 lambPen A dimension-one-ncomp numeric array
 MCPGam A length-one numeric vector
 SICAGam A length-one numeric vector
 disFamily A length-one character vector
 penFamily A length-one character vector
 lambRidge A length-one numeric vector
 model A length-one character vector
 activeset A dimension-nobs-ncomp 0-1 matrix

logLik	<i>logLik method</i>
--------	----------------------

Description

Provides the estimated logLikelihood of an FMRs model from an [fmrsfit-class](#)

Usage

```
logLik(object, ...)

## S4 method for signature 'fmrsfit'
logLik(object, ...)
```

Arguments

object	An fmrsfit-class
...	Other possible arguments

Value

A numeric value

Author(s)

Farhad Shokoohi <shokoohi@icloud.com>

Examples

```

set.seed(1980)
nComp = 2
nCov = 10
nObs = 500
dispersion = c(1, 1)
mixProp = c(0.4, 0.6)
rho = 0.5
coeff1 = c( 2,  2, -1, -2, 1, 2, 0, 0, 0, 0, 0)
coeff2 = c(-1, -1,  1,  2, 0, 0, 0, 0, -1, 2, -2)
umax = 40

dat <- fmrs.gendata(nObs = nObs, nComp = nComp, nCov = nCov,
coeff = c(coeff1, coeff2), dispersion = dispersion,
mixProp = mixProp, rho = rho, umax = umax,
disFamily = 'lnorm')

res.mle <- fmrs.mle(y = dat$y, x = dat$x, delta = dat$delta,
nComp = nComp, disFamily = 'lnorm',
initCoeff = rnorm(nComp*nCov+nComp),
initDispersion = rep(1, nComp),
initmixProp = rep(1/nComp, nComp))
logLik(res.mle)

```

mixProp

mixProp method

Description

Provides the estimated mixing proportions of an FMRs model form an [fmrsfit-class](#)

Usage

```

mixProp(object, ...)

## S4 method for signature 'fmrsfit'
mixProp(object, ...)

```

Arguments

object	An fmrsfit-class
...	Other possible arguments

Value

A numeric vector of length-nComp

Author(s)

Farhad Shokoohi <shokoohi@icloud.com>

Examples

```

set.seed(1980)
nComp = 2
nCov = 10
nObs = 500
dispersion = c(1, 1)
mixProp = c(0.4, 0.6)
rho = 0.5
coeff1 = c( 2,  2, -1, -2, 1, 2, 0, 0, 0, 0, 0)
coeff2 = c(-1, -1,  1,  2, 0, 0, 0, 0, -1, 2, -2)
umax = 40

dat <- fmrs.gendata(nObs = nObs, nComp = nComp, nCov = nCov,
coeff = c(coeff1, coeff2), dispersion = dispersion,
mixProp = mixProp, rho = rho, umax = umax,
disFamily = 'lnorm')

res.mle <- fmrs.mle(y = dat$y, x = dat$x, delta = dat$delta,
nComp = nComp, disFamily = 'lnorm',
initCoeff = rnorm(nComp*nCov+nComp),
initDispersion = rep(1, nComp),
initmixProp = rep(1/nComp, nComp))
mixProp(res.mle)

```

ncomp

ncomp method

Description

Provides the order of an FMRs model from an [fmrsfit-class](#)

Usage

```

ncomp(object, ...)
## S4 method for signature 'fmrsfit'
ncomp(object, ...)

```

Arguments

object	An fmrsfit-class
...	Other possible arguments

Value

An integer value

Author(s)

Farhad Shokoohi <shokoohi@icloud.com>

Examples

```

set.seed(1980)
nComp = 2
nCov = 10
nObs = 500
dispersion = c(1, 1)
mixProp = c(0.4, 0.6)
rho = 0.5
coeff1 = c( 2,  2, -1, -2, 1, 2, 0, 0, 0, 0, 0)
coeff2 = c(-1, -1,  1,  2, 0, 0, 0, 0, -1, 2, -2)
umax = 40

dat <- fmrs.gendata(nObs = nObs, nComp = nComp, nCov = nCov,
coeff = c(coeff1, coeff2), dispersion = dispersion,
mixProp = mixProp, rho = rho, umax = umax,
disFamily = 'lnorm')

res.mle <- fmrs.mle(y = dat$y, x = dat$x, delta = dat$delta,
nComp = nComp, disFamily = 'lnorm',
initCoeff = rnorm(nComp*nCov+nComp),
initDispersion = rep(1, nComp),
initmixProp = rep(1/nComp, nComp))
ncomp(res.mle)

```

ncov

ncov method

Description

Provides the number of covariates of an FMRs model from an [fmrsfit-class](#)

Usage

```

ncov(object, ...)
## S4 method for signature 'fmrsfit'
ncov(object, ...)

```

Arguments

object	An fmrsfit-class
...	Other possible arguments

Value

An integer value

Author(s)

Farhad Shokoohi <shokoohi@icloud.com>

Examples

```

set.seed(1980)
nComp = 2
nCov = 10
nObs = 500
dispersion = c(1, 1)
mixProp = c(0.4, 0.6)
rho = 0.5
coeff1 = c( 2,  2, -1, -2, 1, 2, 0, 0, 0, 0, 0)
coeff2 = c(-1, -1,  1,  2, 0, 0, 0, 0, -1, 2, -2)
umax = 40

dat <- fmrs.gendata(nObs = nObs, nComp = nComp, nCov = nCov,
coeff = c(coeff1, coeff2), dispersion = dispersion,
mixProp = mixProp, rho = rho, umax = umax,
disFamily = 'lnorm')

res.mle <- fmrs.mle(y = dat$y, x = dat$x, delta = dat$delta,
nComp = nComp, disFamily = 'lnorm',
initCoeff = rnorm(nComp*nCov+nComp),
initDispersion = rep(1, nComp),
initmixProp = rep(1/nComp, nComp))
ncov(res.mle)

```

nobs

nobs method

Description

Provides the number of observations in an FMRs model from an [fmrsfit-class](#)

Usage

```

nobs(object, ...)
## S4 method for signature 'fmrsfit'
nobs(object, ...)

```

Arguments

object	An fmrsfit-class
...	Other possible arguments

Value

An integer value

Author(s)

Farhad Shokoohi <shokoohi@icloud.com>

Examples

```

set.seed(1980)
nComp = 2
nCov = 10
nObs = 500
dispersion = c(1, 1)
mixProp = c(0.4, 0.6)
rho = 0.5
coeff1 = c( 2,  2, -1, -2, 1, 2, 0, 0, 0, 0, 0)
coeff2 = c(-1, -1,  1,  2, 0, 0, 0, 0, -1, 2, -2)
umax = 40

dat <- fmrs.gendata(nObs = nObs, nComp = nComp, nCov = nCov,
coeff = c(coeff1, coeff2), dispersion = dispersion,
mixProp = mixProp, rho = rho, umax = umax,
disFamily = 'lnorm')

res.mle <- fmrs.mle(y = dat$y, x = dat$x, delta = dat$delta,
nComp = nComp, disFamily = 'lnorm',
initCoeff = rnorm(nComp*nCov+nComp),
initDispersion = rep(1, nComp),
initmixProp = rep(1/nComp, nComp))
nobs(res.mle)

```

residuals

residuals method

Description

Provides the residuals of the fitted FMRs model from an [fmrsfit-class](#)

Usage

```

residuals(object, ...)

## S4 method for signature 'fmrsfit'
residuals(object, ...)

```

Arguments

object	An fmrsfit-class
...	Other possible arguments

Value

A numeric array of dimension-nObs-nComp

Author(s)

Farhad Shokoohi <shokoohi@icloud.com>

Examples

```

set.seed(1980)
nComp = 2
nCov = 10
nObs = 500
dispersion = c(1, 1)
mixProp = c(0.4, 0.6)
rho = 0.5
coeff1 = c( 2,  2, -1, -2, 1, 2, 0, 0, 0, 0, 0)
coeff2 = c(-1, -1,  1,  2, 0, 0, 0, 0, -1, 2, -2)
umax = 40

dat <- fmrs.gendata(nObs = nObs, nComp = nComp, nCov = nCov,
coeff = c(coeff1, coeff2), dispersion = dispersion,
mixProp = mixProp, rho = rho, umax = umax,
disFamily = 'lnorm')

res.mle <- fmrs.mle(y = dat$y, x = dat$x, delta = dat$delta,
nComp = nComp, disFamily = 'lnorm',
initCoeff = rnorm(nComp*nCov+nComp),
initDispersion = rep(1, nComp),
initmixProp = rep(1/nComp, nComp))
head(residuals(res.mle))

```

summary

summary method

Description

Displays the fitted FMRs model by showing the estimated coefficients, dispersions and mixing proportions

Display the selected component-wise tuning parameters

Usage

```

summary(object, ...)

summary(object, ...)

## S4 method for signature 'fmrsfit'
summary(object, ...)

## S4 method for signature 'fmrstunpar'
summary(object, ...)

```

Arguments

object	An fmrsfit-class or fmrstunpar-class
...	Other possible arguments

Value

Summary of the fitted FMRs model
 Summary of the selected component-wise tuning parameters

Author(s)

Farhad Shokoohi <shokoohi@icloud.com>
 Farhad Shokoohi <shokoohi@icloud.com>

Examples

```
set.seed(1980)
nComp = 2
nCov = 10
nObs = 500
dispersion = c(1, 1)
mixProp = c(0.4, 0.6)
rho = 0.5
coeff1 = c( 2,  2, -1, -2, 1, 2, 0, 0, 0, 0, 0)
coeff2 = c(-1, -1,  1,  2, 0, 0, 0, 0, -1, 2, -2)
umax = 40

dat <- fmrs.gendata(nObs = nObs, nComp = nComp, nCov = nCov,
                     coeff = c(coeff1, coeff2), dispersion = dispersion,
                     mixProp = mixProp, rho = rho, umax = umax,
                     disFamily = 'lnorm')

res.mle <- fmrs.mle(y = dat$y, x = dat$x, delta = dat$delta,
                      nComp = nComp, disFamily = 'lnorm',
                      initCoeff = rnorm(nComp*nCov+nComp),
                      initDispersion = rep(1, nComp),
                      initmixProp = rep(1/nComp, nComp))
summary(res.mle)

res.lam <- fmrs.tunsel(y = dat$y, x = dat$x, delta = dat$delta,
                        nComp = nComp, disFamily = 'lnorm',
                        initCoeff = c(coefficients(res.mle)),
                        initDispersion = dispersion(res.mle),
                        initmixProp = mixProp(res.mle),
                        penFamily = 'adlasso')
summary(res.lam)
```

weights

*weights method***Description**

Provides the weights of fitted observations for each observation under all components of an FMRs model

Usage

```
weights(object, ...)

## S4 method for signature 'fmrsfit'
weights(object, ...)
```

Arguments

object	An fmrsfit-class
...	Other possible arguments

Value

A numeric array of dimension-nObs-nComp

Author(s)

Farhad Shokoohi <shokoohi@icloud.com>

Examples

```
set.seed(1980)
nComp = 2
nCov = 10
nObs = 500
dispersion = c(1, 1)
mixProp = c(0.4, 0.6)
rho = 0.5
coeff1 = c( 2,  2, -1, -2, 1, 2, 0, 0, 0, 0, 0)
coeff2 = c(-1, -1,  1,  2, 0, 0, 0, 0, -1, 2, -2)
umax = 40

dat <- fmrs.gendata(nObs = nObs, nComp = nComp, nCov = nCov,
coeff = c(coeff1, coeff2), dispersion = dispersion,
mixProp = mixProp, rho = rho, umax = umax,
disFamily = 'lnorm')

res.mle <- fmrs.mle(y = dat$y, x = dat$x, delta = dat$delta,
nComp = nComp, disFamily = 'lnorm',
initCoeff = rnorm(nComp*nCov+nComp),
initDispersion = rep(1, nComp),
initmixProp = rep(1/nComp, nComp))
head(weights(res.mle))
```

Index

- * **AFT**
 - fmrs.gendata, 6
 - fmrs.mle, 8
 - fmrs.tunsel, 10
 - fmrs.varsel, 13
- * **Adaptive**
 - fmrs.tunsel, 10
 - fmrs.varsel, 13
- * **Algorithm**
 - fmrs.varsel, 13
- * **Censored**
 - fmrs.gendata, 6
 - fmrs.mle, 8
 - fmrs.tunsel, 10
 - fmrs.varsel, 13
- * **Data**
 - fmrs.gendata, 6
- * **EM**
 - fmrs.mle, 8
 - fmrs.varsel, 13
- * **ElasticNet**
 - fmrs.varsel, 13
- * **FMRs**
 - fmrs.gendata, 6
 - fmrs.mle, 8
 - fmrs.tunsel, 10
- * **FMR**
 - fmrs.varsel, 13
- * **Generation**
 - fmrs.gendata, 6
- * **LASSO**
 - fmrs.tunsel, 10
 - fmrs.varsel, 13
- * **MCP**
 - fmrs.tunsel, 10
 - fmrs.varsel, 13
- * **NR**
 - fmrs.mle, 8
- * **Regression**
 - fmrs.tunsel, 10
 - fmrs.varsel, 13
- * **Ridge**
 - fmrs.mle, 8
- fmrs.tunsel, 10
- fmrs.varsel, 13
- * **SCAD**
 - fmrs.tunsel, 10
 - fmrs.varsel, 13
- * **SICA**
 - fmrs.tunsel, 10
 - fmrs.varsel, 13
- * **Selection**
 - fmrs.varsel, 13
- * **Tuning**
 - fmrs.tunsel, 10
- * **fmr, aft, censoring, data generation**
 - fmrs.gendata, 6
- * **fmr, aft, lasso, adlasso, mcp, scad, sica, ridge, elastic net**
 - fmrs.varsel, 13
- * **fmr, aft, lasso, adlasso, mcp, scad, sica, ridge**
 - fmrs.tunsel, 10
- * **fmr, aft, mle, ridge, fmrs**
 - fmrs.mle, 8
- * **Inorm, norm, weibull**
 - fmrs.gendata, 6
 - fmrs.mle, 8
 - fmrs.tunsel, 10
 - fmrs.varsel, 13
- * **object**
 - fmrsfit-class, 16
 - fmrstunpar-class, 17
- BIC, 2
- BIC,BIC-method (BIC), 2
- BIC,fmrsfit-method (BIC), 2
- coefficients, 3
- coefficients,coefficients-method (coefficients), 3
- coefficients,fmrsfit-method (coefficients), 3
- dispersion, 4
- dispersion,dispersion-method (dispersion), 4

dispersion, fmrsfit-method (dispersion),
 4
fitted, 5
fitted, fitted-method (fitted), 5
fitted, fmrsfit-method (fitted), 5
fmrs (fmrs-package), 2
fmrs-package, 2
fmrs.gendata, 2, 6, 10, 12, 15
fmrs.gendata, ANY-method (fmrs.gendata),
 6
fmrs.gendata-method (fmrs.gendata), 6
fmrs.mle, 2, 7, 8, 12, 15, 16
fmrs.mle, ANY-method (fmrs.mle), 8
fmrs.mle-method (fmrs.mle), 8
fmrs.tunsel, 2, 7, 10, 10, 15, 17
fmrs.tunsel, ANY-method (fmrs.tunsel), 10
fmrs.tunsel-method (fmrs.tunsel), 10
fmrs.varsel, 2, 7, 10, 12, 13, 16
fmrs.varsel, ANY-method (fmrs.varsel), 13
fmrs.varsel-method (fmrs.varsel), 13
fmrsfit-class, 16
fmrstunpar (fmrstunpar-class), 17
fmrstunpar-class, 17
frmsfit (fmrsfit-class), 16

logLik, 17
logLik, fmrsfit-method (logLik), 17
logLik, logLik-method (logLik), 17

mixProp, 18
mixProp, fmrsfit-method (mixProp), 18
mixProp, mixProp-method (mixProp), 18

ncomp, 19
ncomp, fmrsfit-method (ncomp), 19
ncomp, ncomp-method (ncomp), 19
ncov, 20
ncov, fmrsfit-method (ncov), 20
ncov, ncov-method (ncov), 20
nobs, 21
nobs, fmrsfit-method (nobs), 21
nobs, nobs-method (nobs), 21

residuals, 22
residuals, fmrsfit-method (residuals), 22
residuals, residuals-method (residuals),
 22

summary, 23
summary, fmrsfit-method (summary), 23
summary, fmrstunpar-method (summary), 23
summary, summary-method (summary), 23