

Package ‘encoDnaseI’

October 8, 2016

Title data provided by UCSC for Cd4 raw measures of DnaseI hypersensitivity

Description data provided by UCSC for Cd4 raw measures of DnaseI hypersensitivity

Version 0.10.0

Author VJ Carey <stvjc@channing.harvard.edu>

Depends R (>= 2.15.0), methods, Biobase (>= 2.5.5), lattice, GGtools, GGBase

Suggests GGdata

Maintainer VJ Carey <stvjc@channing.harvard.edu>

License Artistic-2.0

biocViews ExperimentData, Genome, Homo_sapiens_Data, SNPData, ENCODE

NeedsCompilation no

R topics documented:

| | |
|---------------------------|---|
| hg18track-class | 1 |
| juxtaPlot | 3 |
| rawCd4DnaseI | 4 |

| | |
|--------------|----------|
| Index | 5 |
|--------------|----------|

| | |
|-----------------|--|
| hg18track-class | <i>Class "hg18track" container for hg18 annotation found in genome browser track files; class "chrnum" extends numeric for an indexing application on hg18track objects.</i> |
|-----------------|--|

Description

container for hg18 annotation found in genome browser track files

Objects from the Class

Objects can be created by calls of the form `new("hg18track", assayData, featureData, experimentData, annotation)`. These are single-sample eSet instances.

Note that `demoTrk19` is a restriction of the `rawCD4` structure to the interval of chromosome 19 that was assayed in the ENCODE project for DnaseI hypersensitivity.

Slots

`assayData`: Object of class "AssayData" ~~
`phenoData`: Object of class "AnnotatedDataFrame" ~~
`featureData`: Object of class "AnnotatedDataFrame" ~~
`experimentData`: Object of class "MIAME" ~~
`annotation`: Object of class "character" ~~
`._.classVersion_.`: Object of class "Versions" ~~

Extends

Class "eSet", directly. Class "VersionedBiobase", by class "eSet", distance 2. Class "Versioned", by class "eSet", distance 3.

Methods

[signature(x = "hg18track"): select using numeric, logical, or chrnum indices.

chrnum signature(object = "hg18track"): extract numeric tokens for chromosome number at which data values are obtained; note that chrnum is also used as name of a class.

dataVals signature(object = "hg18track"): actual data values

getTrkXY signature(object = "hg18track", type = "character"): obtain a list with components x, y indicating location and data value respectively; location is within chromosome; default type is 'midpoint' of locations given as intervals

getTrkXY signature(object = "hg18track", type = "missing"): take default midpoint x values corresponding to data values

rangeLocs signature(object = "hg18track"): if measures from only one chromosome are present, this returns low and high values of chromStart and chromEnd respectively, otherwise error.

clipTrk signature(obj = "hg18track", low="numeric", hi="numeric", attr="ANY"): create a restriction of the track using an interval specification. by default the chromStart featureData component is used for coordinates to clip; if attr is non-missing, the featureData component named by attr will be used.

initialize signature(.Object = "hg18track"): create a new instance

Author(s)

VJ Carey <stvjc@channing.harvard.edu>

Examples

```
showClass("hg18track")
data(rawCD4)
rawCD4
rawCD4.chr1 = rawCD4[ chrnum(1), ]
rangeLocs(rawCD4.chr1)
plot(getTrkXY(rawCD4.chr1), ylab="data value", xlab="interval midpt on chr 1" )
c52 = clipTrk(rawCD4[ chrnum(5), ], 1.30e8, 1.33e8 )
plot(getTrkXY(c52))
```

juxtaPlot

two-panel plot with track info and snp screen t-values

Description

two-panel plot with track info and snp screen t-values

Usage

```
juxtaPlot(trk, ssr, locstr)
```

Arguments

| | |
|--------|--|
| trk | instance of hg18track |
| ssr | instance of GGtools snpScreenResult |
| locstr | matrix with 2 rows: rsid (numeric component of dbSNP id) and loc |

Details

xyplot of lattice package is used.

Value

xyplot output; use print in Sweave.

Author(s)

VJ Carey <stvjc@channing.harvard.edu>

Examples

```
## Not run:
# see vignette
data(sOSR2)
data(c19g) # track excerpt
juxtaPlot(c19g, sOSR2)

## End(Not run)
```

| | |
|--------------|---|
| rawCd4DnaseI | <i>A data frame with information on the UCSC browser track related to DNaseI hypersensitivity</i> |
|--------------|---|

Description

A data frame with information on the UCSC browser track related to DNaseI hypersensitivity; the rawCD4 object is an eSet extension representing the same information; rawHelaDnaseI is like rawCD4 but results on HeLa cells.

Usage

```
data(rawCd4DnaseI)
data(rawHelaDnaseI)
data(rawCD4)
```

Details

Obtained from a MySQL representation of the data distributed at the Genome Browser FTP site

Value

a data.frame

Author(s)

Vince Carey <stvjc@channing.harvard.edu>

References

hgdownload.cse.ucsc.edu ... it appears that they do not offer the MYD/MYI representations, just the txt.gz and sql files now. So if you obtain the encodeNhgriDnaseHsChipRawCd4.txt and .sql files at goldenPath/currentGenomes/Homo_Sapiens/encode/database, you can reconstruct the underlying data for this data.frame (hg18, Nov 2007).

Examples

```
data(rawCd4DnaseI)
dim(rawCd4DnaseI)
rawCd4DnaseI[1:5,]
library(lattice)
xyplot(dataValue~chromStart|chrom, data=rawCd4DnaseI, subset=chrom %in%
  c("chr1", "chr10", "chr19", "chr20"), scales=list(x=list(relation="free")))
```

Index

*Topic **classes**

hg18track-class, 1

*Topic **models**

juxtaPlot, 3

rawCd4DnaseI, 4

[, hg18track, ANY, ANY, ANY-method
(hg18track-class), 1

[, hg18track-method (hg18track-class), 1

c19g (juxtaPlot), 3

chrnum (hg18track-class), 1

chrnum, hg18track-method
(hg18track-class), 1

chrnum, numeric-method
(hg18track-class), 1

chrnum-class (hg18track-class), 1

chromStarts (hg18track-class), 1

chromStarts, hg18track-method
(hg18track-class), 1

clipTrk (hg18track-class), 1

clipTrk, hg18track, numeric, numeric, ANY-method
(hg18track-class), 1

clipTrk, hg18track, numeric, numeric-method
(hg18track-class), 1

dataVals (hg18track-class), 1

dataVals, hg18track-method
(hg18track-class), 1

demoPGM1ssr (juxtaPlot), 3

demoTrk19 (hg18track-class), 1

eSet, 2

getTrkXY (hg18track-class), 1

getTrkXY, hg18track, character-method
(hg18track-class), 1

getTrkXY, hg18track, missing-method
(hg18track-class), 1

hg18track, 3

hg18track-class, 1

initialize, hg18track-method
(hg18track-class), 1

juxtaPlot, 3

makeHg18track (hg18track-class), 1

rangeLocs (hg18track-class), 1

rangeLocs, hg18track-method
(hg18track-class), 1

rawCD4 (rawCd4DnaseI), 4

rawCd4DnaseI, 4

rawHelaDnaseI (rawCd4DnaseI), 4

sOSR2 (juxtaPlot), 3

Versioned, 2

VersionedBiobase, 2