

# Package ‘SpikeInSubset’

October 17, 2019

**Title** Part of Affymetrix's Spike-In Experiment Data

**Version** 1.24.0

**Author** Rafael Irizarry <rafa@jhu.edu> and Zhijin Wu

**Description**

Includes probe-level and expression data for the HGU133 and HGU95 spike-in experiments

**Maintainer** Rafael A. Irizarry <rafa@jhu.edu>

**License** LGPL

**Depends** R (>= 2.4.0), Biobase (>= 2.5.5), affy (>= 1.23.4)

**biocViews** ExperimentData, MicroarrayData

**git\_url** <https://git.bioconductor.org/packages/SpikeInSubset>

**git\_branch** RELEASE\_3\_9

**git\_last\_commit** 957e773

**git\_last\_commit\_date** 2019-05-02

**Date/Publication** 2019-10-17

## R topics documented:

hgu133a.spikein.xhyb . . . . .	1
SpikeIn . . . . .	2
<b>Index</b>	<b>3</b>

---

hgu133a.spikein.xhyb *Cross hybridizers*

---

### Description

Probe Sets likely to crosshybridize to spiked-in probesets in the Affymetrix HGU133A spike in

This object is list. Each component of the list contains probeset names of possible crosshybridizers. The sequences of each spiked-in clone were collected and blasted against all HG-U133A target sequences. Target sequences are the ~600bp regions from which probes were selected. Thresholds of 100, 150 and 200bp were used and define the three components of the list.

### Usage

```
data(hgu133a.spikein.xhyb)
```

**Format**

A list

**Source**

Simon Cawley <simon\_cawley@affymetrix.com>

---

SpikeIn

*Subset of Affymetrix SpikeIn Experiment Data*

---

**Description**

Probe-level and pre-processed data for six arrays (two triplicates) from the HGU95 and HGU133 SpikeIn experiments.

**Usage**

```
data(spikein95)
data(rma95)
data(mas95)
```

```
data(spikein133)
data(rma133)
data(mas133)
```

**Format**

SpikeIn is [ProbeSet](#) containing the \$PM\$ and \$MM\$ intensities for a gene spiked in at different concentrations. Use pData to see the concentrations.

**Source**

spikein95 and spikein133 are instances of [ProbeSet](#) with the probe-level data for six arrays (two triplicates) from the HGU95 and HGU133 SpikeIn experiments respectively. rma95 and rma133 contain the data pre-processed with RMA. mas95 and mas133 contain the data pre-processed with mas5 (expression and present/absent calls). The calls are in objects called paca11s95 and paca11s133.

For more information see Irizarry, R.A., et al. NAR (2003) <http://www.biostat.jhsph.edu/~ririzarr/papers/index.html>

# Index

## \*Topic **datasets**

hgu133a.spikein.xhyb, [1](#)  
SpikeIn, [2](#)

hgu133a.spikein.xhyb, [1](#)

mas133 (SpikeIn), [2](#)  
mas95 (SpikeIn), [2](#)

pacalls133 (SpikeIn), [2](#)  
pacalls95 (SpikeIn), [2](#)  
ProbeSet, [2](#)

rma133 (SpikeIn), [2](#)  
rma95 (SpikeIn), [2](#)

SpikeIn, [2](#)  
spikein133 (SpikeIn), [2](#)  
spikein95 (SpikeIn), [2](#)