

Package ‘MatrixQCvis’

May 20, 2024

Type Package

Title Shiny-based interactive data-quality exploration for omics data

Version 1.12.0

Date 2024-04-25

VignetteBuilder knitr

Description Data quality assessment is an integral part of preparatory data analysis to ensure sound biological information retrieval.

We present here the MatrixQCvis package, which provides shiny-based interactive visualization of data quality metrics at the per-sample and per-feature level. It is broadly applicable to quantitative omics data types that come in matrix-like format (features x samples). It enables the detection of low-quality samples, drifts, outliers and batch effects in data sets. Visualizations include amongst others bar- and violin plots of the (count/intensity) values, mean vs standard deviation plots, MA plots, empirical cumulative distribution function (ECDF) plots, visualizations of the distances between samples, and multiple types of dimension reduction plots. Furthermore, MatrixQCvis allows for differential expression analysis based on the limma (moderated t-tests) and proDA (Wald tests) packages. MatrixQCvis builds upon the popular Bioconductor SummarizedExperiment S4 class and enables thus the facile integration into existing workflows. The package is especially tailored towards metabolomics and proteomics mass spectrometry data, but also allows to assess the data quality of other data types that can be represented in a SummarizedExperiment object.

Depends SummarizedExperiment (>= 1.20.0), plotly (>= 4.9.3), shiny (>= 1.6.0)

Imports ComplexHeatmap (>= 2.7.9), dplyr (>= 1.0.5), ExperimentHub (>= 2.6.0), ggplot2 (>= 3.3.3), grDevices (>= 4.1.0), Hmisc (>= 4.5-0), htmlwidgets (>= 1.5.3), impute (>= 1.65.0), imputeLCMD (>= 2.0), limma (>= 3.47.12), MASS (>= 7.3-58.1), methods (>= 4.1.0), pcaMethods (>= 1.83.0), proDA (>= 1.5.0), rlang (>= 0.4.10), rmarkdown (>= 2.7), Rtsne (>= 0.15), shinydashboard (>= 0.7.1), shinyhelper (>= 0.3.2), shinyjs (>= 2.0.0), stats (>= 4.1.0), tibble (>= 3.1.1), tidyr (>= 1.1.3), umap (>= 0.2.7.0), UpSetR (>= 1.4.0), vsn (>= 3.59.1)

Suggests BiocGenerics (>= 0.37.4), BiocStyle (>= 2.19.2), hexbin (>= 1.28.2), htrr (>= 1.4.7), jpeg (>= 0.1-10), knitr (>= 1.33), statmod (>= 1.5.0), testthat (>= 3.0.2)

biocViews Visualization, ShinyApps, GUI, QualityControl, DimensionReduction, Metabolomics, Proteomics, Transcriptomics

License GPL-3

Encoding UTF-8

RoxygenNote 7.3.1

git_url <https://git.bioconductor.org/packages/MatrixQCvis>

git_branch RELEASE_3_19

git_last_commit 4bf7768

git_last_commit_date 2024-04-30

Repository Bioconductor 3.19

Date/Publication 2024-05-19

Author Thomas Naake [aut, cre] (<<https://orcid.org/0000-0001-7917-5580>>),
Wolfgang Huber [aut] (<<https://orcid.org/0000-0002-0474-2218>>)

Maintainer Thomas Naake <thomasnaake@gmail.com>

Contents

barplotSamplesMeasuredMissing	3
batchCorrectionAssay	4
createBoxplot	5
createDfFeature	6
cv	7
cvFeaturePlot	8
dimensionReduction	9
dimensionReductionPlot	10
distSample	11
distShiny	12
driftPlot	13
ECDF	14
explVar	15
extractComb	16
featurePlot	17
histFeature	18
histFeatureCategory	19
hist_sample	20
hist_sample_num	20
hoeffDPlot	21
hoeffDValues	22
imputeAssay	23
MPlot	25
MValues	26

measuredCategory	27
mosaic	28
normalizeAssay	29
permuteExpIVar	30
plotCV	31
plotPCALoadings	32
plotPCAVar	33
plotPCAVarPvalue	34
samplesMeasuredMissing	35
shinyQC	36
sumDistSample	37
tblPCALoadings	38
transformAssay	39
upsetCategory	40
volcanoPlot	41

Index **43**

barplotSamplesMeasuredMissing
Barplot of number of measured/missing features of samples

Description

barplotSamplesMeasuredMissing plots the number of measured/missing features of samples as a barplot. The function will take as input the returned tbl of samplesMeasuredMissing.

Usage

```
barplotSamplesMeasuredMissing(tbl, measured = TRUE)
```

Arguments

- tbl tbl object
- measured logical, should the number of measured or missing values be plotted

Value

gg object from ggplot2

Examples

```
## create se
a <- matrix(seq_len(100), nrow = 10, ncol = 10,
            dimnames = list(seq_len(10), paste("sample", seq_len(10))))
a[c(1, 5, 8), seq_len(5)] <- NA
set.seed(1)
a <- a + rnorm(100)
cD <- data.frame(name = colnames(a), type = c(rep("1", 5), rep("2", 5)))
```

```

rD <- data.frame(spectra = rownames(a))
se <- SummarizedExperiment::SummarizedExperiment(assay = a,
  rowData = rD, colData = cD)

## create the data.frame with information on number of measured/missing
## values
tbl <- samplesMeasuredMissing(se)

## plot number of measured values
barplotSamplesMeasuredMissing(tbl, measured = TRUE)

## plot number of missing values
barplotSamplesMeasuredMissing(tbl, measured = FALSE)

```

batchCorrectionAssay Remove batch effects from (count/intensity) values of a SummarizedExperiment

Description

The function `batchCorrectionAssay` removes the batch effect of (count/intensity) values of a `SummarizedExperiment`. It uses either the `removeBatchEffect` function or no batch effect correction method (pass-through, none).

Usage

```

batchCorrectionAssay(
  se,
  method = c("none", "removeBatchEffect (limma)"),
  batchColumn = colnames(se@colData)
)

```

Arguments

<code>se</code>	<code>SummarizedExperiment</code>
<code>method</code>	character, one of "none" or "removeBatchEffect"
<code>batchColumn</code>	character, one of <code>colnames(colData(se))</code>

Details

The column `batchColumn` in `colData(se)` contains the information on the batch identity. Internal use in `shinyQC`.

If `batchColumn` is `NULL`, `batchColumn` is internally set to the name of the first column in `colData(se)` if `method = "removeBatchEffect (limma)"`.

Value

matrix

Examples

```
## create se
a <- matrix(seq_len(100), nrow = 10, ncol = 10,
            dimnames = list(seq_len(10), paste("sample", seq_len(10))))
a[c(1, 5, 8), seq_len(5)] <- NA
set.seed(1)
a <- a + rnorm(100)
cD <- data.frame(name = colnames(a),
                type = c(rep("1", 5), rep("2", 5)), batch = rep(c(1, 2), 5))
rD <- data.frame(spectra = rownames(a))
se <- SummarizedExperiment::SummarizedExperiment(assay = a,
                                                rowData = rD, colData = cD)

batchCorrectionAssay(se, method = "removeBatchEffect (limma)",
                    batchColumn = "batch")
```

createBoxplot

Create a boxplot of (count/intensity) values per sample

Description

The function `create_boxplot` creates a boxplot per sample for the intensity/count values.

Usage

```
createBoxplot(
  se,
  orderCategory = colnames(colData(se)),
  title = "",
  log = TRUE,
  violin = FALSE
)
```

Arguments

<code>se</code>	SummarizedExperiment containing the (count/intensity) values in the assay slot
<code>orderCategory</code>	character, one of <code>colnames(colData(se))</code>
<code>title</code>	character or numeric of length(1)
<code>log</code>	logical, if TRUE (count/intensity) values are displayed as log values
<code>violin</code>	logical, if FALSE a boxplot is created, if TRUE a violin plot is created

Details

Internal usage in `shinyQC`.

Value

gg object from ggplot2

Examples

```
## create se
a <- matrix(seq_len(100), nrow = 10, ncol = 10,
            dimnames = list(seq_len(10), paste("sample", seq_len(10))))
a[c(1, 5, 8), seq_len(5)] <- NA
set.seed(1)
a <- a + rnorm(100)
cD <- data.frame(name = colnames(a), type = c(rep("1", 5), rep("2", 5)))
rD <- data.frame(spectra = rownames(a))
se <- SummarizedExperiment::SummarizedExperiment(assay = a,
                                                rowData = rD, colData = cD)

createBoxplot(se, orderCategory = "name", title = "", log = TRUE,
              violin = FALSE)
```

createDfFeature	<i>Create data frame of (count/intensity) values for a selected feature along data processing steps</i>
-----------------	---

Description

The function `createDfFeature` takes as input a list of matrices and returns the row Feature of each matrix as a column of a `data.frame`. The function `createDfFeature` provides the input for the function `featurePlot`.

Usage

```
createDfFeature(l, feature)
```

Arguments

<code>l</code>	list containing matrices at different processing steps
<code>feature</code>	character, element of <code>rownames</code> of the matrices in <code>l</code>

Details

Internal usage in `shinyQC`

Value

`data.frame`

Examples

```
set.seed(1)
x1 <- matrix(rnorm(100), ncol = 10, nrow = 10,
             dimnames = list(paste("feature", seq_len(10)),
                             paste("sample", seq_len(10))))
x2 <- x1 + 5
x3 <- x2 + 10

l <- list(x1 = x1, x2 = x2, x3 = x3)
createDfFeature(l, "feature 1")
```

cv

Calculate coefficient of variation

Description

The function `cv` calculates the coefficient of variation from columns of a matrix. The coefficients of variation are calculated according to the formula $\text{sd}(y) / \text{mean}(y) * 100$ with y the column values, thus, the function returns the coefficient of variation in percentage.

Usage

```
cv(x, name = "raw")
```

Arguments

<code>x</code>	matrix
<code>name</code>	character, the name of the returned list

Details

The function returned a named list (the name is specified by the `name` argument) containing the coefficient of variation of the columns of `x`.

Value

list

Examples

```
x <- matrix(seq_len(10), ncol = 2)
cv(x)
```

`cvFeaturePlot`*Plot of feature-wise coefficient of variation values*

Description

The function `cvFeaturePlot` returns a plotly plot of coefficient of variation values. It will create a violin plot and superseded points of coefficient of variation values per list entry of `l`.

Usage

```
cvFeaturePlot(l, lines = FALSE)
```

Arguments

<code>l</code>	list containing matrices
<code>lines</code>	logical

Details

`lines = TRUE` will connect the points belonging to the same feature with a line. If there are less than two features, the violin plot will not be plotted. The violin plots will be ordered according to the order in `l`

Value

plotly

Examples

```
x1 <- matrix(seq_len(100), ncol = 10, nrow = 10,
             dimnames = list(paste("feature", seq_len(10)),
                             paste("sample", seq_len(10))))
x2 <- x1 + 5
x3 <- x2 + 10
l <- list(x1 = x1, x2 = x2, x3 = x3)
cvFeaturePlot(l, lines = FALSE)
```

dimensionReduction *Dimensionality reduction with dimensionReduction methods PCA, PCoA, NMDS, UMAP and tSNE*

Description

The function `dimensionReduction` creates a `data.frame` with the coordinates of the projected data (first entry of returned output). The function allows for the following projections: Principal Component Analysis (PCA), Principal Coordinates Analysis/Multidimensional Scaling (PCoA), Non-metric Multidimensional scaling (NMDS), t-distributed stochastic neighbor embedding (tSNE), and Uniform Manifold Approximation and Projection (UMAP).

The second list entry will contains the object returned from `prcomp` (PCA), `cmdscale` (PCoA), `isoMDS` (NMDS), `Rtsne` (tSNE), or `umap` (UMAP).

Usage

```
dimensionReduction(  
  x,  
  type = c("PCA", "PCoA", "NMDS", "tSNE", "UMAP"),  
  params = list()  
)
```

Arguments

<code>x</code>	matrix, containing no missing values, samples are in columns and features are in rows
<code>type</code>	character, specifying the type/method to use for dimensionality reduction. One of PCA, PCoA, NMDS, tSNE, or UMAP.
<code>params</code>	list, arguments/parameters given to the functions <code>stats::prcomp</code> , <code>stats::dist</code> , <code>Rtsne::Rtsne</code> , <code>umap::umap</code>

Details

The function `dimensionReduction` is a wrapper around the following functions `stats::prcomp` (PCA), `stats::cmdscale` (PCoA), `MASS::isoMDS` (NMDS), `Rtsne::Rtsne` (tSNE), and `umap::umap` (UMAP). For the function `umap::umap` the method is set to naive.

Value

list, first entry contains a `tbl`, second entry contains the object returned from `prcomp` (PCA), `cmdscale` (PCoA), `isoMDS` (NMDS), `Rtsne` (tSNE), or `umap` (UMAP)

Author(s)

Thomas Naake

Examples

```
x <- matrix(rnorm(seq_len(10000)), ncol = 100)
rownames(x) <- paste("feature", seq_len(nrow(x)))
colnames(x) <- paste("sample", seq_len(ncol(x)))
params <- list(method = "euclidean", ## dist
  initial_dims = 10, max_iter = 100, dims = 3, perplexity = 3, ## tSNE
  min_dist = 0.1, n_neighbors = 15, spread = 1) ## UMAP
dimensionReduction(x, type = "PCA", params = params)
dimensionReduction(x, type = "PCoA", params = params)
dimensionReduction(x, type = "NMDS", params = params)
dimensionReduction(x, type = "tSNE", params = params)
dimensionReduction(x, type = "UMAP", params = params)
```

dimensionReductionPlot

Plot the coordinates from dimensionReduction values

Description

The function `dimensionReductionPlot` creates a dimension reduction plot. The function takes as input the `tbl` object obtained from the `dimensionReduction` function. The `tbl` contains transformed values by one of the dimension reduction methods.

Usage

```
dimensionReductionPlot(
  tbl,
  se,
  color = c("none", colnames(se@colData)),
  size = c("none", colnames(se@colData)),
  explainedVar = NULL,
  x_coord,
  y_coord,
  height = 600,
  interactive = TRUE
)
```

Arguments

<code>tbl</code>	<code>tbl</code> as obtained by the function <code>dimensionReduction</code>
<code>se</code>	<code>SummarizedExperiment</code>
<code>color</code>	character, one of "none" or <code>colnames(se@colData)</code>
<code>size</code>	character, one of "none" or <code>colnames(se@colData)</code>
<code>explainedVar</code>	<code>NULL</code> or named numeric, if numeric <code>explainedVar</code> contains the explained variance per principal component (names of <code>explainedVar</code> corresponds to the principal components)

x_coord	character, column name of tbl that stores x coordinates
y_coord	character, column name of tbl that stores y coordinates
height	numeric, specifying the height of the plot (in pixels)
interactive	logical(1), if TRUE dimensionReductionPlot will return a plotly object, if FALSE dimensionReductionPlot will return a gg object

Details

The function dimensionReductionPlot is a wrapper for a ggplot/ggplotly expression.

Value

plotly or gg

Author(s)

Thomas Naake

Examples

```
library(SummarizedExperiment)

## create se
a <- matrix(seq_len(100), nrow = 10, ncol = 10, byrow = TRUE,
            dimnames = list(seq_len(10), paste("sample", seq_len(10))))
set.seed(1)
a <- a + rnorm(100)
cD <- data.frame(name = colnames(a), type = c(rep("1", 5), rep("2", 5)),
                median_vals = apply(a, 2, median))
rD <- data.frame(spectra = rownames(a))
se <- SummarizedExperiment(assay = a, rowData = rD, colData = cD)

pca <- dimensionReduction(x = assay(se), type = "PCA", params = list())[[1]]

dimensionReductionPlot(tbl = pca, se = se, color = "type", size = "median_vals",
                      x_coord = "PC1", y_coord = "PC2")
```

distSample

Create a heatmap using distance information between samples

Description

The function distSample creates a heatmap from a distance matrix created by the function distShiny. The heatmap is annotated by the column specified by the label column in colData(se).

Usage

```
distSample(d, se, label = "name", title = "raw", ...)
```

Arguments

<code>d</code>	matrix containing distances, obtained from <code>distShiny</code>
<code>se</code>	<code>SummarizedExperiment</code>
<code>label</code>	character, refers to a column in <code>colData(se)</code>
<code>title</code>	character
<code>...</code>	further arguments passed to <code>ComplexHeatmap::Heatmap</code>

Details

Internal use in `shinyQC`

Value

Heatmap object from `ComplexHeatmap`

Examples

```
## create se
a <- matrix(seq_len(100), nrow = 10, ncol = 10,
            dimnames = list(seq_len(10), paste("sample", seq_len(10))))
a[c(1, 5, 8), seq_len(5)] <- NA
set.seed(1)
a <- a + rnorm(100)
a_i <- imputeAssay(a, method = "MinDet")
cD <- data.frame(name = colnames(a_i),
                type = c(rep("1", 5), rep("2", 5)))
rD <- data.frame(spectra = rownames(a_i))
se <- SummarizedExperiment::SummarizedExperiment(assay = a_i, rowData = rD,
                                                colData = cD)

dist <- distShiny(a_i)
distSample(dist, se, label = "type", title = "imputed",
           show_row_names = TRUE)
```

`distShiny`

Create distance matrix from numerical matrix

Description

The function `distShiny` takes as an input a numerical matrix or `data.frame` and returns the distances between the rows and columns based on the defined method (e.g. euclidean distance).

Usage

```
distShiny(x, method = "euclidean")
```

Arguments

`x` matrix or data.frame with samples in columns and features in rows
`method` character, method for distance calculation

Details

Internal use in shinyQC.

Value

matrix

Examples

```
x <- matrix(seq_len(100), nrow = 10, ncol = 10,
            dimnames = list(seq_len(10), paste("sample", seq_len(10))))
distShiny(x = x)
```

driftPlot

Plot the trend line for aggregated values

Description

The function `driftPlot` aggregates the (count/intensity) values from the `assay()` slot of a `SummarizedExperiment` by the median or sum of the (count/intensity) values. `driftPlot` then visualizes these aggregated values and adds a trend line (using either LOESS or a linear model) from (a subset of) the aggregated values. The subset is specified by the arguments `category` and `level`.

Usage

```
driftPlot(
  se,
  aggregation = c("median", "sum"),
  category = colnames(colData(se)),
  orderCategory = colnames(colData(se)),
  level = c("all", unique(colData(se)[, category])),
  method = c("loess", "lm")
)
```

Arguments

`se` `SummarizedExperiment`
`aggregation` character, type of aggregation of (count/intensity) values
`category` character, column of `colData(se)`
`orderCategory` character, column of `colData(se)`

level	character, from which samples should the LOESS curve be calculated, either "all" or one of the levels of the selected columns of colData(se) ("category")
method	character, either "loess" or "lm"

Details

The x-values are sorted according to the orderCategory argument: The levels of the corresponding column in colData(se) are pasted with the sample names (in the column name) and factorized. Internal usage in shinyQC.

Value

gg object from ggplot2

Examples

```
#' ## create se
set.seed(1)
a <- matrix(rnorm(1000), nrow = 10, ncol = 100,
            dimnames = list(seq_len(10), paste("sample", seq_len(100))))
a[c(1, 5, 8), seq_len(5)] <- NA
cD <- data.frame(name = colnames(a), type = c(rep("1", 50), rep("2", 50)))
rD <- data.frame(spectra = rownames(a))
se <- SummarizedExperiment::SummarizedExperiment(assay = a,
            rowData = rD, colData = cD)

driftPlot(se, aggregation = "sum", category = "type",
            orderCategory = "type", level = "1", method = "loess")
```

ECDF

Create ECDF plot of a sample against a reference

Description

The function ECDF creates a plot of the empirical cumulative distribution function of a specified sample and an outgroup (reference). The reference is specified by the group argument. The row-wise (feature) mean values of the reference are calculated after excluding the specified sample.

Usage

```
ECDF(se, sample = colnames(se), group = c("all", colnames(colData(se))))
```

Arguments

se	SummarizedExperiment object
sample	character, name of the sample to compare against the group
group	character, either "all" or one of colnames(colData(se))

Details

Internal use in shinyQC.

The function ECDF uses the `ks.test` function from `stats` to perform a two-sample Kolmogorov-Smirnov test. The Kolmogorov-Smirnov test is run with the alternative `"two.sided"` (null hypothesis is that the true distribution function of the sample is equal to the hypothesized distribution function of the group).

The exact argument in `ks.test` is set to `NULL`, meaning that an exact p-value is computed if the product of the sample sizes is less than 10000 of `sample` and `group`. Otherwise, asymptotic distributions are used whose approximations might be inaccurate in low sample sizes.

Value

gg object from `ggplot2`

Examples

```
## create se
set.seed(1)
a <- matrix(rnorm(1000), nrow = 100, ncol = 10,
            dimnames = list(seq_len(100), paste("sample", seq_len(10))))
a[c(1, 5, 8), seq_len(5)] <- NA
cD <- data.frame(name = colnames(a), type = c(rep("1", 5), rep("2", 5)))
rD <- data.frame(spectra = rownames(a))
se <- SummarizedExperiment(assay = a, rowData = rD, colData = cD)

ECDF(se, sample = "sample 1", group = "all")
```

explVar	<i>Retrieve the explained variance for each principal component (PCA) or axis (PCoA)</i>
---------	--

Description

The function `explVar` calculates the proportion of explained variance for each principal component (PC, `type = "PCA"`) and axis (`type = "PCoA"`).

Usage

```
explVar(d, type = c("PCA", "PCoA"))
```

Arguments

<code>d</code>	prcomp or list from <code>cmdscale</code>
<code>type</code>	character, one of <code>"PCA"</code> or <code>"PCoA"</code>

Details

explVar uses the function prcomp from the stats package to retrieve the explained standard deviation per PC (type = "PCA") and the function cmdscale from the stats package to retrieve the explained variation based on eigenvalues per Axis (type = "PCoA").

Value

numeric vector with the proportion of explained variance for each PC or Axis

Author(s)

Thomas Naake

Examples

```
x <- matrix(seq_len(100), nrow = 10, ncol = 10,
            dimnames = list(seq_len(10), paste("sample", seq_len(10))))
set.seed(1)
x <- x + rnorm(100)

## run for PCA
pca <- dimensionReduction(x = x,
                        params = list(center = TRUE, scale = TRUE), type = "PCA")[[2]]
explVar(d = pca, type = "PCA")

## run for PCoA
pcoa <- dimensionReduction(x = x,
                          params = list(method = "euclidean"), type = "PCoA")[[2]]
explVar(d = pcoa, type = "PCoA")
```

extractComb

Obtain the features that are present in a specified set

Description

The function extractComb extracts the features that match a combination depending if the features was measured or missing. The function will return the sets that match the combination, thus, the function might be useful when answering questions about which features are measured/missing under certain combinations (e.g. sample types or experimental conditions).

Usage

```
extractComb(se, combination, measured = TRUE, category = "type")
```

Arguments

se	SummarizedExperiment
combination	character, refers to factors in category
measured	logical
category	character, corresponding to a column name in colData(se)

Details

The function `extractComb` uses the `make_comb_mat` function from `ComplexHeatmap` package.

Presence is defined by a feature being measured in at least one sample of a set.

Absence is defined by a feature with only missing values (i.e. no measured values) of a set.

Value

character

Examples

```
## create se
a <- matrix(seq_len(100), nrow = 10, ncol = 10,
            dimnames = list(seq_len(10), paste("sample", seq_len(10))))
a[c(1, 5, 8), seq_len(5)] <- NA
set.seed(1)
a <- a + rnorm(100)
cD <- data.frame(name = colnames(a), type = c(rep("1", 5), rep("2", 5)))
rD <- data.frame(spectra = rownames(a))
se <- SummarizedExperiment::SummarizedExperiment(assay = a, rowData = rD, colData = cD)

extractComb(se, combination = "2", measured = TRUE, category = "type")
```

featurePlot

Create a plot of (count/intensity) values over the samples

Description

The function `featurePlot` creates a plot of (count/intensity) values for different data processing steps (referring to columns in the `data.frame`) over the different samples (referring to rows in the `data.frame`).

Usage

```
featurePlot(df)
```

Arguments

df	data.frame
----	------------

Details

Internal usage in shinyQC.

Value

gg object from ggplot2

Examples

```
set.seed(1)
x1 <- matrix(rnorm(100), ncol = 10, nrow = 10,
             dimnames = list(paste("feature", seq_len(10)),
                             paste("sample", seq_len(10))))
x2 <- x1 + 5
x3 <- x2 + 10
l <- list(x1 = x1, x2 = x2, x3 = x3)
df <- createDfFeature(1, "feature 1")
featurePlot(df)
```

histFeature

Histogram for measured value per feature

Description

The function histFeature creates a histogram with the number of measured/missing values per feature.

Usage

```
histFeature(x, measured = TRUE, ...)
```

Arguments

x	matrix containing intensities. Missing values are encoded as NA.
measured	logical, should the measured values (measured = TRUE) or missing values (measured = FALSE) be taken
...	additional parameters passed to geom_histogram, e.g. binwidth.

Value

plotly object from ggplotly

Examples

```
x <- matrix(c(c(1, 1, 1), c(1, NA, 1), c(1, NA, 1),
             c(1, 1, 1), c(NA, 1, 1), c(NA, 1, 1)), byrow = FALSE, nrow = 3)
colnames(x) <- c("A_1", "A_2", "A_3", "B_1", "B_2", "B_3")
histFeature(x, binwidth = 1)
```

histFeatureCategory *Histogram of features per sample type*

Description

The function histFeatureCategory creates histogram plots for each sample type in se.

Usage

```
histFeatureCategory(se, measured = TRUE, category = "type", ...)
```

Arguments

se	SummarizedExperiment, the assay slot contains the intensity values per sample. Missing values are encoded as NA.
measured	logical, should the measured values (measured = TRUE) or missing values (measured = FALSE) be taken
category	character, corresponding to a column in colData(se)
...	additional parameters passed to geom_histogram, e.g. binwidth.

Value

plotly object from ggplotly

Examples

```
## create se
a <- matrix(seq_len(100), nrow = 10, ncol = 10,
            dimnames = list(seq_len(10), paste("sample", seq_len(10))))
a[c(1, 5, 8), seq_len(5)] <- NA
set.seed(1)
a <- a + rnorm(100)
cD <- data.frame(name = colnames(a), type = c(rep("1", 5), rep("2", 5)))
rD <- data.frame(spectra = rownames(a))
se <- SummarizedExperiment::SummarizedExperiment(assay = a,
                                                rowData = rD, colData = cD)

histFeatureCategory(se, measured = TRUE, category = "type")
```

hist_sample	<i>Plot a histogram of the number of a category</i>
-------------	---

Description

hist_sample plots the number of a category (e.g. sample types) as a histogram. It use the returned tbl from hist_sample_num.

Usage

```
hist_sample(tbl, category = "type")
```

Arguments

tbl	tbl as returned by hist_sample_num
category	character, x-axis label of the plot

Value

gg object from ggplot2

Examples

```
## create se
a <- matrix(seq_len(100), nrow = 10, ncol = 10,
            dimnames = list(seq_len(10), paste("sample", seq_len(10))))
a[c(1, 5, 8), seq_len(5)] <- NA
set.seed(1)
a <- a + rnorm(100)
cD <- data.frame(name = colnames(a), type = c(rep("1", 4), rep("2", 6)))
rD <- data.frame(spectra = rownames(a))
se <- SummarizedExperiment::SummarizedExperiment(assay = a,
        rowData = rD, colData = cD)

tbl <- hist_sample_num(se, category = "type")
hist_sample(tbl)
```

hist_sample_num	<i>Return the number of a category</i>
-----------------	--

Description

hist_sample_num returns the number of a category (e.g. sample types) as a tbl. The function will retrieve first the column category in colData(se). The function will return a tbl containing the numerical values of the quantities.

Usage

```
hist_sample_num(se, category = "type")
```

Arguments

```
se          SummarizedExperiment object
category    character, corresponding to a column in colData(se)
```

Value

```
tbl
```

Examples

```
## create se
a <- matrix(seq_len(100), nrow = 10, ncol = 10,
            dimnames = list(seq_len(10), paste("sample", seq_len(10))))
a[c(1, 5, 8), seq_len(5)] <- NA
set.seed(1)
a <- a + rnorm(100)
cD <- data.frame(name = colnames(a), type = c(rep("1", 4), rep("2", 6)))
rD <- data.frame(spectra = rownames(a))
se <- SummarizedExperiment::SummarizedExperiment(assay = a,
                                                rowData = rD, colData = cD)

hist_sample_num(se, category = "type")
```

```
hoeffDPlot
```

```
Create a plot from a list of Hoeffding's D values
```

Description

The function `hoeffDPlot` creates via `ggplot` a violin plot per factor, a jitter plot of the data points and (optionally) connects the points via lines. `hoeffDPlot` uses the `plotly` package to make the figure interactive.

Usage

```
hoeffDPlot(df, lines = TRUE)
```

Arguments

```
df          data.frame containing one or multiple columns containing the Hoeffding's D
            statistics
lines       logical, should points belonging to the same sample be connected
```

Details

The function `hoeffDPlot` will create the violin plot and jitter plot according to the specified order given by the `colnames` of `df`. `hoeffDPlot` will thus internally refactor the `colnames` of the supplied `data.frame` according to the order of the `colnames`.

Value

gg object from `ggplot2`

Examples

```
## create se
set.seed(1)
a <- matrix(rnorm(10000), nrow = 1000, ncol = 10,
            dimnames = list(seq_len(1000), paste("sample", seq_len(10))))
a[c(1, 5, 8), seq_len(5)] <- NA
cD <- data.frame(name = colnames(a), type = c(rep("1", 5), rep("2", 5)))
rD <- data.frame(spectra = rownames(a))
se <- SummarizedExperiment::SummarizedExperiment(assay = a,
                                                rowData = rD, colData = cD)

tbl <- MValues(se, log = FALSE, group = "all")
hd_r <- hoeffDValues(tbl, "raw")

## normalized values
se_n <- se
assay(se_n) <- normalizeAssay(a, "sum")
tbl_n <- MValues(se_n, log = FALSE, group = "all")
hd_n <- hoeffDValues(tbl_n, "normalized")

df <- data.frame(raw = hd_r, normalized = hd_n)
hoeffDPlot(df, lines = TRUE)
hoeffDPlot(df, lines = FALSE)
```

hoeffDValues

Create values of Hoeffding's D statistics from M and A values

Description

The function creates and returns Hoeffding's D statistics values from MA values.

In case `sample_n` is set to a numerical value (e.g. 10000), a random subset containing `sample_n` is taken to calculate Hoeffding's D values to speed up the calculation. In case there are less features than `sample_n`, all features are taken.

Usage

```
hoeffDValues(tbl, name = "raw", sample_n = NULL)
```

Arguments

tbl	tibble, as obtained from the function MAvalues
name	character(1), name of the returned list
sample_n	numeric(1), number of features (subset) to be taken for calculation of Hoeffding's D values

Details

The function uses the function `hoeffd` from the `Hmisc` package to calculate the values.

Value

named list with Hoeffding's D values per sample

Examples

```
## create se
a <- matrix(seq_len(100), nrow = 10, ncol = 10,
            dimnames = list(seq_len(10), paste("sample", seq_len(10))))
a[c(1, 5, 8), seq_len(5)] <- NA
set.seed(1)
a <- a + rnorm(100)
cD <- data.frame(name = colnames(a), type = c(rep("1", 5), rep("2", 5)))
rD <- data.frame(spectra = rownames(a))
se <- SummarizedExperiment::SummarizedExperiment(assay = a,
                                                rowData = rD, colData = cD)

tbl <- MAvalues(se)
hoeffDValues(tbl, "raw")

## normalized values
se_n <- se
assay(se_n) <- normalizeAssay(a, "sum")
tbl_n <- MAvalues(se_n, group = "all")
hoeffDValues(tbl_n, "normalized")

## transformed values
se_t <- se
assay(se_t) <- transformAssay(a, "log")
tbl_t <- MAvalues(se_t, group = "all")
hoeffDValues(tbl_t, "transformed")
```

Description

The function `impute` imputes missing values based on one of the following principles: Bayesian missing value imputation (BPCA), k-nearest neighbor averaging (kNN), Maximum likelihood-based imputation method using the EM algorithm (MLE), replacement by the smallest non-missing value in the data (Min), replacement by the minimal value observed as the q-th quantile (MinDet, default $q = 0.01$), and replacement by random draws from a Gaussian distribution centred to a minimal value (MinProb).

Usage

```
imputeAssay(a, method = c("BPCA", "kNN", "MLE", "Min", "MinDet", "MinProb"))
```

Arguments

<code>a</code>	matrix with samples in columns and features in rows
<code>method</code>	character, one of "BPCA", "kNN", "MLE", "Min", "MinDet", or "MinProb"

Details

BPCA wrapper for `pcaMethods::pca` with `methods = "bpca"`. BPCA is a missing at random (MAR) imputation method.

kNN wrapper for `impute::impute.knn` with `k = 10`, `rowmax = 0.5`, `colmax = 0.5`, `maxp = 1500`. kNN is a MAR imputation method.

MLE wrapper for `imputeLCMD::impute.MAR` with `method = "MLE"`, `model.selector = 1/imputeLCMD::impute.wrapper.M`. MLE is a MAR imputation method.

Min imputes the missing values by the observed minimal value of x . Min is a missing not at random (MNAR) imputation method.

MinDet is a wrapper for `imputeLCMD::impute.MinDet` with `q = 0.01`. MinDet performs the imputation using a deterministic minimal value approach. The missing entries are replaced with a minimal value, estimated from the q-th quantile from each sample. MinDet is a MNAR imputation method.

MinProb is a wrapper for `imputeLCMD::impute.MinProb` with `q = 0.01` and `tune.sigma = 1`. MinProb performs the imputation based on random draws from a Gaussian distribution with the mean set to the minimal value of a sample. MinProb is a MNAR imputation method.

Value

matrix

Examples

```
a <- matrix(seq_len(100), nrow = 10, ncol = 10,
            dimnames = list(seq_len(10), paste("sample", seq_len(10))))
a[c(1, 5, 8), seq_len(5)] <- NA

imputeAssay(a, method = "kNN")
imputeAssay(a, method = "Min")
imputeAssay(a, method = "MinDet")
```



```
tbl <- MAvalues(se, log = FALSE, group = "all")
MAplot(tbl, group = "all", plot = "all")
```

MAvalues

Create values (M and A) for MA plot

Description

The function MAvalues will create MA values as input for the function MAplot and hoeffDValues. M and A are specified relative to specified samples which is determined by the group argument. In case of group == "all", all samples (except the specified one) are taken for the reference calculation. In case of group != "all" will use the samples belonging to the same group given in colnames(colData(se)) except the specified one.

Usage

```
MAvalues(se, log2 = TRUE, group = c("all", colnames(colData(se))))
```

Arguments

se	SummarizedExperiment
log2	logical, specifies if values are log2-transformed prior to calculating M and A values. If the values are already transformed, log2 should be set to FALSE. If log2 = TRUE and if there are values in assay(se) that are 0, the log2 values are calculated by log2(assay(se) + 1)
group	character, either "all" or one of colnames(colData(se))

Value

tbl with columns Feature, name (sample name), A, M and additional columns of colData(se)

Examples

```
## create se
set.seed(1)
a <- matrix(rnorm(10000), nrow = 1000, ncol = 10,
            dimnames = list(seq_len(1000), paste("sample", seq_len(10))))
a[c(1, 5, 8), seq_len(5)] <- NA
cD <- data.frame(name = colnames(a), type = c(rep("1", 5), rep("2", 5)))
rD <- data.frame(spectra = rownames(a))
se <- SummarizedExperiment(assay = a, rowData = rD, colData = cD)

MAvalues(se, log = FALSE, group = "all")
```

measuredCategory	<i>Obtain the number of measured intensities per sample type</i>
------------------	--

Description

The function `measuredCategory` creates a `tbl` with the number of measured values per feature. 0 means that there were only missing values (NA) for the feature and sample type. `measuredCategory` will return a `tbl` where columns are the unique sample types and rows are the features as in `assay(se)`.

Usage

```
measuredCategory(se, measured = TRUE, category = "type")
```

Arguments

<code>se</code>	SummarizedExperiment
<code>measured</code>	logical, should the measured values (<code>measured = TRUE</code>) or missing values (<code>measured = FALSE</code>) be taken
<code>category</code>	character, corresponds to a column name in <code>colData(se)</code>

Details

`measuredCategory` is a helper function.

Value

matrix with number of measured/missing features per category type

Examples

```
## create se
set.seed(1)
a <- matrix(rnorm(100), nrow = 10, ncol = 10,
            dimnames = list(seq_len(10), paste("sample", seq_len(10))))
a[c(1, 5, 8), seq_len(5)] <- NA
cD <- data.frame(name = colnames(a), type = c(rep("1", 5), rep("2", 5)))
rD <- data.frame(spectra = rownames(a))
se <- SummarizedExperiment::SummarizedExperiment(assay = a,
                                                rowData = rD, colData = cD)

measuredCategory(se, measured = TRUE, category = "type")
```

`mosaic`*Mosaic plot for two factors in colData(se)*

Description

The function `mosaic` creates a mosaic plot of two factors from an `SummarizedExperiment` object. The columns `f1` and `f2` are taken from `colData(se)`.

Usage

```
mosaic(se, f1, f2)
```

Arguments

<code>se</code>	SummarizedExperiment object
<code>f1</code>	character, <code>f1</code> is one of the column names in <code>colData(se)</code>
<code>f2</code>	character, <code>f2</code> is one of the column names in <code>colData(se)</code>

Details

Code partly taken from <https://stackoverflow.com/questions/21588096/pass-string-to-facet-grid-ggplot2>

Value

gg object from `ggplot2`

Examples

```
## create se
set.seed(1)
a <- matrix(rnorm(100), nrow = 10, ncol = 10,
            dimnames = list(seq_len(10), paste("sample", seq_len(10))))
a[c(1, 5, 8), seq_len(5)] <- NA
cD <- data.frame(name = colnames(a),
                 type = c(rep("1", 5), rep("2", 5)),
                 cell_type = c("A", "B"))
rD <- data.frame(spectra = rownames(a))
se <- SummarizedExperiment::SummarizedExperiment(assay = a,
                                                  rowData = rD, colData = cD)

mosaic(se, "cell_type", "type")
```

normalizeAssay	<i>Normalize a data sets (reduce technical sample effects)</i>
----------------	--

Description

The function `normalizeAssay` performs normalization by sum of the (count/intensity) values per sample (`method = "sum"`), quantile division per sample (`method = "quantile division"`), or by quantile normalization (adjusting the value distributions that they become identical in statistical properties, `method = "quantile"`). The value for quantile division (e.g., the 75 specified by the `probs` argument). Quantile normalization is performed by using the `normalizeQuantiles` function from `limma`.

For the methods `"sum"` and `"quantile division"`, normalization will be done depending on the `multiplyByNormalizationValue` parameter. If set to `TRUE`, normalization values (e.g. sum or quantile) will be calculated per sample. In a next step, adjusted normalization values will be calculated for each sample in relation to the median normalization values across all samples. Finally, the values in `a` are multiplied by these adjusted normalization values. If `multiplyByNormalizationValue` is set to `FALSE`, normalization values (e.g. sum or quantile) will be calculated per sample. The values in `a` are sample-wise divided by the normalization values.

Usage

```
normalizeAssay(
  a,
  method = c("none", "sum", "quantile division", "quantile"),
  probs = 0.75,
  multiplyByNormalizationValue = FALSE
)
```

Arguments

<code>a</code>	matrix with samples in columns and features in rows
<code>method</code>	character, one of <code>"none"</code> , <code>"sum"</code> , <code>"quantile division"</code> , <code>"quantile"</code>
<code>probs</code>	numeric, ranging between $[0, 1)$. <code>probs</code> is used as the divisor for quantile division in <code>method = "quantile division"</code>
<code>multiplyByNormalizationValue</code>	logical, if <code>TRUE</code> , normalization values will be calculated and the values in <code>a</code> will be multiplied by the values. The parameter is only relevant for <code>method = "sum"</code> and <code>method = "quantile division"</code>

Details

Internal usage in `shinyQC`. If `method` is set to `"none"`, the object `x` is returned as is (pass-through).

If `probs` is `NULL`, `probs` is internally set to 0.75 if `method = "quantile division"`.

Depending on the values in `a`, if `multiplyByNormalizationValue` is set to `TRUE` the returned normalized values will be in the same order of magnitude than the original values, while if `FALSE`, the returned values will be in a smaller order of magnitude.

Value

matrix

Examples

```
a <- matrix(seq_len(100), nrow = 10, ncol = 10,
            dimnames = list(seq_len(10), paste("sample", seq_len(10))))
normalizeAssay(a, "sum")
```

permuteExplVar	<i>Permute the expression values and retrieve the explained variance</i>
----------------	--

Description

The function permuteExplVar determines the explained variance of the permuted expression matrix (x). It is used to determine the optimal number of PCs for tSNE.

Usage

```
permuteExplVar(x, n = 10, center = TRUE, scale = TRUE, sample_n = NULL)
```

Arguments

<code>x</code>	matrix or data.frame, samples in columns and features in rows
<code>n</code>	numeric, number of permutation rounds
<code>center</code>	logical, passed to the function explVar
<code>scale</code>	logical, passed to the function explVar
<code>sample_n</code>	numeric(1), number of features (subset) to be taken for calculation of permuted explained variance, the top <code>sample_n</code> varying values based on their standard deviation will be taken

Details

For the input of tSNE, typically, we want to reduce the initial number of dimensions linearly with PCA (used as the `initial_dims` arguments in the `Rtsne` function). The reduced data set is used for feeding into tSNE. By plotting the percentage of variance explained by the Principal Components (PCs) we can estimate how many PCs we keep as input into tSNE. However, if we select too many PCs, noise will be included as input to tSNE; if we select too few PCs we might lose the important data structures. To get a better understanding how many PCs to include, randomization will be employed and the observed variance will be compared to the permuted variance.

Value

matrix with explained variance

Author(s)

Thomas Naake

Examples

```
x <- matrix(seq_len(100), nrow = 10, ncol = 10,  
  dimnames = list(seq_len(10), paste("sample", seq_len(10))))  
permuteExplVar(x = x, n = 10, center = TRUE, scale = TRUE, sample_n = NULL)
```

plotCV

Plot CV values

Description

The function plotCV displays the coefficient of variation values of set of values supplied in a data.frame object. The function will create a plot using the ggplot2 package and will print the values in the different columns in different colors.

Usage

```
plotCV(df)
```

Arguments

df data.frame containing one or multiple columns containing the coefficients of variation

Details

Internal usage in shinyQC.

Value

gg object from ggplot2

Examples

```
x1 <- matrix(seq_len(10), ncol = 2)  
x2 <- matrix(seq(11, 20), ncol = 2)  
x3 <- matrix(seq(21, 30), ncol = 2)  
x4 <- matrix(seq(31, 40), ncol = 2)  
  
## calculate cv values  
cv1 <- cv(x1, "x1")  
cv2 <- cv(x2, "x2")  
cv3 <- cv(x3, "x3")  
cv4 <- cv(x4, "x4")
```

```
df <- data.frame(cv1, cv2, cv3, cv4)
plotCV(df)
```

plotPCALoadings *Plot for PCA loadings of features*

Description

The function plotPCALoadings creates a loadings plot of the features.

Usage

```
plotPCALoadings(tbl, x_coord, y_coord)
```

Arguments

tbl	tbl as obtained by the function dimensionReduction
x_coord	character, column name of tbl that stores x coordinates
y_coord	character, column name of tbl that stores y coordinates

Details

The function takes as input the output of the function tblPlotPCALoadings. It uses the ggplotly function from plotly to create an interactive plotly plot.

Value

plotly

Author(s)

Thomas Naake

Examples

```
x <- matrix(rnorm(seq_len(10000)), ncol = 100)
rownames(x) <- paste("feature", seq_len(nrow(x)))
colnames(x) <- paste("sample", seq_len(ncol(x)))
params <- list(method = "euclidean", ## dist
               initial_dims = 10, max_iter = 100, dims = 3, perplexity = 3, ## tSNE
               min_dist = 0.1, n_neighbors = 15, spread = 1) ## UMAP
tbl <- tblPCALoadings(x, params)
plotPCALoadings(tbl, x_coord = "PC1", y_coord = "PC2")
```

plotPCAVar	<i>Plot of explained variance against the principal components</i>
------------	--

Description

The function `plotPCAVar` plots the explained variance (in y-axis against the principal components for the measured and permuted values.

Usage

```
plotPCAVar(var_x, var_perm = NULL)
```

Arguments

<code>var_x</code>	numeric (named numeric vector)
<code>var_perm</code>	matrix with the explained variance obtained by permutation (function <code>permuteExplVar</code>)

Details

The argument `var_perm` is optional and visualization of permuted values can be omitted by setting `var_perm = NULL`.

Value

gg object from `ggplot`

Author(s)

Thomas Naake

Examples

```
x <- matrix(seq_len(100), ncol = 10)
pca <- dimensionReduction(x = x, params = list(center = TRUE, scale = TRUE),
  type = "PCA")[[2]]
var_x <- explVar(d = pca, type = "PCA")
var_perm <- permuteExplVar(x = x, n = 100, center = TRUE, scale = TRUE)
plotPCAVar(var_x = var_x, var_perm = var_perm)
```

plotPCAVarPvalue	<i>Plot p-values for the significance of principal components</i>
------------------	---

Description

The function `plotPCAVarPvalue` plots the p-values of significances of principal components. Using the visual output, the optimal number of principal components can be selected.

Usage

```
plotPCAVarPvalue(var_x, var_perm)
```

Arguments

<code>var_x</code>	numeric, measured variances
<code>var_perm</code>	matrix, variances obtained by permutation

Details

Internal usage in shinyQC.

Value

gg object from ggplot

Author(s)

Thomas Naake

Examples

```
x <- matrix(seq_len(100), ncol = 10)
pca <- dimensionReduction(x = x, params = list(center = TRUE, scale = TRUE),
  type = "PCA")[[2]]
var_x <- explVar(d = pca, type = "PCA")
var_perm <- permuteExplVar(x = x, n = 100, center = TRUE, scale = TRUE)
plotPCAVarPvalue(var_x = var_x, var_perm = var_perm)
```

`samplesMeasuredMissing`

Create tibble containing number of measured/missing features of samples

Description

`samplesMeasuredMissing` returns a tibble with the number of measured/missing features of samples. The function will take as input a `SummarizedExperiment` object and will access its `assay()` slot

Usage

```
samplesMeasuredMissing(se)
```

Arguments

`se` SummarizedExperiment object

Value

tibble with number of measured/missing features per sample

Examples

```
## create se
a <- matrix(seq_len(100), nrow = 10, ncol = 10,
            dimnames = list(seq_len(10), paste("sample", seq_len(10))))
a[c(1, 5, 8), seq_len(5)] <- NA
set.seed(1)
a <- a + rnorm(100)
sample <- data.frame(name = colnames(a), type = c(rep("1", 5), rep("2", 5)))
featData <- data.frame(spectra = rownames(a))
se <- SummarizedExperiment::SummarizedExperiment(assay = a,
        rowData = featData, colData = sample)

## create the data.frame with information on number of measured/missing
## values
samplesMeasuredMissing(se)
```

`shinyQC`*Shiny application for initial QC exploration of -omics data sets*

Description

The shiny application allows to explore -omics data sets especially with a focus on quality control. shinyQC gives information on the type of samples included (if this was previously specified within the SummarizedExperiment object). It gives information on the number of missing and measured values across features and across sets (e.g. quality control samples, control, and treatment groups, only displayed for SummarizedExperiment objects that contain missing values).

shinyQC includes functionality to display (count/intensity) values across samples (to detect drifts in intensity values during the measurement), to display mean-sd plots, MA plots, ECDF plots, and distance plots between samples. shinyQC includes functionality to perform dimensionality reduction (currently limited to PCA, PCoA, NMDS, tSNE, and UMAP). Additionally, it includes functionality to perform differential expression analysis (currently limited to moderated t-tests and the Wald test).

Usage

```
shinyQC(se, app_server = FALSE)
```

Arguments

<code>se</code>	SummarizedExperiment object (can be omitted)
<code>app_server</code>	logical (set to TRUE if run under a server environment)

Details

`rownames(se)` should be set to the corresponding name of features, while `colnames(se)` should be set to the sample IDs. `rownames(se)` and `colnames(se)` are not allowed to be NULL. `colnames(se)`, `colnames(assay(se))` and `rownames(colData(se))` all have to be identical.

shinyQC allows to subset the supplied SummarizedExperiment object.

On exit of the shiny application, the (subsetting) SummarizedExperiment object is returned with information on the processing steps (normalization, transformation, batch correction and imputation). The object will only returned if `app_server = FALSE` and if the function call is assigned to an object, e.g. `tmp <- shinyQC(se)`.

If the `se` argument is omitted the app will load an interface that allows for data upload.

Value

shiny application, SummarizedExperiment upon exiting the shiny application

Author(s)

Thomas Naake

Examples

```
library(dplyr)
library(SummarizedExperiment)

## create se
set.seed(1)
a <- matrix(rnorm(100, mean = 10, sd = 2), nrow = 10, ncol = 10,
            dimnames = list(seq_len(10), paste("sample", seq_len(10))))
a[c(1, 5, 8), seq_len(5)] <- NA
cD <- data.frame(name = colnames(a), type = c(rep("1", 5), rep("2", 5)))
rD <- data.frame(spectra = rownames(a))
se <- SummarizedExperiment(assay = a, rowData = rD, colData = cD)

shinyQC(se)
```

sumDistSample

Plot the sum of distances to other samples

Description

The function `sumDistSample` creates a plot showing the sum of distance of a sample to other samples.

Usage

```
sumDistSample(d, title = "raw")
```

Arguments

`d` matrix containing distances, obtained from `distShiny`
`title` character specifying the title to be added to the plot

Value

gg object from `ggplot2`

Examples

```
a <- matrix(seq_len(100), nrow = 10, ncol = 10,
            dimnames = list(seq_len(10), paste("sample", seq_len(10))))
dist <- distShiny(a)

sumDistSample(dist, title = "raw")
```

tblPCALoadings	<i>Return tibble with PCA loadings for features</i>
----------------	---

Description

The function `tblPCALoadings` returns a tibble with loadings values for the features (row entries) in `x`.

Usage

```
tblPCALoadings(x, params)
```

Arguments

<code>x</code>	matrix, containing no missing values
<code>params</code>	list, arguments/parameters given to the function <code>stats::prcomp</code>

Details

The function `tblPCALoadings` accesses the list entry `rotation` of the `prcomp` object.

Value

tbl

Author(s)

Thomas Naake

Examples

```
set.seed(1)
x <- matrix(rnorm(seq_len(10000)), ncol = 100)
rownames(x) <- paste("feature", seq_len(nrow(x)))
colnames(x) <- paste("sample", seq_len(ncol(x)))
params <- list(method = "euclidean", ## dist
               initial_dims = 10, max_iter = 100, dims = 3, perplexity = 3, ## tSNE
               min_dist = 0.1, n_neighbors = 15, spread = 1) ## UMAP
tblPCALoadings(x, params)
```

transformAssay	<i>Transform the (count/intensity) values of a data.frame, tbl or matrix</i>
----------------	--

Description

The function `transformAssay` transforms the (count/intensity) values of a matrix. It uses either `log`, `log2`, variance stabilizing normalisation (`vsn`) or no transformation method (pass-through, `none`). The object `x` has the samples in the columns and the features in the rows.

Usage

```
transformAssay(a, method = c("none", "log", "log2", "vsn"), .offset = 1)
```

Arguments

<code>a</code>	matrix with samples in columns and features in rows
<code>method</code>	character, one of "none", "log", "log2" or "vsn"
<code>.offset</code>	numeric(1), offset to add when method set to "log" or "log2" and a contains values of 0, default to 1

Details

Internal use in `shinyQC`.

Value

matrix

Examples

```
a <- matrix(seq_len(1000), nrow = 100, ncol = 10,  
            dimnames = list(seq_len(100), paste("sample", seq_len(10))))  
transformAssay(a, "none")  
transformAssay(a, "log")  
transformAssay(a, "log2")  
transformAssay(a, "vsn")
```

upsetCategory

UpSet plot to display measures values across sample types

Description

The function `upsetCategory` displays the frequency of measured values per feature with respect to class/sample type to assess difference in occurrences. Internally, the measured values per sample are obtained via the `measuredCategory` function: this function will access the number of measured/missing values per category and feature. From this, a binary `tbl` will be created specifying if the feature is present/missing, which will be given to the `upset` function from the `UpSetR` package.

Usage

```
upsetCategory(se, category = colnames(colData(se)), measured = TRUE)
```

Arguments

<code>se</code>	SummarizedExperiment, containing the intensity values in <code>assay(se)</code> , missing values are encoded by NA
<code>category</code>	character, corresponding to a column in <code>colData(se)</code>
<code>measured</code>	logical, should the measured values (<code>measured = TRUE</code>) or missing values (<code>measured = FALSE</code>) be taken

Details

Presence is defined by a feature being measured in at least one sample of a set.

Absence is defined by a feature with only missing values (i.e. no measured values) of a set.

Value

upset plot

Examples

```
## create se
a <- matrix(seq_len(100), nrow = 10, ncol = 10,
            dimnames = list(seq_len(10), paste("sample", seq_len(10))))
a[c(1, 5, 8), seq_len(5)] <- NA
set.seed(1)
a <- a + rnorm(100)
cD <- data.frame(name = colnames(a), type = c(rep("1", 5), rep("2", 5)))
rD <- data.frame(spectra = rownames(a))
se <- SummarizedExperiment::SummarizedExperiment(assay = a,
                                                rowData = rD, colData = cD)

upsetCategory(se, category = "type")
```

volcanoPlot

*Volcano plot of fold changes/differences against p-values***Description**

The function `ComplexHeatmap` creates a volcano plot. On the y-axis the $-\log_{10}(\text{p-values})$ are displayed, while on the x-axis the fold changes/differences are displayed. The output of the function differs depending on the `type` parameter. For `type == "ttest"`, the fold changes are plotted; for `type == "proDA"`, the differences are plotted.

Usage

```
volcanoPlot(df, type = c("ttest", "proDA"))
```

Arguments

<code>df</code>	data.frame as received from <code>topTable (ttest)</code> or <code>test_diff (proDA)</code>
<code>type</code>	character

Details

Internal use in `shinyQC`.

Value

`plotly`

Examples

```
## create se
a <- matrix(seq_len(100), nrow = 10, ncol = 10,
            dimnames = list(seq_len(10), paste("sample", seq_len(10))))
a[c(1, 5, 8), seq_len(5)] <- NA
set.seed(1)
a <- a + rnorm(100)
a_i <- imputeAssay(a, method = "MinDet")
cD <- data.frame(sample = colnames(a),
                type = c(rep("1", 5), rep("2", 5)))
rD <- data.frame(spectra = rownames(a))
se <- SummarizedExperiment::SummarizedExperiment(assay = a,
                                                rowData = rD, colData = cD)
se_i <- SummarizedExperiment::SummarizedExperiment(assay = a_i,
                                                  rowData = rD, colData = cD)

## create model and contrast matrix
modelMatrix_expr <- stats::formula("~ 0 + type")
contrast_expr <- "type1-type2"
modelMatrix <- model.matrix(modelMatrix_expr, data = colData(se))
contrastMatrix <- limma::makeContrasts(contrasts = contrast_expr,
```

```
                                levels = modelMatrix)

## ttest
fit <- limma::lmFit(a_i, design = modelMatrix)
fit <- limma::contrasts.fit(fit, contrastMatrix)
fit <- limma::eBayes(fit, trend = TRUE)
df_ttest <- limma::topTable(fit, n = Inf, adjust = "fdr", p = 0.05)
df_ttest <- cbind(name = rownames(df_ttest), df_ttest)

## plot
volcanoPlot(df_ttest, type = "ttest")

## proDA

fit <- proDA::proDA(a, design = modelMatrix)
df_proDA <- proDA::test_diff(fit = fit, contrast = contrast_expr,
                             sort_by = "adj_pval")

## plot
volcanoPlot(df_proDA, type = "proDA")
```

Index

barplotSamplesMeasuredMissing, 3
batchCorrectionAssay, 4

createBoxplot, 5
createDfFeature, 6
cv, 7
cvFeaturePlot, 8

dimensionReduction, 9
dimensionReductionPlot, 10
distSample, 11
distShiny, 12
driftPlot, 13

ECDF, 14
explVar, 15
extractComb, 16

featurePlot, 17

hist_sample, 20
hist_sample_num, 20
histFeature, 18
histFeatureCategory, 19
hoeffDPlot, 21
hoeffDValues, 22

imputeAssay, 23

MPlot, 25
MAvalues, 26
measuredCategory, 27
mosaic, 28

normalizeAssay, 29

permuteExplVar, 30
plotCV, 31
plotPCALoadings, 32
plotPCAVar, 33
plotPCAVarPvalue, 34

samplesMeasuredMissing, 35
shinyQC, 36
sumDistSample, 37

tblPCALoadings, 38
transformAssay, 39

upsetCategory, 40

volcanoPlot, 41