

# Package ‘MuData’

May 20, 2024

**Title** Serialization for MultiAssayExperiment Objects

**Version** 1.8.0

**Description** Save MultiAssayExperiments to h5mu files supported by muon and mudata.  
Muon is a Python framework for multimodal omics data analysis. It uses an HDF5-based format for data storage.

**URL** <https://github.com/ilia-kats/MuData>

**BugReports** <https://github.com/ilia-kats/MuData/issues>

**Imports** methods, stats, MultiAssayExperiment, SingleCellExperiment,  
SummarizedExperiment, DelayedArray

**Depends** Matrix, S4Vectors, rhdf5

**Suggests** HDF5Array, rmarkdown, knitr, fs, testthat, BiocStyle, covr,  
SingleCellMultiModal, CiteFuse, scater

**VignetteBuilder** knitr

**License** GPL-3

**Encoding** UTF-8

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.1.2

**Config/testthat/edition** 3

**biocViews** DataImport

**git\_url** <https://git.bioconductor.org/packages/MuData>

**git\_branch** RELEASE\_3\_19

**git\_last\_commit** 1c442c2

**git\_last\_commit\_date** 2024-04-30

**Repository** Bioconductor 3.19

**Date/Publication** 2024-05-19

**Author** Danila Bredikhin [aut, cre] (<<https://orcid.org/0000-0001-8089-6983>>),  
Ilia Kats [aut] (<<https://orcid.org/0000-0001-5220-5671>>)

**Maintainer** Danila Bredikhin <[danila.bredikhin@embl.de](mailto:danila.bredikhin@embl.de)>

## Contents

|                     |          |
|---------------------|----------|
| readH5AD . . . . .  | 2        |
| readH5MU . . . . .  | 3        |
| writeH5AD . . . . . | 3        |
| writeH5MU . . . . . | 4        |
| <b>Index</b>        | <b>5</b> |

---

|          |  |
|----------|--|
| readH5AD | <i>Read an .h5ad file and create a <a href="#">SingleCellExperiment</a>.</i> |
|----------|--|

---

## Description

In file-backed mode, the main X matrix is not read into memory, but references the HDF5 file and its required parts are read on demand. This requires the HDF5Array package to be installed.

## Usage

```
readH5AD(file, backed = FALSE)
```

## Arguments

|        |                                  |
|--------|----------------------------------|
| file   | Path to the .h5ad file.          |
| backed | Whether to use file-backed mode. |

## Value

A [SingleCellExperiment](#).

## Examples

```
data(miniACC, package="MultiAssayExperiment")
writeH5AD(miniACC[[1]], "miniacc.h5ad")
sce <- readH5AD("miniacc.h5ad")
```

---

|          |  |
|----------|--|
| readH5MU | <i>Read an .h5mu file and create a <a href="#">MultiAssayExperiment</a>.</i> |
|----------|--|

---

### Description

In file-backed mode, the main X matrices are not read into memory, but reference the HDF5 file and their required parts are read on demand. This requires the HDF5Array package to be installed.

### Usage

```
readH5MU(file, backed = FALSE)
```

### Arguments

|        |                                  |
|--------|----------------------------------|
| file   | Path to the .h5mu file.          |
| backed | Whether to use file-backed mode. |

### Value

A [MultiAssayExperiment](#)

### Examples

```
data(miniACC, package="MultiAssayExperiment")
writeH5MU(miniACC, "miniacc.h5mu")
mae <- readH5MU("miniacc.h5mu")
```

---

|           |   |
|-----------|---|
| writeH5AD | <i>Save an experiment to an .h5ad file.</i> |
|-----------|---|

---

### Description

Note that NA values are not supported by HDF5, and therefore by h5ad. The behavior of this function if NAs are present is undefined.

### Usage

```
writeH5AD(object, file, overwrite)
```

### Arguments

|           |                              |
|-----------|------------------------------|
| object    | The object to save.          |
| file      | Name of the file to save to. |
| overwrite | Currently unused.            |

**Value**

NULL, invisibly

**Examples**

```
data(miniACC, package="MultiAssayExperiment")
writeH5AD(miniACC[[1]], "miniacc.h5ad")
```

---

writeH5MU

*Save a [MultiAssayExperiment](#) to an .h5mu file.*

---

**Description**

Note that NA values are not supported by HDF5, and therefore by h5mu. The behavior of this function if NAs are present is undefined.

**Usage**

```
writeH5MU(object, file, overwrite)
```

**Arguments**

|           |  |
|-----------|--|
| object    | A <a href="#">MultiAssayExperiment</a> . |
| file      | Name of the file to save to.             |
| overwrite | Currently unused.                        |

**Value**

NULL, invisibly

**Examples**

```
data(miniACC, package="MultiAssayExperiment")
writeH5MU(miniACC, "miniacc.h5mu")
```

# Index

MultiAssayExperiment, [3](#), [4](#)

readH5AD, [2](#)

readH5MU, [3](#)

SingleCellExperiment, [2](#)

writeH5AD, [3](#)

writeH5MU, [4](#)