

Package ‘cummeRbund’

May 19, 2024

Title Analysis, exploration, manipulation, and visualization of Cufflinks high-throughput sequencing data.

Version 2.46.0

Date 2013-04-22

Author L. Goff, C. Trapnell, D. Kelley

Description Allows for persistent storage, access, exploration, and manipulation of Cufflinks high-throughput sequencing data. In addition, provides numerous plotting functions for commonly used visualizations.

Imports methods, plyr, BiocGenerics, S4Vectors ($\geq 0.9.25$), Biobase

Depends R ($\geq 2.7.0$), BiocGenerics ($\geq 0.3.2$), RSQLite, ggplot2, reshape2, fastcluster, rtracklayer, Gviz

Suggests cluster, plyr, NMFN, stringr, GenomicFeatures, GenomicRanges, rjson

Maintainer Loyal A. Goff <lgoff@csail.mit.edu>

License Artistic-2.0

Collate AllGenerics.R AllClasses.R database-setup.R methods-CuffSet.R methods-CuffData.R methods-CuffDist.R methods-CuffGeneSet.R methods-CuffFeatureSet.R methods-CuffGene.R methods-CuffFeature.R tools.R

LazyLoad yes

biocViews HighThroughputSequencing, HighThroughputSequencingData, RNAseq, RNAseqData, GeneExpression, DifferentialExpression, Infrastructure, DataImport, DataRepresentation, Visualization, Bioinformatics, Clustering, MultipleComparisons, QualityControl

git_url <https://git.bioconductor.org/packages/cummeRbund>

git_branch RELEASE_3_19

git_last_commit 43e9e24

git_last_commit_date 2024-04-30

Repository Bioconductor 3.19

Date/Publication 2024-05-19

Contents

cummeRbund-package	3
addFeatures	5
count-methods	7
countMatrix	8
csBoxplot	9
csCluster	10
csClusterPlot	11
csDendro	12
csDensity	13
csDistHeat	14
csHeatmap	15
csScatter	17
csSpecificity	18
csVolcano	19
CuffData-class	20
CuffDist-class	21
CuffFeature-class	22
CuffFeatureSet-class	24
CuffGene-class	25
CuffGeneSet-class	27
CuffSet-class	28
diffData	30
Dimensionality Reduction	31
dispersionPlot	32
distValues	33
Exploratory Analysis	34
expressionBarplot	35
expressionPlot	37
featureNames	38
features	39
findGene	40
findSimilar	41
fpkm-methods	42
fpkmMatrix	43
getFeatures	44
getGene	45
getGeneId	46
getGenes	47
getLevels	48
getRepLevels	49
getSig	50
getSigTable	51
JSdist	52
JSdistFromP	53
JSdistVec	54
makeprobs	55

makeprobsvec	56
MAplot	57
PINK1	58
QCplots	59
readCufflinks	60
repFpkm-methods	62
replicates	63
runInfo	64
sampleGeneSet	65
sampleIDs	65
samples	66
shannon.entropy	67
sigMatrix	68

Index 70

cummeRbund-package	<i>cummeRbund: The finishing touch on your Tuxedo workflow. Analysis, manipulation, and visualization of Cufflinks HTS data. ~ package title ~</i>
--------------------	--

Description

Allows for persistent storage, access, and manipulation of Cufflinks high-throughput sequencing data. In addition, provides numerous plotting functions for commonly used visualizations. ~ A concise (1-5 lines) description of the package ~

Details

Package: cummeRbund
 Version: 0.1.3
 Suggests:
 Depends: R (>= 2.7.0), RSQLite, reshape2, ggplot2, methods
 License: MIT License
 Collate: AllGenerics.R AllClasses.R database-setup.R methods-CuffSet.R methods-CuffData.R methods-CuffDist.R met
 LazyLoad: yes
 biocViews: HighThroughputSequencing, HighThroughputSequencingData, RNAseq, RNAseqData, GeneExpression, Differ
 Packaged: 2011-08-05 18:03:50 UTC; lgoff
 Built: R 2.12.1; ; 2011-08-05 18:03:57 UTC; unix

Index:

CuffData-class	Class "CuffData"
CuffDist-class	Class "CuffDist"
CuffFeature-class	Class "CuffFeature"
CuffFeatureSet-class	Class "CuffFeatureSet"

```

CuffGene-class          Class "CuffGene"
CuffGeneSet-class      Class "CuffGeneSet"
CuffSet-class          Class "CuffSet"
JSdist                 Jensen-Shannon distance on columns
addFeatures            addFeatures
addFeatures-methods    ~~ Methods for Function addFeatures in Package
                        'cummeRbund' ~~
createdB               createdB
csBoxplot              csBoxplot
csBoxplot-methods     ~~ Methods for Function csBoxplot in Package
                        'cummeRbund' ~~
csDensity              Density plot of CuffData
csDensity-methods     ~~ Methods for Function csDensity in Package
                        'cummeRbund' ~~
csHeatmap              csHeatmap
csHeatmap-methods     ~~ Methods for Function csHeatmap in Package
                        'cummeRbund' ~~
csScatter              Scatter Plot
csScatter-methods     ~~ Methods for Function csScatter in Package
                        'cummeRbund' ~~
csVolcano              Volcano Plot
csVolcano-methods     ~~ Methods for Function csVolcano in Package
                        'cummeRbund' ~~
cummeRbund-package     cummeRbund: The finishing touch on your Tuxedo
                        workflow. Analysis, manipulation, and
                        visualization of Cufflinks HTS data.
diffData               Differential comparison data
diffData-methods      ~~ Methods for Function diffData in Package
                        'cummeRbund' ~~
dim-methods           ~~ Methods for Function dim in Package 'base'
                        ~~
expressionBarplot      Barplot
expressionBarplot-methods
                        ~~ Methods for Function expressionBarplot in
                        Package 'cummeRbund' ~~
expressionPlot         Expression Plot
expressionPlot-methods
                        ~~ Methods for Function expressionPlot in
                        Package 'cummeRbund' ~~
featureNames           Feature names
featureNames-methods  ~~ Methods for Function featureNames in Package
                        'cummeRbund' ~~
features               Features
features-methods      ~~ Methods for Function features in Package
                        'cummeRbund' ~~
fpkm                   Retrieve FPKM values
fpkm-methods          ~~ Methods for Function fpkm in Package
                        'cummeRbund' ~~

```

```

fpkmMatrix          Retrieve FPKM values as matrix
fpkmMatrix-methods  ~~ Methods for Function fpkmMatrix in Package
                    'cummeRbund' ~~

getGene             getGene
getGene-methods    ~~ Methods for Function getGene in Package
                    'cummeRbund' ~~

getGenes            getGenes
getGenes-methods   ~~ Methods for Function getGenes in Package
                    'cummeRbund' ~~

getLevels           getLevels
getLevels-methods  ~~ Methods for Function getLevels in Package
                    'cummeRbund' ~~

length-methods     ~~ Methods for Function length in Package
                    'base' ~~

makeprobs           Transform a matrix into probabilities by
                    columns

readCufflinks       readCufflinks

samples             Get sample list from CuffData object
samples-methods    ~~ Methods for Function samples in Package
                    'cummeRbund' ~~

shannon.entropy     Shannon entropy

```

Further information is available in the following vignettes:

cummeRbund-manual An R package for visualization and analysis of Cufflinks high-throughput sequencing data (source, pdf)

~~ An overview of how to use the package, including the most important ~~ functions ~~

Author(s)

L. Goff, C. Trapnell

Maintainer: Loyal A. Goff <lgoff@csail.mit.edu>

References

~~ Literature or other references for background information ~~

addFeatures

addFeatures

Description

Adds a data.frame of features to a the SQLite backend database.

Usage

```
## S4 method for signature 'CuffSet'  
addFeatures(object, features, level="genes", ...)
```

Arguments

object	An object of class ('CuffSet' or 'CuffData')
features	A data.frame of features to add. 1st column MUST contain ids (ie. gene_id for 'gene' features, isoform_id for 'isoform' features, etc)
level	One of c('genes','isoforms','TSS','CDS') to indicate which type of features you are being added, and to what data-level.
...	Additional arguments.

Details

None

Value

None

Note

None

Author(s)

Loyal A. Goff

References

None

Examples

```
#None yet.
```

`count-methods`*Retrieve count values (raw and normalized)*

Description

Returns a data.frame from @count slot

Details

Returns a data.frame of count values.

Value

A data.frame of count-level values for a set of features.

Methods

```
signature(object = "CuffData")
```

```
signature(object = "CuffFeature")
```

```
signature(object = "CuffFeatureSet")
```

Note

None

Author(s)

Loyal A. Goff

References

None

Examples

```
data(sampleData)  
count(PINK1)
```

countMatrix *countMatrix*

Description

Retrieve count values as gene by condition matrix

Usage

```
## S4 method for signature 'CuffData'  
countMatrix(object,fullnames=FALSE,sampleIdList)  
## S4 method for signature 'CuffData'  
repCountMatrix(object,fullnames=FALSE,repIdList)
```

Arguments

object	An object of class ('CuffData','CuffFeatureSet','CuffGeneSet','CuffGene',or 'Cuff-Feature')
fullnames	A logical value whether or not to concatenate gene_short_name and tracking_id values (easier to read labels)
sampleIdList	A vector of sample names to subset the resulting matrix.
repIdList	A vector of replicate names to subset the resulting replicate matrix.

Details

None.

Value

A feature x condition matrix of count values.

Note

None

Author(s)

Loyal A. Goff

References

None.

Examples

```
data(sampleData)  
countMatrix(sampleGeneSet)  
repCountMatrix(sampleGeneSet)
```

csBoxplot	<i>csBoxplot</i>
-----------	------------------

Description

Creates a ggplot2 plot object with a geom_box layer displaying summary statistics for FPKM values across samples (x).

Usage

```
## S4 method for signature 'CuffData'  
csBoxplot(object, logMode=TRUE, pseudocount=0.0001, replicates=FALSE,...)
```

Arguments

object	An object of class CuffData.
logMode	A logical argument to log10 -transform FPKM values.
pseudocount	Value added to FPKM to avoid log-transform issues.
replicates	A logical value whether or not to plot individual replicates or aggregate condition values.
...	Additional arguments to csBoxplot

Details

None

Value

A ggplot2 plot object with a geom_box layer.

Note

None

Author(s)

Loyal A. Goff

References

None

Examples

```
a<-readCufflinks(system.file("extdata", package="cummeRbund")) #Read cufflinks data and create CuffSet object  
genes<-a@genes #CuffData object for all genes  
csBoxplot(genes)
```

 csCluster

csCluster

Description

Returns a ggplot2 plot object with geom_line layer plotting FPKM values over conditions faceted by k-means clustering clusters. (Euclidean). This is very crude at this point. This does not return any of the clustering information directly, but if you want it, you can retrieve it from the ggplot object returned.

Usage

```
## S4 method for signature 'CuffFeatureSet'
csCluster(object,k,logMode=T,method = "none",pseudocount=1,...)
```

Arguments

object	An object of class CuffFeatureSet.
k	Number of pre-defined clusters to attempt to find.
logMode	A logical value whether or not to log-transform the FPKM values prior to clustering.
method	Distance function to use when computing cluster solution. Default "none" will use the Jensen-Shannon distance (JSdist). Provide a function that returns a dist object on rows.
pseudocount	Value added to FPKM to avoid log-transform issues.
...	Additional arguments to pam.

Details

Uses 'kmeans' function.

Author(s)

Loyal A. Goff

Source

None

References

None.

Examples

```
data(sampleData)
csCluster(sampleGeneSet,4)
```

csClusterPlot	<i>csClusterPlot</i>
---------------	----------------------

Description

Replaces the default plotting behavior of the old csCluster. Takes as an argument the output of csCluster and plots expression profiles of features facet by cluster.

Usage

```
csClusterPlot(clustering, pseudocount=1.0, logMode=FALSE, drawSummary=TRUE, sumFun=mean_cl_boot)
```

Arguments

clustering	The output of csCluster. (Must be the output of csCluster. Only this data format contains the necessary information for csClusterPlot.)
pseudocount	Value added to FPKM to avoid log transformation issues.
logMode	Logical argument whether to plot FPKM with log axis (Y-axis).
drawSummary	Logical value whether or not to draw a summary line for each cluster (by default this is the cluster mean)
sumFun	Summary function used to by drawSummary (default: mean_cl_boot)

Details

This replaces the default plotting behavior of the old csCluster() method. This was necessary so as to preserve the cluster information obtained by csCluster in a stable format. The output of csClusterPlot is a ggplot2 object of expressionProfiles faceted by cluster ID.

Value

A ggplot2 object of expressionProfiles faceted by cluster ID.

Note

None.

Author(s)

Loyal A. Goff

References

None.

Examples

```
data(sampleData)
myClustering<-csCluster(sampleGeneSet,k=4)
csClusterPlot(myClustering)
```

csDendro

csDendro

Description

Creates a grid graphics plot of a dendrogram of Jensen-Shannon distances between conditions of a CuffFeatureSet or CuffGeneSet object.

Usage

```
## S4 method for signature 'CuffFeatureSet'
csDendro(object,logMode=T,pseudocount=1,replicates=FALSE)
## S4 method for signature 'CuffData'
csDendro(object,logMode=T,pseudocount=1,replicates=FALSE,...)
```

Arguments

object	An object of class 'CuffFeatureSet' or 'CuffGeneSet'
logMode	A logical argument to log10-transform FPKM values prior to plotting.
pseudocount	Value to be added to FPKM for appropriate log transformation and clustering. (Avoids zero-based errors)
replicates	A logical value whether or not to plot individual replicates or aggregate condition values.
...	Additional arguments to csHeatmap

Details

None

Value

Returns a dendrogram object and plots that object by default.

Note

None

Author(s)

Loyal A. Goff and Cole Trapnell

References

None.

Examples

```
data(sampleData)
csDendro(sampleGeneSet)
```

csDensity	<i>Density plot of CuffData</i>
-----------	---------------------------------

Description

Creates a smoothed density plot, by sample, for log₁₀ FPKM values from a cuffdiff run.

Usage

```
## S4 method for signature 'CuffData'
csDensity(object, logMode=TRUE, pseudocount=0, labels, features=FALSE, replicates=FALSE,...)
## S4 method for signature 'CuffFeatureSet'
csDensity(object, logMode=TRUE, pseudocount=0, labels, features=FALSE, replicates=FALSE,...)
```

Arguments

object	An object of class CuffData.
logMode	A logical value of whether or not to log ₁₀ -transform FPKM values. By default this is TRUE.
pseudocount	Pseudocount value added to FPKM to avoid errors in log-transformation of true zero values.
labels	A list of tracking_id values or gene_short_name values used for 'callout' points on the density plot for reference. (Not implemented yet).
features	Will include all fields from 'features' slot in returned ggplot object. Useful for further manipulations of plot object using feature-level attributes (e.g. gene_type, class_code, etc)
replicates	A logical value whether or not to plot individual replicates or aggregate condition values.
...	Additional arguments

Details

Creates a density plot, by sample, for log₁₀-transformed FPKM values from a cuffdiff run.

Value

A ggplot2 plot object

Note

None

Author(s)

Loyal A. Goff

References

None

Examples

```
a<-readCufflinks(system.file("extdata", package="cummeRbund")) #Create CuffSet object from sample data
genes<-a@genes #Create CuffData object for all 'genes'
d<-csDensity(genes) #Create csDensity plot
d #Render plot
```

csDistHeat

csDistHeat

Description

Creates a ggplot plot object with a geom_tile layer of JS Distance values between samples or genes.

Usage

```
## S4 method for signature 'CuffFeatureSet'
csDistHeat(object, replicates=F, samples.not.genes=T,
  logMode=T, pseudocount=1.0,
  heatscale=c(low='lightyellow',mid='orange',high='darkred'),
  heatMidpoint=NULL, ...)
```

Arguments

object	An object of class 'CuffFeatureSet' or 'CuffGeneSet'
replicates	A logical argument whether or not to use individual replicate FPKM values as opposed to condition FPKM estimates. (default: FALSE)
samples.not.genes	Compute distances between samples rather than genes. If False, compute distances between genes.
logMode	A logical argument to log10-transform FPKM values prior to plotting.
pseudocount	Value to be added to FPKM for appropriate log transformation and clustering. (Avoids zero-based errors)
heatscale	A list with min length=2, max length=3 that describe the the color scale.
heatMidpoint	Value for midpoint of color scale.
...	Additional arguments to csHeatmap

Details

None

Value

A ggplot2 plot object with a geom_tile layer to display distance between samples or genes.

Note

None

Author(s)

Loyal A. Goff, Cole Trapnell, and David Kelley

References

None

Examples

```
data(sampleData)
csDistHeat(sampleGeneSet)
```

csHeatmap

csHeatmap

Description

Creates a ggplot plot object with a geom_tile layer of FPKM values per feature and sample.

Usage

```
## S4 method for signature 'CuffFeatureSet'
csHeatmap(object, rescaling='none', clustering='none', labCol=T, labRow=T, logMode=T, pseudocount=1.0,
border=FALSE, heatscale= c(low='lightyellow',mid='orange',high='darkred'), heatMidpoint=NULL, fullnames=T)
## S4 method for signature 'CuffFeatureSet'
csFoldChangeHeatmap(object, control_condition, replicate_num=NULL, clustering='none', labCol=T, labRow=T,
border=FALSE, heatscale=c(low='steelblue',mid='white',high='tomato'), heatMidpoint=0,fullnames=T,replicate_num=NULL)
```

Arguments

object	An object of class 'CuffFeatureSet' or 'CuffGeneSet'
control_condition	A character argument indicating which condition should be used as the denominator for fold change. (e.g. "Day0", "Control", etc)
replicate_num	If replicates == TRUE, you must specify both a control condition and a replicate number to use as the denominator.

rescaling	Rescaling can either be 'row' or 'column' OR you can pass rescale a function that operates on a matrix to do your own rescaling. Default is 'none'.
clustering	Clustering can either be 'row', 'column', 'none', or 'both', in which case the appropriate indices are re-ordered based on the pairwise Jensen-Shannon distance of FPKM values.
labCol	A logical argument to display column labels.
labRow	A logical argument to display row labels.
logMode	A logical argument to log10-transform FPKM values prior to plotting.
pseudocount	Value to be added to FPKM for appropriate log transformation and clustering. (Avoids zero-based errors)
border	A logical argument to draw border around plot.
heatscale	A list with min length=2, max length=3 that detail the low,mid,and high colors to build the color scale.
heatMidpoint	Value for midpoint of color scale.
fullnames	A logical value whether to use 'fullnames' (concatenated gene_short_name and gene_id) for rows in heatmap. Default [TRUE].
replicates	A logical value whether or not to plot individual replicates or aggregate condition values.
method	Function to be used for clustering. Default is JS-distance. You can pass your own function to this argument as long as the output is an instance of the 'dist' class and is applied to the rows of the input matrix.
heatRange	Numerical argument for upper bound on log fold change to be visualized.
...	Additional arguments to csHeatmap

Details

None

Value

A ggplot2 plot object with a geom_tile layer to display FPKM values by sample (x) and feature (y)

Note

None

Author(s)

Loyal A. Goff and Cole Trapnell

References

None.

Examples

```
data(sampleData)
csHeatmap(sampleGeneSet)
```


csScatter

*Scatter Plot***Description**

A scatter plot comparing the FPKM values from two samples in a cuffdiff run.

Usage

```
## S4 method for signature 'CuffData'
csScatter(object, x, y, logMode=TRUE, pseudocount=1.0, labels, smooth=FALSE, colorByStatus = FALSE, drawRug=TRUE)
## S4 method for signature 'CuffData'
csScatterMatrix(object, replicates=FALSE, logMode=TRUE, pseudocount=1.0, hexbin=FALSE, useCounts=FALSE, ...)
```

Arguments

object	An object of class ('CuffData', 'CuffFeatureSet')
x	Sample name for x axis
y	Sample name for y axis
logMode	Logical argument to render axes on log10 scale (default: T)
replicates	Logical argument whether or not to draw individual replicate values instead of condition values. (default: T)
pseudocount	Value to add to zero FPKM values for log transformation (default: 0.0001)
smooth	Logical argument to add a smooth-fit regression line
labels	A list of tracking_ids or gene_short_names that will be 'callout' points in the plot for reference. Useful for finding genes of interest in the field. Not implemented yet.
colorByStatus	A logical argument whether or not to color the points by 'significant' Y or N. [Default = FALSE]
drawRug	A logical argument whether or not to draw the rug for x and y axes [Default = TRUE]
hexbin	Logical value whether or not to visualize overplotting with hexbin.
useCounts	Uses normalized counts instead of FPKM.
...	Additional arguments to csScatter

Details

None

Value

ggplot object with geom_point and geom_rug layers

Note

None

Author(s)

Loyal A. Goff

References

None

Examples

```
a<-readCufflinks(system.file("extdata", package="cummeRbund")) #Create CuffSet object from sample data
genes<-a@genes #Create CuffData object for all genes
s<-csScatter(genes,'hESC','Fibroblasts',smooth=TRUE) #Create plot object
s #render plot object
```

csSpecificity

csSpecificity

Description

Returns a matrix of 'Specificity scores' (S) defined as $1 - \text{JSD}(p_g, q_i)$ where p_g is the Log10+1 expression profile of a gene g across all conditions j , collapsed into a probability distribution, and q_i is the unit vector of 'perfect expression' in a given condition i .

Usage

```
## S4 method for signature 'CuffFeatureSet'
csSpecificity(object,logMode=T,pseudocount=1,relative=FALSE,...)
## S4 method for signature 'CuffData'
csSpecificity(object,logMode=T,pseudocount=1,relative=FALSE,...)
```

Arguments

object	An object of class CuffFeatureSet, CuffGeneSet, or CuffData.
logMode	A logical argument to log10-transform FPKM values prior to plotting.
pseudocount	Value to be added to FPKM for appropriate log transformation and clustering. (Avoids zero-based errors)
relative	A logical argument that when TRUE, will scale the S values from 0-1 by dividing by max(S)
...	Additional arguments to fpkmMatrix.

Details

None

Author(s)

Loyal A. Goff

Source

None

References

None.

Examples

```
data(sampleData)
csSpecificity(sampleGeneSet)
```

csVolcano

Volcano Plot

Description

Creates a volcano plot of log fold change in expression vs $-\log(\text{pval})$ for a pair of samples (x,y)

Usage

```
## S4 method for signature 'CuffData'
csVolcano(object, x, y, alpha=0.05, showSignificant=TRUE, features=FALSE, xlimits = c(-20, 20), ...)
## S4 method for signature 'CuffData'
csVolcanoMatrix(object, alpha=0.05, xlimits=c(-20, 20), mapping=aes(), ...)
```

Arguments

object	An object of class CuffData, CuffFeatureSet, or CuffGeneSet
x	Sample name from 'samples' table for comparison
y	Sample name from 'samples' table for comparison
alpha	Provide an alpha cutoff for visualizing significant genes
showSignificant	A logical value whether or not to distinguish between significant features or not (by color).
features	Will include all fields from 'features' slot in returned ggplot object. Useful for further manipulations of plot object using feature-level attributes (e.g. gene_type, class_code, etc)
xlimits	Set boundaries for x limits to avoid infinity plotting errors. [Default c(-20,20)]
mapping	Passthrough argument for ggplot aesthetics. Can be ignored completely.
...	Additional arguments

Details

This creates a 'volcano' plot of fold change vs. significance for a pairwise comparison of genes or features across two different samples.

Value

A ggplot2 plot object

Note

None

Author(s)

Loyal A. Goff

References

None.

Examples

```
a<-readCufflinks(system.file("extdata", package="cummeRbund")) #Create CuffSet object
genes<-a@genes #Create cuffData object for all genes
v<-csVolcano(genes,"hESC","Fibroblasts") # Volcano plot of all genes for conditions x='hESC' and y='Fibroblast'
v #print plot
```

CuffData-class

Class "CuffData"

Description

A 'pointer' class for all information (FPKM, annotation, differential expression) for a given feature type (genes, isoforms, TSS, CDS). The methods for this function communicate directly with the SQL backend to present data to the user.

Objects from the Class

Objects can be created by calls of the form `new("CuffData", DB, tables, filters, type, idField, ...)`.

Slots

DB: Object of class "SQLiteConnection" ~~
 tables: Object of class "list" ~~
 filters: Object of class "list" ~~
 type: Object of class "character" ~~
 idField: Object of class "character" ~~

Methods

- dim** signature(x = "CuffData"): ...
- getFeatures** signature(object = "CuffData"): ...
- DB** signature(object = "CuffData"): Accessor for @DB slot
- diffTable** signature(object = "CuffData"): Create a Full table (wide format) of differential expression information for all pairwise comparisons
- makeRnk** signature(object = "CuffData"): Internal method to create .rnk file. Should not be called directly
- annotation** signature(object="CuffData"): Access annotation data

Note

None

Author(s)

Loyal A. Goff

References

None

See Also

None

Examples

```
showClass("CuffData")
```

CuffDist-class

Class "CuffDist"

Description

A 'pointer' class to information relative to the distribution-level tests (promoters, splicing, and relative CDS usage)

Objects from the Class

Objects can be created by calls of the form `new("CuffDist", DB, table, type, idField, ...)`.

Slots

DB: Object of class "SQLiteConnection" ~~
 table: Object of class "character" ~~
 type: Object of class "character" ~~
 idField: Object of class "character" ~~

Methods

dim signature(x = "CuffDist"): ...
samples signature(x = "CuffDist"): ...
DB signature(object = "CuffDist"): Accessor for @DB slot

Note

None

Author(s)

Loyal A. Goff

References

None

See Also

None

Examples

```
showClass("CuffDist")
```

CuffFeature-class	<i>Class "CuffFeature"</i>
-------------------	----------------------------

Description

A 'data' container class for all FPKM, annotation, and differential expression data for a single feature (gene, isoform, TSS, or CDS).

Objects from the Class

Objects can be created by calls of the form `new("CuffFeature", annotation, fpkm, diff, ...)`.

Slots

annotation: Object of class "data.frame" ~~
fpkm: Object of class "data.frame" ~~
diff: Object of class "data.frame" ~~
repFpkm: Object of class "data.frame" ~~
count: Object of class "data.frame" ~~
genome: Object of class "character" ~~

Methods

fpkmMatrix signature(object="CuffFeature"): ...
repFpkmMatrix signature(object = "CuffFeature"): ...
length signature(x = "CuffFeature"): ...

Accessors

annotation signature(object="CuffFeature"): Access @annotation slot
diffData signature(object="CuffFeature"): Access @diff slot
samples signature(object="CuffFeature"): Get vector of samples

Note

'CuffGene' is a superclass of 'CuffFeature' that links gene information for a given gene with all isoform-, TSS-, and CDS-level data for the given gene.

Author(s)

Loyal A. Goff

References

None

See Also

[CuffGene](#)

Examples

```
showClass("CuffFeature")
```

CuffFeatureSet-class *Class "CuffFeatureSet"*

Description

A 'data' container class for all FPKM, annotation, and differential expression data for a set of features (genes, isoforms, TSS, CDS).

Objects from the Class

Objects can be created by calls of the form `new("CuffFeatureSet", annotation, fpkm, diff, ...)`.

Slots

annotation: Object of class "data.frame" ~~
fpkm: Object of class "data.frame" ~~
diff: Object of class "data.frame" ~~
repFpkm: Object of class "data.frame" ~~
count: Object of class "data.frame" ~~
genome: Object of class "character" ~~

Methods

diffData signature(object = "CuffFeatureSet"): ...
featureNames signature(object = "CuffFeatureSet"): ...
features signature(object = "CuffFeatureSet"): ...
fpkmMatrix signature(object = "CuffFeatureSet"): ...
repFpkmMatrix signature(object = "CuffFeatureSet"): ...
countMatrix signature(object = "CuffFeatureSet"): ...
samples signature(object = "CuffFeatureSet"): ...
length signature(object = "CuffFeatureSet"): ...

Accessors

annotation signature(object="CuffFeatureSet"): Access @annotation slot

Note

None.

Author(s)

Loyal A. Goff

References

None.

See Also

[CuffGeneSet](#)

Examples

```
showClass("CuffFeatureSet")
```

CuffGene-class	<i>Class "CuffGene"</i>
----------------	-------------------------

Description

A 'data' container class for all FPKM, annotation, and differential expression Data (as well as for all linked features) for a given gene.

Objects from the Class

Objects can be created by calls of the form `new("CuffGene", id, isoforms, TSS, CDS, promoters, splicing, relCDS, annotation, fpkm, diff, ...)`.

Slots

id: Object of class "character" ~~
 isoforms: Object of class "CuffFeature" ~~
 TSS: Object of class "CuffFeature" ~~
 CDS: Object of class "CuffFeature" ~~
 promoters: Object of class "CuffFeature" ~~
 relCDS: Object of class "CuffFeature" ~~
 splicing: Object of class "CuffFeature" ~~
 annotation: Object of class "data.frame" ~~
 genome: Object of class "character" ~~
 fpkm: Object of class "data.frame" ~~
 diff: Object of class "data.frame" ~~
 features: Object of class "data.frame" ~~

Extends

Class "[CuffFeature](#)", directly.

Methods

- length** signature(object="CuffFeature"): Part of length validation (internal use only)
- makeGeneRegionTrack** signature(object="CuffFeature"): Creates a GeneRegionTrack object (see package Gviz) from a CuffGene object.
- genePlot** signature(object="CuffFeature"): Internal use only.
- csPie** signature(object="CuffGene"): Allows for visualization of relative isoform proportion as a pie chart by condition (or optionally as stacked bar charts by adding + coord_cartesian())

Accessors

- genes** signature(object = "CuffGene"): Access @genes slot
- isoforms** signature(object = "CuffGene"): Access @isoforms slot
- TSS** signature(object = "CuffGene"): Access @TSS slot
- CDS** signature(object = "CuffGene"): Access @CDS slot
- promoters** signature(object = "CuffGene"): Access @CDS slot
- relCDS** signature(object = "CuffGene"): Access @CDS slot
- splicing** signature(object = "CuffGene"): Access @CDS slot
- features** signature(object = "CuffGene"): Access @features slot

Note

None.

Author(s)

Loyal A. Goff

References

None.

See Also

[CuffFeature](#)

Examples

```
showClass("CuffGene")
```

CuffGeneSet-class *Class "CuffGeneSet"*

Description

A 'data' container class for all FPKM, annotation, and differential expression data (an associated features) for a given set of genes.

Objects from the Class

Objects can be created by calls of the form `new("CuffGeneSet", annotation, fpkm, diff, ...)`.

Slots

ids: Object of class "character" ~~
 isoforms: Object of class "CuffFeatureSet" ~~
 TSS: Object of class "CuffFeatureSet" ~~
 CDS: Object of class "CuffFeatureSet" ~~
 promoters: Object of class "CuffFeatureSet" ~~
 relCDS: Object of class "CuffFeatureSet" ~~
 splicing: Object of class "CuffFeatureSet" ~~
 annotation: Object of class "data.frame" ~~
 fpkm: Object of class "data.frame" ~~
 diff: Object of class "data.frame" ~~

Extends

Class "[CuffFeatureSet](#)", directly.

Methods

No methods defined with class "CuffGeneSet" in the signature.

Accessors

genes signature(object = "CuffGeneSet"): Access @genes slot
isoforms signature(object = "CuffGeneSet"): Access @isoforms slot
TSS signature(object = "CuffGeneSet"): Access @TSS slot
CDS signature(object = "CuffGeneSet"): Access @CDS slot
promoters signature(object = "CuffGeneSet"): Access @promoters slot
relCDS signature(object = "CuffGeneSet"): Access @relCDS slot
splicing signature(object = "CuffGeneSet"): Access @splicing slot

Note

None.

Author(s)

Loyal A. Goff

References

None.

See Also

[CuffFeatureSet](#)

Examples

```
showClass("CuffGeneSet")
```

CuffSet-class

Class "CuffSet"

Description

A 'pointer' class to connect to, and retrieve data from the SQLite backend database.

Objects from the Class

Objects can be created by calls of the form `new("CuffSet", DB, conditions, genes, isoforms, TSS, CDS, promoters, splicing, relCDS, ...)`. Available methods are primary accessors to retrieve CuffGeneSet or CuffGene objects for manipulation.

Slots

```
DB: Object of class "SQLiteConnection" ~~
conditions: Object of class "data.frame" ~~
genes: Object of class "CuffData" ~~
isoforms: Object of class "CuffData" ~~
phenoData: Object of class "data.frame" ~~
TSS: Object of class "CuffData" ~~
CDS: Object of class "CuffData" ~~
promoters: Object of class "CuffDist" ~~
splicing: Object of class "CuffDist" ~~
relCDS: Object of class "CuffDist" ~~
conditions: Object of class "data.frame" ~~
```

Methods

[signature(x = "CuffSet"): ...

Accessors

DB signature(object="CuffSet"): Access @DB slot

genes signature(object = "CuffSet"): Access @genes slot

isoforms signature(object = "CuffSet"): Access @isoforms slot

TSS signature(object = "CuffSet"): Access @TSS slot

CDS signature(object = "CuffSet"): Access @CDS slot

promoters signature(object = "CuffSet"): Access @promoters slot

splicing signature(object = "CuffSet"): Access @splicing slot

relCDS signature(object = "CuffSet"): Access @relCDS slot

varModel signature(object = "CuffSet"): Access varModel info

Note

None.

Author(s)

Loyal A. Goff

References

None.

See Also

None.

Examples

```
showClass("CuffSet")
```

diffData *Differential comparison data*

Description

An accessor method to retrieve differential expression data from a 'CuffData', 'CuffFeatureSet', or 'CuffFeature' object

Usage

```
## S4 method for signature 'CuffData'
diffData(object, x, y, features=FALSE)
## S4 method for signature 'CuffData'
diffTable(object, logCutoffValue=99999)
```

Arguments

object	An object of class ('CuffData' or 'CuffFeatureSet')
x	Optional, if x and y are both missing, data for all pairwise differential comparisons are returned, otherwise if x and y are sample names from the 'samples' table, than only differential data pertaining to those two samples are returned.
y	See 'x'
features	A logical value that returns all feature-level data as part of data.frame when true. object must be of class 'CuffData'.
logCutoffValue	Cutoff value for FC estimates to convert to [-]Inf values. Should never really be needed...
...	Additional arguments.

Details

None

Value

A data.frame object

Note

None

Author(s)

Loyal A. Goff

References

None

Examples

```
data(sampleData)
diff<-diffData(sampleGeneSet) #returns a dataframe of differential expression data from sample CuffGeneSet object.
```

Dimensionality Reduction

Dimensionality reduction utilities

Description

Dimensionality reduction plots for feature selection and extraction for cummeRbund

Usage

```
## S4 method for signature 'CuffData'
MDSplot(object,replicates=FALSE,logMode=TRUE,pseudocount=1.0)
## S4 method for signature 'CuffData'
PCApplot(object,x="PC1", y="PC2",replicates=FALSE,pseudocount=1.0,scale=TRUE,showPoints = TRUE,...)
```

Arguments

object	The output of class CuffData from which to draw expression estimates. (e.g. genes(cuff))
x	For PCApplot, indicates which principal component is to be presented on the x-axis (e.g. "PC1","PC2","PC3", etc)
y	See x.
pseudocount	Value added to FPKM to avoid log transformation issues.
logMode	Logical value whether or not to use log-transformed expression estimates (default: TRUE)
replicates	A logical value to indicate whether or not individual replicate expression estimates will be used.
scale	For PCApplot, a logical value passed directly to prcomp.
showPoints	For PCApplot, a logical value whether or not to display individual gene values on final PCA plot.
...	Additional passthrough arguments (may not be fully implemented yet).

Details

These methods attempt to project a matrix of expression estimates across conditions and/or replicates onto a smaller number of dimensions for feature selection, feature extraction, and can also be useful for outlier detection.

Value

A ggplot2 object.

Note

None.

Author(s)

Loyal A. Goff

References

None.

Examples

```
cuff<-readCufflinks(system.file("extdata", package="cummeRbund")) #Create CuffSet object from sample data
p<-PCAplot(genes(cuff),x="PC2",y="PC3",replicates=TRUE)
m<-MDSplot(genes(cuff),replicates=TRUE)
p #Render PCA plot
m #Render MDS plot
```

dispersionPlot

Mean count vs dispersion plot

Description

A scatter plot comparing the mean counts against the estimated dispersion for a given level of features from a cuffdiff run.

Usage

```
## S4 method for signature 'CuffData'
dispersionPlot(object)
## S4 method for signature 'CuffSet'
dispersionPlot(object)
```

Arguments

object An object of class ('CuffData')

Details

None

Value

ggplot object with geom_point layer

Note

None

Author(s)

Loyal A. Goff

References

None

Examples

```
a<-readCufflinks(system.file("extdata", package="cummeRbund")) #Create CuffSet object from sample data
genes<-genes(a) #Create CuffData object for all genes
d<-dispersionPlot(genes) #Create plot object
d #render plot object
```

distValues

distValues

Description

Returns a data.frame of distribution-level test values from a CuffDist object (@promoters, @splicing, @relCDS)

Usage

```
## S4 method for signature 'CuffDist'
distValues(object)
```

Arguments

object	An object of class 'CuffDist'
...	Additional arguments to distValues

Details

None

Value

Returns a data.frame of distribution-level test values.

Note

None

Author(s)

Loyal A. Goff

References

None

See Also

None

Examples

```
a<-readCufflinks(system.file("extdata", package="cummeRbund")) # Read cufflinks data and create CuffSet object
distValues(a@promoters) # returns data.frame of values from CuffDist object in slot 'promoters'
```

Exploratory Analysis *Methods for Exploratory Analysis in cummeRbund*

Description

Exploratory analysis methods for cummeRbund RNA-Seq data.

Usage

```
## S4 method for signature 'CuffData'
csNMF(object,k,logMode=T,pseudocount=1,maxiter=1000,replicates=FALSE,fullnames=FALSE)
## S4 method for signature 'CuffFeatureSet'
csNMF(object,k,logMode=T,pseudocount=1,maxiter=1000,replicates=FALSE,fullnames=FALSE)
```

Arguments

object	The output of class CuffData or CuffFeatureSet from which to draw expression estimates. (e.g. genes(cuff) or custom feature set via getGenes() or getFeatures())
k	rank value for factorization
logMode	Logical value whether or not to use log-transformed FPKM values. [Default: TRUE]
pseudocount	Value added to FPKM to avoid log transformation issues.
maxiter	Maximum number of iterations for factorization [Default: 1000]
replicates	A logical value to indicate whether or not individual replicate expression estimates will be used.
fullnames	Logical passthrough value to fpkmMatrix whether or not to concatenate gene_short_name with tracking_id. [Default: FALSE]

Details

csNMF is a convenience method to invoke the `nmmf()` method from `package:NMFN`. This performs non-negative matrix factorization on the provided data and can be useful for many downstream applications.

Value

csNMF returns W, H - decomposed matrices of input FPKM values. (See `package:NMFN` for details)

Note

None.

Author(s)

Loyal A. Goff

References

None.

Examples

```
data(sampleData)
csNMF(sampleGeneSet, 4)
```

expressionBarplot *Barplot*

Description

A barplot of FPKM values with confidence intervals for a given gene, set of genes, or features of a gene (e.g. isoforms, TSS, CDS, etc).

Usage

```
## S4 method for signature 'CuffFeatureSet'
expressionBarplot(object, logMode=TRUE, pseudocount=1.0, showErrorbars=TRUE, showStatus=TRUE, replica
```

Arguments

object	An object of class ('CuffFeatureSet', 'CuffGeneSet', 'CuffFeature', 'CuffGene')
logMode	A logical value whether or not to draw y-axis on log10 scale. Default = FALSE.
pseudocount	Numerical value added to each FPKM during log-transformation to avoid errors.
showErrorbars	A logical value whether or not to draw error bars. Default = TRUE
showStatus	A logical value whether or not to draw visual queues for quantification status of a given gene:condition. Default = TRUE
replicates	A logical value whether or not to plot individual replicates or aggregate condition values.
...	Additional arguments.

Details

None

Value

A ggplot2 plot object

Note

Need to implement logMode and features for this plotting method.

Author(s)

Loyal A. Goff

References

None

Examples

```
data(sampleData)
PINK1 # sample CuffFeature object
expressionBarplot(PINK1) #Barplot of PINK1 FPKM values
expressionBarplot(PINK1@isoforms) #Barplot of PINK1 FPKM values faceted by isoforms
```

expressionPlot	<i>Expression Plot</i>
----------------	------------------------

Description

A line plot (optionally with confidence intervals) detailing FPKM expression levels across conditions for a given gene(s) or feature(s)

Usage

```
## S4 method for signature 'CuffFeature'
expressionPlot(object, logMode=FALSE, pseudocount=1.0, drawSummary=FALSE, sumFun=mean_cl_boot, showErrorbars=FALSE, showStatus=TRUE, replicates=TRUE, facet=TRUE, ...)
```

Arguments

object	An object of class ('CuffFeature' or 'CuffGene')
logMode	A logical value to draw y-axis (FPKM) on log-10 scale. Default = FALSE.
pseudocount	A numeric value added to FPKM to avoid errors on log-10 transformation.
drawSummary	A logical value. Draws a 'summary' line with mean FPKM values for each condition.
sumFun	Function used to determine values for summary line. Default = mean_cl_boot
showErrorbars	A logical value whether or not to draw error bars.
showStatus	A logical value whether or not to draw visual queues for quantification status of a given gene:condition. Default = TRUE
replicates	A logical value whether or not to plot individual replicates or aggregate condition values.
facet	A logical value whether or not to facet the plot by feature id (default=TRUE).
...	Additional arguments

Details

None

Value

A ggplot2 plot object

Note

None

Author(s)

Loyal A. Goff

References

None

Examples

```
data(sampleData)
PINK1 # sample CuffFeature object
expressionPlot(PINK1) #Line plot of PINK1 FPKM values
expressionPlot(PINK1@isoforms) #Line plot of PINK1 FPKM values faceted by isoforms
```

featureNames	<i>Feature names</i>
--------------	----------------------

Description

Retrieve a vector of feature names from a 'CuffData' or 'CuffFeatureSet' object

Usage

```
## S4 method for signature 'CuffData'
featureNames(object)
```

Arguments

object An object of class ('CuffData' or 'CuffFeatureSet')

Details

None

Value

A list of feature names

Note

None

Author(s)

Loyal A. Goff

References

None

Examples

```
data(sampleData)
featureNames(sampleGeneSet)
```

features

Features

Description

Returns a data frame of features from a CuffGene object

Usage

```
## S4 method for signature 'CuffGene'  
features(object)
```

Arguments

object An object of class ('CuffGene')

Details

None

Value

A data.frame of feature-level information

Note

None

Author(s)

Loyal A. Goff

References

None

Examples

```
data(sampleData)  
features(PINK1)
```

`findGene`*findGene*

Description

A helper function to retrieve the `gene_ids` given a 'lookup' value (e.g. `gene_short_name`, `isoform_id`, etc). Utility to search for `gene_id` and `gene_short_name` given a single 'query' string (e.g. `query='pink1'` will return all genes with 'pink1' (case-insensitive) in the `gene_short_name` field.

Usage

```
## S4 method for signature 'CuffSet'  
findGene(object, query)
```

Arguments

<code>object</code>	An object of class 'CuffSet' (Primary 'pointer' object for Cufflinks data).
<code>query</code>	A character string for which you would like to retrieve corresponding <code>gene_id</code> values.

Details

None.

Value

Returns a data.frame of `gene_id` and `gene_short_name` values corresponding to genes from which 'query' matches

Note

Right now, this does not return an error if it cannot find a gene. (this is probably a bad thing...)

Author(s)

Loyal A. Goff

References

None.

Examples

```
cuff<-readCufflinks(system.file("extdata", package="cummeRbund")) #Read cufflinks data and create master CuffSet  
myQuery<-'pink1'  
findGene(cuff,myQuery) # Retrieve gene_id values for any genes matching 'pink1'
```

findSimilar	<i>findSimilar</i>
-------------	--------------------

Description

Returns a CuffGeneSet containing n genes with the most similar expression profiles to gene/profile x.

Usage

```
## S4 method for signature 'CuffSet'
findSimilar(object, x, n, distThresh, returnGeneSet=TRUE, ...)
```

Arguments

object	A object of class 'CuffSet'
x	A 'gene_id' or 'gene_short_name' from which to look up an expression profile OR a vector of expression values to compare all genes (vector must have same length and order of 'samples')
n	Number of similar genes to return
distThresh	A thresholding value on which to filter results based on JS-distance (e.g. A distThresh of 1.0 will return all genes, 0.0 will return those genes with 'perfect identity' to the gene of interest.)
returnGeneSet	A logical value whether to return a CuffGeneSet object [default] or a distance-ranked data frame of similar genes. The latter is useful if you want to explore the returned list based on distances.
...	Additional arguments to fpkmMatrix call within findSimilar (e.g. fullnames=T)

Details

By default, returns a CuffGeneSet object with n similar genes. This may change in the future.

Value

A CuffGeneSet object of n most similar genes to x.

Note

None

Author(s)

Loyal A. Goff

References

None

Examples

```
a<-readCufflinks(system.file("extdata", package="cummeRbund"))  
mySimilarGenes<-findSimilar(a,"PINK1",10)
```

fpkm-methods

Retrieve FPKM values

Description

Returns a data.frame from @FPKM slot

Details

Returns a data.frame of FPKM values.

Value

A data.frame of FPKM-level values for a set of features.

Methods

```
signature(object = "CuffData")  
signature(object = "CuffFeature")  
signature(object = "CuffFeatureSet")
```

Note

None

Author(s)

Loyal A. Goff

References

None

Examples

```
data(sampleData)  
fpkm(PINK1)
```

fpkmMatrix	<i>fpkmMatrix</i>
------------	-------------------

Description

Retrieve FPKM values as gene by condition (fpkmMatrix) or gene by replicate (repFpkmMatrix) matrix

Usage

```
## S4 method for signature 'CuffData'  
fpkmMatrix(object, fullnames=FALSE, sampleIdList)  
## S4 method for signature 'CuffData'  
repFpkmMatrix(object, fullnames=FALSE, repIdList)
```

Arguments

object	An object of class ('CuffData', 'CuffFeatureSet', 'CuffGeneSet', 'CuffGene', or 'Cuff-Feature')
fullnames	A logical value whether or not to concatenate gene_short_name and tracking_id values (easier to read labels)
sampleIdList	A vector of sample names to subset the resulting matrix.
repIdList	A vector of sample names to subset the resulting matrix.

Details

None.

Value

A feature x condition matrix of FPKM values.

Note

None

Author(s)

Loyal A. Goff

References

None.

Examples

```
data(sampleData)
fpkmMatrix(sampleGeneSet)
repFpkmMatrix(sampleGeneSet)
```

getFeatures

getFeatures

Description

Primary accessor from a CuffSet object to retrieve all related information for >1 (MANY) given FEATURES, indexed by tracking id.

Usage

```
## S4 method for signature 'CuffSet'
getFeatures(object, featureIdList, sampleIdList=NULL, level='isoforms')
```

Arguments

object	An object of class 'CuffSet' (Primary 'pointer' object for Cufflinks data).
featureIdList	A vector of 'isoform_id', 'TSS_group_id', or 'CDS_id' to identify which features for which you would like to retrieve all information.
sampleIdList	A vector of sample names used to subset or re-order samples in returned object
level	Feature level to be queried for significance (must be one of c('isoforms', 'TSS', 'CDS'))

Details

None.

Value

Returns a CuffFeatureSet object containing all related information for a given set of tracking_id values

Note

Right now, this does not return an error if it cannot find a gene. (this is probably a bad thing...)

Author(s)

Loyal A. Goff

References

None.

Examples

```
cuff<-readCufflinks(system.file("extdata", package="cummeRbund")) #Read cufflinks data and create master CuffSet
sample.isoform.ids<-sample(featureNames(isoforms(cuff)),10)
myGene<-getFeatures(cuff,sample.isoform.ids) # Retrieve all information for a set of 10 sampled features.
```

getGene	<i>getGene</i>
---------	----------------

Description

Primary accessor from a CuffSet object to retrieve all related information for 1 (one) given gene, indexed by gene_id or gene_short_name.

Usage

```
## S4 method for signature 'CuffSet'
getGene(object, geneId, sampleIdList=NULL)
```

Arguments

object	An object of class 'CuffSet' (Primary 'pointer' object for Cufflinks data).
geneId	A character string to identify which gene for which you would like to retrieve all information.
sampleIdList	A vector of sample names used to subset or re-order samples in returned object

Details

None.

Value

Returns a CuffGene object containing all related information for a given gene_id or gene_short_name

Note

Right now, this does not return an error if it cannot find a gene. (this is probably a bad thing...)

Author(s)

Loyal A. Goff

References

None.

Examples

```
a<-readCufflinks(system.file("extdata", package="cummeRbund")) #Read cufflinks data and create master CuffSet obj
myGene<-getGene(a,"PINK1") # Retrieve all information for gene "PINK1"
```

 getGeneId

getGene

Description

A helper function to retrieve the gene_ids for a given list of feature ids (e.g. isoform_ids, tss_group_ids, or CDS_ids). This should not be called directly by the user

Usage

```
## S4 method for signature 'CuffSet'
getGeneId(object, idList)
```

Arguments

object	An object of class 'CuffSet' (Primary 'pointer' object for Cufflinks data).
idList	A character string to identify the identifiers for which you would like to retrieve corresponding gene_id values.

Details

None.

Value

Returns a vector of gene_id values corresponding to genes from which idList are sub-features.

Note

Right now, this does not return an error if it cannot find a gene. (this is probably a bad thing...)

Author(s)

Loyal A. Goff

References

None.

Examples

```
cuff<-readCufflinks(system.file("extdata", package="cummeRbund")) #Read cufflinks data and create master CuffSet
sampleFeatureIds<-sample(featureNames(isoforms(cuff)),10)
correspondingGeneIds<-getGeneId(cuff,sampleFeatureIds) # Retrieve gene_id values for parent genes of sampleFeatur
```

getGenes	<i>getGenes</i>
----------	-----------------

Description

Primary accessor from a CuffSet object to retrieve all related information for >1 (MANY) given genes, indexed by gene_id or gene_short_name.

Usage

```
## S4 method for signature 'CuffSet'  
getGenes(object, geneIdList, sampleIdList=NULL)
```

Arguments

object	An object of class 'CuffSet' (Primary 'pointer' object for Cufflinks data).
geneIdList	A vector of gene_ids or gene_short_namesto identify which genes for which you would like to retrieve all information.
sampleIdList	A vector of sample names used to subset or re-order samples in returned object

Details

None.

Value

Returns a CuffGeneSet object containing all related information for a given set of gene_id or gene_short_name values

Note

Right now, this does not return an error if it cannot find a gene. (this is probably a bad thing...)

Author(s)

Loyal A. Goff

References

None.

Examples

```
a<-readCufflinks(system.file("extdata", package="cummeRbund")) #Read cufflinks data and create master CuffSet obj  
data(sampleData)  
sampleIDs  
myGene<-getGenes(a,sampleIDs) # Retrieve all information for a set of 20 'sample' genes.
```

<code>getLevels</code>	<i>getLevels</i>
------------------------	------------------

Description

Returns a list of samples as levels. This should not be called directly by user.

Usage

```
## S4 method for signature 'CuffData'  
getLevels(object)
```

Arguments

`object` An object of class 'CuffData' or 'CuffFeatureSet' or 'CuffFeature'

Details

For internal usage only.

Value

A vector of sample names as factors.

Note

None.

Author(s)

Loyal A. Goff

References

None.

`getRepLevels` *getRepLevels*

Description

Returns a list of replicate samples as levels. This should not be called directly by user.

Usage

```
## S4 method for signature 'CuffData'  
getRepLevels(object)
```

Arguments

`object` An object of class 'CuffSet' or 'CuffData'

Details

For internal usage only.

Value

A vector of replicate names as factors.

Note

None.

Author(s)

Loyal A. Goff

References

None.

 getSig

getSig

Description

Returns the identifiers of significant genes in a vector format.

Usage

```
## S4 method for signature 'CuffSet'
getSig(object,x,y,alpha=0.05,level='genes',method="BH", useCuffMTC=FALSE)
```

Arguments

object	A CuffSet object (e.g. cuff)
x	Optional argument to restrict significance results to one pairwise comparison. Must be used with a 'y' argument to specify the other half of the pair.
y	See x.
alpha	An alpha value by which to filter multiple-testing corrected q-values to determine significance
level	Feature level to be queried for significance (must be one of c('genes','isoforms','TSS','CDS'))
method	Multiple testing method to be used for correction. (default: "BH")
useCuffMTC	Logical vector whether or not to use the multiple-testing corrected q-values from the cuffdiff analysis directly, or calculate new q-values from a subset of tests.

Details

This is a convenience function to quickly retrieve vectors of identifiers for genes or features that were determined to be significantly regulated between conditions by cuffdiff. This function only returns tracking IDs that correspond to tests with an 'OK' status from cuffdiff, NOTEST values are ignored. By default getSig returns a vector of IDs for all pairwise comparisons together. If you specify an 'x' AND 'y' values as sample names, then only the features that are significant in that particular pairwise comparison are reported, after appropriate multiple testing correction of output p-values.

Value

A vector of feature IDs.

Note

None.

Author(s)

Loyal A. Goff

References

None.

Examples

```
a<-readCufflinks(system.file("extdata", package="cummeRbund")) #Read cufflinks data in sample directory and creat
mySig<-getSig(a,x='hESC',y='Fibroblasts',alpha=0.05,level='genes')
head(mySig)
```

getSigTable

getSigTable

Description

Returns the identifiers of significant genes in a test table - like format.

Usage

```
## S4 method for signature 'CuffSet'
getSigTable(object,alpha=0.05,level='genes')
```

Arguments

object	A CuffSet object (e.g. cuff)
alpha	An alpha value by which to filter multiple-testing corrected q-values to determine significance
level	Feature level to be queried for significance (must be one of c('genes','isoforms','TSS','CDS'))

Details

This is a convenience function to quickly retrieve lists of identifiers for genes or features that were determined to be significantly regulated between conditions by cuffdiff. This function only returns tracking IDs that correspond to tests with an 'OK' status from cuffdiff, NOTEST values are ignored or reported as NA. By default getSig returns a table of genes x conditions, where the column names represent the pairwise comparisons from the cuffdiff analysis. The values in the table are 1 for features that are significant for this comparison and 0 for genes that are not, any failed tests are reported as <NA>. Only includes the features that are significant in at least one comparison.

Value

A data.frame of pairwise test results.

Note

None.

Author(s)

Loyal A. Goff

References

None.

Examples

```
a<-readCufflinks(system.file("extdata", package="cummeRbund")) #Read cufflinks data in sample directory and creat  
mySigTable<-getSigTable(a,alpha=0.05,level='genes')  
head(mySigTable)
```

JSdist

Jensen-Shannon distance on columns

Description

JSdist takes a matrix of expression probabilities (calculated directly or output from `makeprobs()`) and returns a `dist` object of the pairwise Jensen-Shannon distances between columns

Usage

```
JSdist(mat,...)
```

Arguments

<code>mat</code>	A matrix of expression probabilities (e.g. from <code>makeprobs()</code>)
<code>...</code>	Passthrough argument to <code>as.dist()</code>

Details

Returns pairwise Jensen-Shannon distance (in the form of a `dist` object) for a matrix of probabilities (by column)

Value

A `dist` object of pairwise J-S distances between columns.

Note

None

Author(s)

Loyal A. Goff

References

None

Examples

```
mat<-matrix(sample(1:50,50),10)
probs<-makeprobs(mat)
js.distance<-JSdist(probs)
```

JSdistFromP	<i>Jensen-Shannon distance on rows from a pre-defined vector of probabilities</i>
-------------	---

Description

JSdist takes a matrix of expression probabilities (calculated directly or output from makeprobs()) and returns a matrix of Jensen-Shannon distances between individual rows and a specific vector of probabilities (q)

Usage

```
JSdistFromP(mat,q)
```

Arguments

mat	A matrix of expression probabilities (e.g. from makeprobs())
q	A vector of expression probabilities.

Details

Returns Jensen-Shannon distance for each row of a matrix of probabilities against a provided probability distribution (q)

Value

A vector of JS distances

Note

None

Author(s)

Loyal A. Goff

References

None

Examples

```
mat<-matrix(sample(1:50,50),10)
q<-c(100,4,72,8,19)
q<-q/sum(q)
js.distance<-JSdistFromP(mat,q)
```

JSdistVec*JSdistVec*

Description

Returns the Jensen-Shannon Distance (square root of JS divergence) between two probability vectors.

Usage

```
JSdistVec(p, q)
```

Arguments

p	A vector of probabilities
q	A vector of probabilities

Details

Should not be called directly by user.

Value

Returns the JS distance as a numeric

Note

None

Author(s)

Loyal A. Goff

References

None

Examples

```
p<-sample(1:5000,20)
q<-sample(1:5000,20)
p<-makeprobsvec(p)
q<-makeprobsvec(q)
JSdistVec(p,q)
```

makeprobs*Transform a matrix into probabilities by columns*

Description

This function takes a matrix of expression values (must be greater than 0) and returns a matrix of probabilities by column. This is a required transformation for the Jensen-Shannon distance which is a metric that operates on probabilities.

Usage

```
makeprobs(a)
```

Arguments

a A matrix of expression values (values must be greater than 0).

Details

To make a matrix of probabilities by row, use t() to transpose prior to calling makeprobs.

Value

A matrix of expression probabilities by column.

Note

None

Author(s)

Loyal A. Goff

References

None

Examples

```
myMat<-matrix(sample(1:50,50),10)
probs<-makeprobs(myMat)
```

makeprobsvec

makeprobsvec

Description

Sums a vector of numerics and divides by the sum

Usage

makeprobsvec(p)

Arguments

p A vector of numerics

Details

None

Value

A vector of probabilities

Note

Should not be called directly by user.

Author(s)

Loyal A. Goff

References

None

Examples

```
p<-sample(1:5000,20)
makeprobsvec(p)
```

MAplot

MAplot

Description

Creates an M vs A plot (Avg intensity vs log ratio) for a given pair of conditions across all fpkms

Usage

```
## S4 method for signature 'CuffData'  
MAplot(object,x,y,logMode=T,pseudocount=1,smooth=FALSE,useCount=FALSE)
```

Arguments

object	An object of class 'CuffData'.
x	Sample name from 'samples' table for comparison
y	Sample name from 'samples' table for comparison
logMode	A logical argument to log10-transform FPKM values prior to plotting.
pseudocount	Value to be added to FPKM for appropriate log transformation and clustering. (Avoids zero-based errors)
smooth	Logical argument whether or not to draw a smoothed line fit through data.
useCount	Logical argument whether or not to use mean counts instead of FPKM values.

Details

None

Value

Returns a ggplot MvsA plot object.

Note

None

Author(s)

Loyal A. Goff and Cole Trapnell

References

None.

Examples

```
a<-readCufflinks(system.file("extdata", package="cummeRbund")) #Create CuffSet object from sample data
genes<-a@genes #Create CuffData object for all 'genes'
d<-MAplot(genes,'hESC','Fibroblasts') #Create csDensity plot
d #Render plot
```

PINK1

PINK1

Description

A sample 'CuffGene' dataset

Usage

```
data(sampleData)
```

Format

PINK1 is a CuffGene object (extends CuffFeature) with all sample gene-, isoform-, TSS-, and CDS-level data for the gene 'PINK1'.

Details

Sample CuffGene data for gene 'PINK1'

Source

None

References

None

Examples

```
data(sampleData)
PINK1
```

Description

A collection of ggplot2 visualizations for quality control assessment of cuffdiff output.

- fpkmSCVPlot: A measure of cross-replicate variability, the squared coefficient of variation is a normalized measure of variance between empirical replicate FPKM values per condition, across the range of FPKM estimates.

Usage

```
## S4 method for signature 'CuffData'  
fpkmSCVPlot(object,FPKMLowerBound=1, showPool = FALSE)
```

Arguments

object	An object of class CuffData.
FPKMLowerBound	A lower limit cutoff for FPKM values from which a fit of squared Coefficient of variation (default: 1)
showPool	Logical argument whether to display variability across all replicates independent of condition (TRUE) or the cross-replicate variability for each condition (FALSE)

Details

None

Value

A ggplot2 plot object with a geom_box layer.

Note

None

Author(s)

Loyal A. Goff

References

None

Examples

```
a<-readCufflinks(system.file("extdata", package="cummeRbund")) #Read cufflinks data and create CuffSet object
genes<-a@genes #CuffData object for all genes
csBoxplot(genes)
```

readCufflinks	<i>readCufflinks</i>
---------------	----------------------

Description

This initializes the backend SQLite table and provides a DB connection for all downstream data analysis.

Usage

```
readCufflinks(dir = getwd(), dbFile = "cuffData.db", gtfFile = NULL,
runInfoFile = "run.info", repTableFile = "read_groups.info",
geneFPKM = "genes.fpkm_tracking", geneDiff = "gene_exp.diff", geneCount="genes.count_tracking", geneRep="genes.read_group_tracking",
isoformFPKM = "isoforms.fpkm_tracking", isoformDiff = "isoform_exp.diff", isoformCount="isoforms.count_tracking", isoformRep="isoforms.read_group_tracking",
TSSFPKM = "tss_groups.fpkm_tracking", TSSDiff = "tss_group_exp.diff", TSSCount="tss_groups.count_tracking", TSSRep="tss_groups.read_group_tracking",
CDSFPKM = "cds.fpkm_tracking", CDSExpDiff = "cds_exp.diff", CDSCount="cds.count_tracking", CDSRep="cds.read_group_tracking",
CDSDiff = "cds.diff",
promoterFile = "promoters.diff",
splicingFile = "splicing.diff",
varModelFile = "var_model.info",
driver = "SQLite",
genome = NULL,
rebuild = FALSE, verbose=FALSE, ...)
```

Arguments

dir	Directory in which all CuffDiff output files can be located. Defaults to current working directory.
dbFile	Name of backend database. Default is 'cuffData.db'
gtfFile	Path to .gtf file used in cuffdiff analysis. This file will be parsed to retrieve transcript model information.
runInfoFile	run.info file
repTableFile	read_groups.info file
geneFPKM	genes.fpkm_tracking file
geneDiff	gene_exp.diff file
geneCount	genes.count_tracking file
geneRep	genes.read_group_tracking file
isoformFPKM	isoforms.fpkm_tracking file
isoformDiff	isoform_exp.diff file

isoformCount	isoforms.count_tracking file
isoformRep	isoform.read_group_tracking file
TSSFPKM	tss_groups.fpkm_tracking file
TSSDiff	tss_group_exp.diff file
TSSCount	tss_groups.count_tracking file
TSSRep	tss_groups.read_group_tracking file
CDSFPKM	cds.fpkm_tracking file
CDSEXPDiff	cds_exp.diff file
CDSCount	cds.count_tracking file
CDSRep	cds.read_group_tracking file
CSDiff	cds.diff file (distribution tests on CDS)
promoterFile	promoters.diff file (distribution tests on promoters)
splicingFile	splicing.diff (distribution tests on isoforms)
varModelFile	varModel.info (emitted in cuffdiff >= v2.1)
driver	Driver for backend database. (Currently only "SQLite" is supported).
genome	A character string indicating to which genome build the .gtf annotations belong (e.g. 'hg19' or 'mm9')
rebuild	A logical argument to rebuild database backend.
verbose	A logical argument for super verbose reporting (As if it wasn't enough already!)
...	Additional arguments to readCufflinks

Details

This is the initialization function for the cummeRbund package. It creates the SQLite backend database, populates the data, and provides a connection object for all future interactions with the dataset. Once the initial build is complete, this function will default to using the database for all future sessions. **IMPORTANT:** - Each R session should begin with a call to readCufflinks to re-open the connection to the database. - Should any connectivity issues to the database arise, another call to readCufflinks should create a new connection object and repair any issue. - The database can always be rebuild (using rebuild=TRUE) from the original CuffDiff output files.

Value

A CuffSet object. A 'pointer' class that allows interaction with cufflinks/cuffdiff data via a SQLite database backend.

Note

None.

Author(s)

Loyal A. Goff

References

None.

Examples

```
a<-readCufflinks(system.file("extdata", package="cummeRbund")) #Read cufflinks data in sample directory and creat
```

repFpkm-methods

Retrieve FPKM values

Description

Returns a data.frame from @repFpkm slot

Details

Returns a data.frame of replicate FPKM values and associated statistics.

Value

A data.frame of replicate-level FPKM values and associated statistics for a set of features.

Methods

```
signature(object = "CuffData")  
signature(object = "CuffFeature")  
signature(object = "CuffFeatureSet")
```

Note

None

Author(s)

Loyal A. Goff

References

None

Examples

```
data(sampleData)  
repFpkm(PINK1)
```

replicates	<i>Get replicate sample list from CuffData object</i>
------------	---

Description

Returns a list of replicate names from a CuffData or CuffFeatureSet object

Usage

```
## S4 method for signature 'CuffData'  
replicates(object)
```

Arguments

object An object of class ('CuffSet','CuffData')

Details

None

Value

A list of replicate sample names

Note

None

Author(s)

Loyal A. Goff

References

None

See Also

None

Examples

```
a<-readCufflinks(system.file("extdata", package="cummeRbund")) #Create CuffSet object  
replicates(a@genes)
```

`runInfo`*Retrieve run parameters and information from a CuffSet object*

Description

Returns a data.frame of cuffdiff run parameters and information

Usage

```
## S4 method for signature 'CuffSet'  
runInfo(object)
```

Arguments

`object` An object of class ('CuffSet')

Details

None

Value

A data.frame of run parameters

Note

None

Author(s)

Loyal A. Goff

References

None

See Also

None

Examples

```
a<-readCufflinks(system.file("extdata", package="cummeRbund")) #Create CuffSet object  
runInfo(a)
```

sampleGeneSet	<i>sampleGeneSet</i>
---------------	----------------------

Description

A sample CuffGeneSet data set for 20 genes.

Usage

```
data(sampleData)
```

Format

sampleGeneSet is a CuffGeneSet (extends CuffFeatureSet) object containing all sample gene-, isoform-, TSS-, and CDS-level data for 20 different genes. These data were derived from a toy set of hESC-vs-iPSC-vs-Fibroblast RNA-Seq expression data.

Details

None

Source

None

References

None

Examples

```
data(sampleData)
```

sampleIDs	<i>sampleIDs</i>
-----------	------------------

Description

A vector of gene_ids used to create 'sampleGeneSet' example

Usage

```
data(sampleData)
```

Format

The format is: chr "sampleIDs"

Details

None

Source

None

References

None

Examples

```
data(sampleData)
```

samples

Get sample list from CuffData object

Description

Returns a list of sample names from a CuffData or CuffFeatureSet object

Usage

```
## S4 method for signature 'CuffData'  
samples(object)
```

Arguments

object An object of class ('CuffData', 'CuffFeatureSet', 'CuffFeature')

Details

None

Value

A list of sample names

Note

None

Author(s)

Loyal A. Goff

References

None

See Also

None

Examples

```
a<-readCufflinks(system.file("extdata", package="cummeRbund")) #Create CuffSet object
samples(a@genes)
```

shannon.entropy *Shannon entropy*

Description

Calculates the Shannon entropy for a probability distribution

Usage

```
shannon.entropy(p)
```

Arguments

p A vector of probabilities (must sum to ~1)

Details

None

Value

Returns a numeric value for the Shannon entropy of the supplied probability distribution

Note

None

Author(s)

Loyal A. Goff

References

None

Examples

```
x<-sample(1:500,50)
p<-x/sum(x)
shannon.entropy(p)
```

sigMatrix

*sigMatrix***Description**

Returns a ggplot2 plot object representing a matrix of significant features. This is a useful synopsis of all significant pairwise comparisons within the dataset.

Usage

```
## S4 method for signature 'CuffSet'
sigMatrix(object,alpha=0.05,level='genes',orderByDist=FALSE)
```

Arguments

object	An object of class CuffSet.
alpha	An alpha value by which to filter multiple-testing corrected q-values to determine significance
level	Feature level to be queried for significance (must be one of c('genes','isoforms','TSS','CDS'))
orderByDist	Logical. If TRUE then samples are re-ordered based on JS-distance from one another (fairly useless unless you have a specific need for this).

Details

Creates a matrix plot to illustrate the number of significant features of type 'level' at a given alpha from a cuffdiff run.

Value

A ggplot2 plot object

Note

None

Author(s)

Loyal A. Goff

References

None

Examples

```
a<-readCufflinks(system.file("extdata", package="cummeRbund")) #Create CuffSet object from sample data
d<-sigMatrix(a) #Create csDensity plot
d #Render plot
```

Index

- * **JS**
 - JSdist, [52](#)
 - JSdistFromP, [53](#)
- * **Jensen-Shannon**
 - csDistHeat, [14](#)
 - JSdist, [52](#)
 - JSdistFromP, [53](#)
- * **classes**
 - CuffData-class, [20](#)
 - CuffDist-class, [21](#)
 - CuffFeature-class, [22](#)
 - CuffFeatureSet-class, [24](#)
 - CuffGene-class, [25](#)
 - CuffGeneSet-class, [27](#)
 - CuffSet-class, [28](#)
- * **datasets**
 - csCluster, [10](#)
 - csSpecificity, [18](#)
 - PINK1, [58](#)
 - sampleGeneSet, [65](#)
 - sampleIDs, [65](#)
- * **distance**
 - csDistHeat, [14](#)
 - JSdist, [52](#)
 - JSdistFromP, [53](#)
- * **heatmap**
 - csDendro, [12](#)
 - csDistHeat, [14](#)
 - csHeatmap, [15](#)
 - MPlot, [57](#)
- * **metric**
 - JSdist, [52](#)
 - JSdistFromP, [53](#)
- * **package**
 - cummeRbund-package, [3](#)
- [, CuffSet-method (CuffSet-class), [28](#)
- addFeatures, [5](#)
- addFeatures, CuffData-method (addFeatures), [5](#)
- addFeatures, CuffSet-method (addFeatures), [5](#)
- annotation (CuffFeatureSet-class), [24](#)
- annotation, CuffData-method (CuffData-class), [20](#)
- annotation, CuffFeature-method (CuffFeature-class), [22](#)
- annotation, CuffFeatureSet-method (CuffFeatureSet-class), [24](#)
- CDS (CuffSet-class), [28](#)
- CDS, CuffGene-method (CuffGene-class), [25](#)
- CDS, CuffGeneSet-method (CuffGeneSet-class), [27](#)
- CDS, CuffSet-method (CuffSet-class), [28](#)
- conditions (CuffSet-class), [28](#)
- conditions, CuffSet-method (CuffSet-class), [28](#)
- count (count-methods), [7](#)
- count, CuffData-method (count-methods), [7](#)
- count, CuffFeature-method (count-methods), [7](#)
- count, CuffFeatureSet-method (count-methods), [7](#)
- count-methods, [7](#)
- countMatrix, [8](#)
- countMatrix, CuffData-method (countMatrix), [8](#)
- countMatrix, CuffFeatureSet-method (countMatrix), [8](#)
- csBoxplot, [9](#)
- csBoxplot, CuffData-method (csBoxplot), [9](#)
- csCluster, [10](#)
- csCluster, CuffFeatureSet-method (csCluster), [10](#)
- csClusterPlot, [11](#)
- csDendro, [12](#)
- csDendro, CuffData-method (csDendro), [12](#)
- csDendro, CuffFeatureSet-method (csDendro), [12](#)

- csDensity, [13](#)
- csDensity, CuffData-method (csDensity), [13](#)
- csDensity, CuffFeatureSet-method (csDensity), [13](#)
- csDistHeat, [14](#)
- csDistHeat, CuffData-method (csDistHeat), [14](#)
- csDistHeat, CuffFeatureSet-method (csDistHeat), [14](#)
- csFoldChangeHeatmap (csHeatmap), [15](#)
- csFoldChangeHeatmap, CuffFeatureSet-method (csHeatmap), [15](#)
- csHeatmap, [15](#)
- csHeatmap, CuffFeatureSet-method (csHeatmap), [15](#)
- csNMF (Exploratory Analysis), [34](#)
- csNMF, CuffData-method (Exploratory Analysis), [34](#)
- csNMF, CuffFeatureSet-method (Exploratory Analysis), [34](#)
- csPie (CuffGene-class), [25](#)
- csPie, CuffGene-method (CuffGene-class), [25](#)
- csScatter, [17](#)
- csScatter, CuffData-method (csScatter), [17](#)
- csScatter, CuffFeatureSet-method (csScatter), [17](#)
- csScatterMatrix (csScatter), [17](#)
- csScatterMatrix, CuffData-method (csScatter), [17](#)
- csSpecificity, [18](#)
- csSpecificity, CuffData-method (csSpecificity), [18](#)
- csSpecificity, CuffFeatureSet-method (csSpecificity), [18](#)
- csVolcano, [19](#)
- csVolcano, CuffData-method (csVolcano), [19](#)
- csVolcano, CuffFeatureSet-method (csVolcano), [19](#)
- csVolcanoMatrix (csVolcano), [19](#)
- csVolcanoMatrix, CuffData-method (csVolcano), [19](#)
- CuffData-class, [20](#)
- CuffDist-class, [21](#)
- CuffFeature, [25](#), [26](#)
- CuffFeature-class, [22](#)
- CuffFeatureSet, [27](#), [28](#)
- CuffFeatureSet-class, [24](#)
- CuffGene, [23](#)
- CuffGene-class, [25](#)
- CuffGeneSet, [25](#)
- CuffGeneSet-class, [27](#)
- CuffSet-class, [28](#)
- cummeRbund (cummeRbund-package), [3](#)
- cummeRbund-package, [3](#)
- DB (CuffSet-class), [28](#)
- DB, CuffData-method (CuffData-class), [20](#)
- DB, CuffDist-method (CuffDist-class), [21](#)
- DB, CuffSet-method (CuffSet-class), [28](#)
- diffData, [30](#)
- diffData, CuffData-method (diffData), [30](#)
- diffData, CuffFeature-method (CuffFeature-class), [22](#)
- diffData, CuffFeatureSet-method (CuffFeatureSet-class), [24](#)
- diffTable (diffData), [30](#)
- diffTable, CuffData-method (diffData), [30](#)
- diffTable, CuffFeatureSet-method (diffData), [30](#)
- dim, CuffData-method (CuffData-class), [20](#)
- dim, CuffDist-method (CuffDist-class), [21](#)
- Dimensionality Reduction, [31](#)
- dispersionPlot, [32](#)
- dispersionPlot, CuffData-method (dispersionPlot), [32](#)
- dispersionPlot, CuffSet-method (dispersionPlot), [32](#)
- distValues, [33](#)
- distValues, CuffDist-method (distValues), [33](#)
- Exploratory Analysis, [34](#)
- expressionBarplot, [35](#)
- expressionBarplot, CuffFeature-method (expressionBarplot), [35](#)
- expressionBarplot, CuffFeatureSet-method (expressionBarplot), [35](#)
- expressionPlot, [37](#)
- expressionPlot, CuffFeature-method (expressionPlot), [37](#)
- expressionPlot, CuffFeatureSet-method (expressionPlot), [37](#)

- featureNames, 38
- featureNames, CuffData-method (featureNames), 38
- featureNames, CuffFeatureSet-method (CuffFeatureSet-class), 24
- features, 39
- features, CuffFeatureSet-method (CuffFeatureSet-class), 24
- features, CuffGene-method (features), 39
- findGene, 40
- findGene, CuffSet-method (findGene), 40
- findSimilar, 41
- findSimilar, CuffSet-method (findSimilar), 41
- fpkm (fpkm-methods), 42
- fpkm, CuffData-method (fpkm-methods), 42
- fpkm, CuffFeature-method (fpkm-methods), 42
- fpkm, CuffFeatureSet-method (fpkm-methods), 42
- fpkm-methods, 42
- fpkmMatrix, 43
- fpkmMatrix, CuffData-method (fpkmMatrix), 43
- fpkmMatrix, CuffFeature-method (CuffFeature-class), 22
- fpkmMatrix, CuffFeatureSet-method (fpkmMatrix), 43
- fpkmSCVPlot (QCplots), 59
- fpkmSCVPlot, CuffData-method (QCplots), 59

- genePlot (CuffGene-class), 25
- genePlot, CuffGene-method (CuffGene-class), 25
- genes (CuffSet-class), 28
- genes, CuffGene-method (CuffGene-class), 25
- genes, CuffGeneSet-method (CuffGeneSet-class), 27
- genes, CuffSet-method (CuffSet-class), 28
- getFeatures, 44
- getFeatures, CuffData-method (CuffData-class), 20
- getFeatures, CuffSet-method (getFeatures), 44
- getGene, 45
- getGene, CuffSet-method (getGene), 45
- getGeneId, 46
- getGeneId, CuffSet-method (getGeneId), 46
- getGenes, 47
- getGenes, CuffSet-method (getGenes), 47
- getLevels, 48
- getLevels, CuffData-method (getLevels), 48
- getLevels, CuffSet-method (getLevels), 48
- getRepLevels, 49
- getRepLevels, CuffData-method (getRepLevels), 49
- getRepLevels, CuffSet-method (getRepLevels), 49
- getSig, 50
- getSig, CuffSet-method (getSig), 50
- getSigTable, 51
- getSigTable, CuffSet-method (getSigTable), 51

- isoforms (CuffSet-class), 28
- isoforms, CuffGene-method (CuffGene-class), 25
- isoforms, CuffGeneSet-method (CuffGeneSet-class), 27
- isoforms, CuffSet-method (CuffSet-class), 28

- JSdist, 52
- JSdistFromP, 53
- JSdistVec, 54

- length, CuffFeature-method (CuffFeature-class), 22
- length, CuffFeatureSet-method (CuffFeatureSet-class), 24
- length, CuffGene-method (CuffGene-class), 25

- makeGeneRegionTrack (CuffGene-class), 25
- makeGeneRegionTrack, CuffGene-method (CuffGene-class), 25
- makeprobs, 55
- makeprobsvec, 56
- makeRnk (CuffData-class), 20
- makeRnk, CuffData-method (CuffData-class), 20

- MAplot, 57
- MAplot, CuffData-method (MAplot), 57
- MDSplot (Dimensionality Reduction), 31
- MDSplot, CuffData-method (Dimensionality Reduction), 31

- MDSplot, CuffFeatureSet-method
(Dimensionality Reduction), 31
- PCAplot (Dimensionality Reduction), 31
- PCAplot, CuffData-method
(Dimensionality Reduction), 31
- PCAplot, CuffFeatureSet-method
(Dimensionality Reduction), 31
- PINK1, 58
- promoters (CuffSet-class), 28
- promoters, CuffGene-method
(CuffGene-class), 25
- promoters, CuffGeneSet-method
(CuffGeneSet-class), 27
- promoters, CuffSet-method
(CuffSet-class), 28
- QCplots, 59
- readCufflinks, 60
- relCDS (CuffSet-class), 28
- relCDS, CuffGene-method
(CuffGene-class), 25
- relCDS, CuffGeneSet-method
(CuffGeneSet-class), 27
- relCDS, CuffSet-method (CuffSet-class),
28
- repCountMatrix (countMatrix), 8
- repCountMatrix, CuffData-method
(countMatrix), 8
- repCountMatrix, CuffFeatureSet-method
(countMatrix), 8
- repFpkm (repFpkm-methods), 62
- repFpkm, CuffData-method
(repFpkm-methods), 62
- repFpkm, CuffFeature-method
(repFpkm-methods), 62
- repFpkm, CuffFeatureSet-method
(repFpkm-methods), 62
- repFpkm-methods, 62
- repFpkmMatrix (fpkmMatrix), 43
- repFpkmMatrix, CuffData-method
(fpkmMatrix), 43
- repFpkmMatrix, CuffFeature-method
(fpkmMatrix), 43
- repFpkmMatrix, CuffFeatureSet-method
(fpkmMatrix), 43
- replicates, 63
- replicates, CuffData-method
(replicates), 63
- replicates, CuffFeature-method
(replicates), 63
- replicates, CuffFeatureSet-method
(replicates), 63
- replicates, CuffSet-method (replicates),
63
- runInfo, 64
- runInfo, CuffSet-method (runInfo), 64
- sampleGeneSet, 65
- sampleIDs, 65
- samples, 66
- samples, CuffData-method (samples), 66
- samples, CuffDist-method
(CuffDist-class), 21
- samples, CuffFeature-method
(CuffFeature-class), 22
- samples, CuffFeatureSet-method
(CuffFeatureSet-class), 24
- samples, CuffSet-method (samples), 66
- shannon.entropy, 67
- sigMatrix, 68
- sigMatrix, CuffSet-method (sigMatrix), 68
- splicing (CuffSet-class), 28
- splicing, CuffGene-method
(CuffGene-class), 25
- splicing, CuffGeneSet-method
(CuffGeneSet-class), 27
- splicing, CuffSet-method
(CuffSet-class), 28
- TSS (CuffSet-class), 28
- TSS, CuffGene-method (CuffGene-class), 25
- TSS, CuffGeneSet-method
(CuffGeneSet-class), 27
- TSS, CuffSet-method (CuffSet-class), 28
- varModel (CuffSet-class), 28
- varModel, CuffSet-method
(CuffSet-class), 28